

## Ashcroft Test Gauges 2 1/2", 3"

- Accuracy, PSI and kPa: ±0.5%; "H<sub>2</sub>O: 2.5%

PSI and kPa have a Bourdon tube and socket assembly of AISI type 316SS. Connection is made via a 1/4" male NPT lower stem.

The "H<sub>2</sub>O gauge socket is brass; connection is a standard 1/4" male NPT.



4900P-100

### ORDERING INFORMATION

DK4903P	3" Protective Cover	
CPRE24	Transcat Certified Calibration	CALL
PPRE24	Transcat Certified Plus Calibration	CALL

### SPECIFICATIONS AND ORDERING INFORMATION

	Range	Figure Interval	Minor	Catalog Number	Price
PSI 3"	0-15	1	0.1	DK4900P-15	
	0-30	2	0.2	DK4900P-30	
	0-60	5	0.3	DK4900P-60	
	0-100	10	1	DK4900P-100	
	0-150	10	1	DK4900P-150	
	0-200	20	2	DK4900P-200	
	0-300	20	2	DK4900P-300	
	0-400	50	2	DK4900P-400	
	0-600	50	5	DK4900P-600	
	0-800	100	5	DK4900P-800	
0-1000	100	10	DK4900P-1000		
kPa 3"	0-100	10	1	DK4901P-100	
	0-160	20	2	DK4901P-160	
	0-300	20	2	DK4901P-300	
	0-400	50	2	DK4901P-400	
	0-700	50	5	DK4901P-700	
	0-1100	100	10	DK4901P-1100	
	0-1400	100	10	DK4901P-1400	
	0-2000	200	20	DK4901P-2000	
	0-2800	200	20	DK4901P-2800	
	0-4000	500	20	DK4901P-4000	
0-7000	500	50	DK4901P-7000		
Vacuum	30 "Hg	2	0.2	DK4902P	
Inches of Water 2 1/2"	0-10	1	0.1	DK7114P-10	
	0-15	5	0.2	DK7114P-15	
	0-30	5	0.5	DK7114P-30	
	0-60	10	1	DK7114P-60	
	0-100	10	1	DK7114P-100	
	0-160	20	2	DK7114P-160	
	0-200	20	2	DK7114P-200	
0-300	50	5	DK7114P-300		

## U.S. Gauge Test Gauges: 3"

- Vacuum to 5000 PSI
- 1/4" MNPT Connection
- Nickel Polished Brass Case



3423P-100

### SPECIFICATIONS

Accuracy:	±0.5% of span in 30 "Hg VAC through 0-1000 PSI ±1% of span in 0-1500 PSI through 0-5000 PSI
Pressure Element:	Phosphor Bronze—30 through 1000 PSI Beryllium Copper—1500 through 5000 PSI
3422P-5 Series:	Ni-Span-C diaphragm
Connection:	1/4" MNPT low male, brass
Window:	Beveled glass
Pointer:	Knife edged; black; adjustable

### SPECIFICATIONS AND ORDERING INFORMATION

Range	Resolution	Catalog No.	Price
0-5 PSI	0.05 PSI	DK3422P-5	
0-10 PSI	0.1 PSI	DK3422P-10	
0-15 PSI	0.125 PSI	DK3422P-15	
0-30 PSI	0.1 PSI	DK3423P-30	
0-60 PSI	0.2 PSI	DK3423P-60	
0-100 PSI	0.5 PSI	DK3423P-100	
0-160 PSI	1 PSI	DK3423P-160	
0-200 PSI	1 PSI	DK3423P-200	
0-300 PSI	1 PSI	DK3423P-300	
0-600 PSI	2 PSI	DK3423P-600	
0-1000 PSI	5 PSI	DK3423P-1000	
0-1500 PSI	10 PSI	DK3423P-1500	
0-2000 PSI	10 PSI	DK3423P-2000	
0-3000 PSI	20 PSI	DK3423P-3000	
0-5000 PSI	25 PSI	DK3423P-5000	
0-30 "Hg VAC	0.25 "Hg	DK3424P	

### CALIBRATION INFORMATION

CPRE24	Transcat Certified Calibration (for Pressure Gauges)	CALL
PPRE24	Transcat Certified Plus Calibration (for Pressure Gauges)	CALL
CPRE25	Transcat Certified Calibration (for Vac/Compound Gauges)	CALL
PPRE25	Transcat Certified Plus Calibration (for Vac/Compound Gauges)	CALL

D

PRESSURE/FLOW TEST INSTRUMENTS