



Duratem[®] Thermometer Series 600A-01 Accuracy (±1% F.S.)

- Exclusive movementless design resists shock and vibration – no gears to wear or misalign resulting in increased instrument life
- Gas-operated molecular sieve
- No elevation error
- Mercury free
- One bulb size for all ranges
- ±1% full-span accuracy
- Maxivision[®] dial
- Readily available – two to three weeks delivery
- Limited five-year warranty

A high impact-resistant polished stainless steel case. Bayonet ring facilitates easy removal for glass replacement and pointer adjustment. A versatile case that enables surface or flush mounting. Available in 4½" dial size.



SELECTION TABLE

600A — 01		C01				B01		A1		L07		AK			
Table 1		Table 2				Table 3		Table 4		Table 5		Table 6			
CASE STYLE		CASE SIZE		MOUNTING				BULB STYLES*		ARMOR STYLE		LINE LENGTH		RANGES	
CODE	DESCRIPTION	CODE	SIZE	SURFACE		CONNECTION		CODE	DESCRIPTION	CODE	DESCRIPTION	CODE	LINE LENGTH	CODE	SINGLE RANGES
01	ST. ST. BAYONET RING	C01	4½"	✓		✓		B01	12" Bendable extension with ½ NPT union connection	A1	Stainless Steel Spring	L01	5'	AB	-320/200°F
		C11	4½"		✓		✓	B03	Plain bulb with rigid extension, no union			L03	10'	AE	-100/100°F
								B08	Plain bulb with rigid extension, ½ NPT union on armor			L07	20'	AG	-40/180°F
								B17	18" Bendable extension with ½ NPT union connection			L09	30'	AK	20/240°F
								B18	24" Bendable extension with ½ NPT union connection			L13	50'	AL	50/300°F
												L19	80'	AN	50/550°F
														AR	50/750°F
														AT	400/1200°F
														AY	-200/100°C
														BL	-80/40°C
														BN	-40/80°C
														BS	0/120°C
														BT	10/150°C
														BU	0/300°C
														BW	0/400°C
														BJ	200/650°C
														DUAL RANGES	
														CE	20/240°F
															0/120°C
														CF	50/550°F
															0/300°C
														DR	50/300°F
															10/150°C
														DT	-40/180°F
															-40/80°C

*Minimum recommended insertion length ("u" dimension) in liquids is 4 inches and in gases is 6 inches for standard ¾ x 3" bulb

TO ORDER THIS DURATEMP 600A-01 THERMOMETER:

Select:

	600A	01	C01	B01	A1	L07	AK	XNH
1. Case Style: Stainless Steel/Bayonet Ring	_____	Table 1	_____	_____	_____	_____	_____	_____
2. Case Size & Mounting: 4½" Surface, Lower	_____	Table 2	_____	_____	_____	_____	_____	_____
3. Bulb Style: 12" Bendable Extension with Union Connection	_____	Table 3	_____	_____	_____	_____	_____	_____
4. Armor Style: Stainless Steel Spring	_____	Table 4	_____	_____	_____	_____	_____	_____
5. Line Length: 20 feet	_____	Table 5	_____	_____	_____	_____	_____	_____
6. Temperature Range: 20/240°F	_____	Table 6	_____	_____	_____	_____	_____	_____
7. Options: Stainless Steel Tag	_____	(See Page 200)	_____	_____	_____	_____	_____	_____