



35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Clamp Meter

ZERO

HOLD

0

 \bigcirc

mA

FLUKE

771 MILLIAMP PROCESS CLAMP METER



Features include:

- Measure mA signals for PLC and control system analog I/O
- Measure 4 to 20 mA output signals from transmitters without breaking the loop
- Best in class 0.2 % accuracy
- Resolution and sensitivity to 0.01 mA
- · Hold function captures and displays changing measurements
- Dual backlit display with both mA measurement and percent of 4 to 20 mA span
- Measurement Spotlight illuminates hard to see wires in dark enclosures
- Detachable clamp with extension cable for measurements in tight locations
- Measure 10 to 50 mA signals in older control systems using the 99.9 mA range
- Automatic battery savings features
- Power, 15 minutes automatic power down
- · Backlight, 2 minutes, automatic off
- · Spotlight, 2 minutes, automatic off

Automatic battery saving features can be disabled if desired.



Specifications

Performance Specifications (1 Year)

Range/Resolution	Accuracy	Features	Note
-20.99 to +20.99 mA	0.2 % or reading + 5 counts	Zero, Hold, backlight measurement spotlight	Use for measuring and troubleshooting 4 to 20 mA signals
-21.0 to -99.9 mA +21.0 to +99.9 mA	1 % reading + 5 counts	Zero, Hold, backlight measurement spotlight	Use for measuring and troubleshooting 10 to 50 mA signals

Environmental, General Specifications

-10 °C to 55 °C	
-25 °C to 70 °C	
∮ 30 °C to 55 °C	
0 m to 2000 m	
, (2.32 in x 1.5 in x 8.35 in)	
Random 2 g, 5 Hz to 500 Hz	
1 meter drop test (except the jaw)	
0.01 % / °C	
R6, 20 hours typical	

Warranty

Three years for electronics, one year for clamp cable assembly

Ordering Information

Fluke-771 Milliamp Process Meter

Included Accessories Soft carrying case, users manual.



Fluke. Keeping your world up and running.™



Visit us at Transcat.com!

http://www.fluke.com

©2006 Fluke Corporation. All rights reserved. Printed in U.S.A. 10/2006 2772546 D-EN-N Rev A