

CASES
iM2750
 Pelican Storm Case



iM2750 Pelican Storm Case



- Four Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2750 Pelican Storm Case Configurations

Cat. #	Description
iM2750-X0001	iM2750 Pelican Storm Case
iM2750-X0000	iM2750 Storm Case (No foam)
iM2750-X0002	iM2750 Storm Case with Padded Dividers



Black



Yellow



OD Green

iM2750 Pelican Storm Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
24.60" x 19.70" x 14.40" (62.5 x 50 x 36.6 cm)	22.00" x 17.00" x 12.70" (55.9 x 43.2 x 32.2 cm)	
Lid Depth	Bottom Depth	Total Depth
2.00" (5.1 cm)	10.70" (27.2 cm)	12.70" (32.2 cm)
Interior Cubic Volume		
2.75 cubic feet (77.84 cubic decimeter)		
Weight with foam	Weight without foam	Buoyancy Max.
23.4 lbs. (10.61 kg)	18.5 lbs. (8.39 kg)	233.63 lbs. (105.97 kg)
Range Temperature	No. of Wheels	Retractable Handle
-20 / 140° F (-29 / 60° C)	2	YES

iM2750 Pelican Storm Case Certificates

- MIL-STD-810F • FED-STD-101C • ATA 300

iM2750 Pelican Storm Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-VALVE-M-B	Manual Purge Valve
iM2750-DIV	Padded Dividers
iM2750-FOAM	7 pc. Replacement Foam Set
iM27XX-BEZEL	Base Bezel Kit
iM27XX-BEZEL-LID	Lid Bezel Kit
iM27XX-UTILITYORG	Utility Organizer



35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001