


Model 4297
SMA (F) to Type N (M) Adapter**TRANSCAT**▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

**Materials**

Body: Gold Plated Beryllium Copper
Male Contact – Gold Plated Brass
Female Contact – Gold Plated Beryllium Copper
Dielectric: PTFE per L-P-403
Finish: Body and Contacts – Gold Plated per MIL-G-45204, Type II, Class 2
Marking: "Pomona 4297"

Ratings

Operating Voltage:
Shield/Earth: 30VAC/60VDC Max.
Inner Conductor/Shield: 335VRMS Max.
Operating Temperature:
-65°C to +165°C (-85°F to +329°F)
Nominal Impedance: 50 Ohms
Frequency Range: 0 – 12.4 GHz

Ordering Information

Model: 4297

TRANSCAT▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02$ " (.51 mm), $.xxx = \pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.