


Model 1236 & MG-B Minigator Test Clip Patch Cord



FEATURES:

- Features flex boots for insulation protection.
- Alligators are nickel plated for tarnish resistance.
- Alligator clip has .187" (4.75mm) max. jaw opening.
- Ideal for use as a temporary wire.

MATERIALS:

Alligator:

- Body: Steel, Nickel Plated
- Spring: Stainless Steel
- Flex Boot: Vinyl

Wire:

- (Model 1236) 20 AWG, Stranding: 41 x 36 tinned copper, PVC Insulation, .087" (2.21 mm) O.D.
Marking: "POMONA 1236-XX"
- (Model MG-B) 18 AWG, Stranding: 65 x 36 tinned copper, PVC Insulation, .144" (3.66 mm) O.D.
Marking: "POMONA MG-B-XX"

RATINGS:

- Operating Voltage: 33VRMS/70VDC MAX
- Operating Temperature: +50°C (+122°F)
- Current: 5 Amperes

ORDERING INFORMATION: XX = Length in inches

Model 1236-XX-*

Standard Lengths: 24" (60.96mm)

Additional lengths can be quoted upon request.

Model MG-B-XX-*

Standard Lengths: 12" (30.48mm), 24" (60.96mm)

Additional lengths can be quoted upon request.

* = Color of Flex Boot and Wire, -0 Black, -2 Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA