



645

Dual Input Differential Manometer

TRANSCAT

Visit us at [Transcat.com!](http://Transcat.com)

35 Vantage Point Drive Rochester, NY 14624
Call 1.800.800.5001

Features

- Differential input with ± 29 PSI range.
- Seven units of measure (mbar, kPa, PSI, mmHg, inHg, mH2O, inH2O).
- Display - 4 digit dual line with backlight
- Smooth - Stabilizes display when measuring fluctuating pressures
- Data Hold - Freezes reading on display.
- Min / Max - Records Min/Max readings
- Auto Off - Conserve battery power.

Specifications

- Measurement Range:** ± 29 psi
 - Display:** 4 Digit Dual line LCD with backlight
 - Input Type:** Dual Differential (compression fittings)
 - Resolution (max):** 0.01 psi
 - Accuracy:** $\pm 0.2\%$ Full scale + 3 digits)
 - Functions:** One Touch Zero, Data Hold, Back-light, Unit Selection, Smoothing, Auto power Off, Min / Max Record, Resolution Selection
 - Units of Measure:** 7 Units (mbar, kPa, PSI, mmHg, inHg, mH2O, inH2O)
 - Battery Type:** 9V alkaline
 - Battery Life:** 80hours (Typical)
 - Auto Power Off:** 30 minutes
- Standard Accessories (Included):** 9V alkaline battery (A009A), replacement tubing (A601)



Features