

ACCESSORIES

For Timing Devices



ALARM

Flush mounting with rear cable entry capability, works well with all GraLab timing devices.

Electronic high output alarm for warning system.

Two mounting holes in the back plate molding- 5 mm diameter on 50 mm centers.

Optional aid entry shallow base replaces the deep base if required.

A terminal block flame-retardant polyamide.

Available in White ABS Plastic.

Multiple frequencies available, continuous, slow, medium, or fast pulsing tones.

All units provided with an O-ring seal, which on standard base fits into the horn body. When base is utilized, the O-ring fits into the base.



FOOTSWITCH

Model 560 Timer Footswitch efficiently controls all electronic timers.

Compact, attractive, durable steel case includes 8" cord.

Heavy tread on treadle and skid proof base makes it user-friendly, and produces less fatigue.

Electrical rating: 7AMP, 125-250 VAC. Works with timers 450, 451, 555, and 655.



CONTACTOR

The Contactor is compatible and can be used with our complete line of GraLab timers.

Regulates the voltage of timers requiring 600 Watts of power or more.

Compact and durable, the Contactor is protected with a steel case and secure latch.

Compact size and long cord make it easy to transfer from one place to another.

Well defined, the labels found on the equipment make the product user-friendly.

The Contactor will provide the isolation and safety needed from the product to your timer.

Well equipped with a 12AMP continuous and 50AMP inrush capabilities.