


### Model 5910A Maxigrabber<sup>®</sup> Set Pincer Style



- Maxigrabber<sup>®</sup> test clip has been redesigned to meet IEC 1010-2-31. This is the latest international safety standard for test accessories.
- The long shaft is ideal for electronic, electrical and industrial applications where access to hard to reach high voltage test points is a requirement.
- The pincer can securely grab a .16" (4mm) Max. O.D. Terminal Post.
- Safety sheathed jack mates to Pomona's 5907A, 5908A and 5909A Flexible Test Leads for Digital Multi-Meter interfacing.

#### MATERIALS:

Pincher: Beryllium Copper, Nickel Plated

Plunger, Housing: Nylon 6 (Fire Retardant, UL94 V-0 Rated), Color: One Black, One Red

Banana Jack: Body - Brass, Nickel Plated

Tube: Santoprene<sup>®</sup>, Color: Yellow

Compression Spring: Stainless Steel

#### RATING:

IEC 1010, Category III, P2 Compliant

Voltage: 1,000 VRMS/DC

Current: 10 Amps. Max.

#### ORDERING INFORMATION: 5910A (Includes Set of one black and one red)

The Maxigrabber<sup>®</sup> Test Clip is also available in various Pomona DMM Test Kits.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA