

# Waterproof ExStik<sup>®</sup> II pH/Conductivity Meter

**Combination rugged Flat Surface pH electrode**  
Innovative design with flat surface technology for quick on-the-spot  
pH measurements combined with autoranging high accuracy Conductivity cell

## Features:

- Measures 5 parameters including Conductivity, TDS, Salinity, pH, and Temperature using one electrode
- 9 units of measure: pH,  $\mu\text{S}/\text{cm}$ ,  $\text{mS}/\text{cm}$ , ppm, ppt, mg/L, g/L,  $^{\circ}\text{C}$ ,  $^{\circ}\text{F}$
- Analog bargraph indicates trends
- Memory stores up to 25 labeled readings
- Adjustable Conductivity to TDS ratio from 0.4 to 1.0; 0.5 fixed Salinity ratio
- RENEW feature alerts user when electrode needs replacement
- Auto power off and low battery indicator
- Waterproof to IP57
- EC500 meter includes electrode, protective sensor cap, sample cup with cap, four 3V CR-2032 batteries, and 48" (1.2m) neckstrap.
- **Order Conductivity standards and pH buffers separately**
- EC510 Kit includes EC500, 84 $\mu\text{S}/\text{cm}$ , 1413 $\mu\text{S}/\text{cm}$ , 12880 $\mu\text{S}/\text{cm}$  Conductivity calibration standards, pH buffer pouches (1 each of 4, 7, 10pH plus rinse solution), weighted base, 3 sample cups with caps, and case — \$19 Savings



Combination flat surface pH electrode with Conductivity cell

**TRANSCAT**<sup>®</sup>  
Trust in every measure

Visit us at [Transcat.com](http://Transcat.com)

[sales@transcat.com](mailto:sales@transcat.com)

1.800.828.1470

## Ordering Information:

- EC500 .....Waterproof ExStik<sup>®</sup> II pH/Conductivity Meter
- EC510 .....Waterproof ExStik<sup>®</sup> II pH/Conductivity Meter Kit
- EC505 .....Spare ExStik<sup>®</sup> II pH/Conductivity cell module for EC500
- EC-84-P.....84 $\mu\text{S}$  Conductivity Standard (2 bottles - 1 pint each)
- EC-1413-P.....1413 $\mu\text{S}$  Conductivity Standard (2 bottles - 1 pint each)
- EC-12880-P..12880 $\mu\text{S}$  Conductivity Standard (2 bottles - 1 pint each)
- PH4-P .....pH 4 Buffer Solution (2 bottles - 1 pint each)
- PH7-P .....pH 7 Buffer Solution (2 bottles - 1 pint each)
- PH10-P .....pH 10 Buffer Solution (2 bottles - 1 pint each)

Specifications	Range	Max Resolution	Basic Accuracy
Conductivity	0 to 199 $\mu\text{S}/\text{cm}$ , 200 to 1999 $\mu\text{S}/\text{cm}$ , 2.00 to 19.99 $\text{mS}/\text{cm}$	0.1 $\mu\text{S}/\text{cm}$	$\pm 2\%$ FS
TDS/Salinity	0 to 99.9ppm (mg/L), 100-999ppm (mg/L) 1.00 to 9.99ppt	0.1ppm (mg/L)	$\pm 2\%$ FS
pH	0.00 to 14.00pH	0.01pH	$\pm 0.01\text{pH}$
Temperature	23 $^{\circ}$ to 194 $^{\circ}\text{F}$ (-5 to 90 $^{\circ}\text{C}$ )	0.1 $^{\circ}\text{F}/^{\circ}\text{C}$	$\pm 1.8^{\circ}\text{F}/1^{\circ}\text{C}$
Waterproof	IP57		
Memory	25 datasets		
Dimensions	1.4 x 7.3 x 1.6" (36 x 186 x 41mm)		
Weight	3.8oz (110g)		

