

A compact full-purpose meter



- **27 ranges/10 functions**
- **VoltTect™ non-contact voltage detection**
- **Magne-Grip™ holster with magnetic strap**
- **Large digital display is easier to read**
- **750 V AC/ 1000 V DC**
- **2000 count resolution**
- **Resistance and continuity**
- **Battery load test with 1.5 V and 9 V capabilities**
- **MinMax record minimum and maximum values**
- **Data Hold freezes display**
- **Triple safety rating**

The new Wavetek Meterman 5XP digital multimeter provides superior features and accuracy in a smaller form factor. The 5XP has unique features such as VoltTect™ non-contact voltage (NCV)

detection and our exclusive Magne-Grip™ holster that frees both hands for work. The 5XP is the right choice for residential, commercial and general troubleshooting applications.

5XP Specifications

DC Volts

Ranges 200 mV, 2 V, 20 V, 200 V, 1000 V

Resolution 100 µV

Accuracy $\pm (1.0\% \text{ rdg} + 1 \text{ digit})$

Input impedance 10 MΩ

Overload protection Range – 200 mV: 1000 VDC/750 VAC rms (3 minutes)

Other ranges: 1000 VDC/750 VAC rms

AC Volts (45 Hz - 500 Hz)

Ranges 200 m, 2 V, 20 V, 200 V, 750 V

Resolution 100 µV

Accuracy $\pm (1.5\% \text{ rdg} + 5 \text{ digits})$

Input impedance 10 MΩ

Overload protection 200 mV range: 1000 VDC/750 VAC rms (3 minutes)

Other ranges: 1000 VDC/750 VAC rms

DC Current

Ranges 200 µA, 2 mA, 20 mA, 200 mA

Resolution 0.1 µA

Accuracy $\pm (1.5\% \text{ rdg} + 1 \text{ digit})$

Input protection 315 mA/1000 V fast blow ceramic fuse 6.3 x 32 mm on mA input

Burden voltage 300 mV max. (1 V max. on 200 mA range)

AC Current (45 Hz - 500 Hz)

Ranges 200 µA, 2 mA, 20 mA, 200 mA

Resolution 0.1 µA

Accuracy $\pm (2.0\% \text{ rdg} + 5 \text{ digits})$

Input protection 315 mA/1000 V fast blow ceramic fuse 6.3 x 32 mm on mA input

Burden voltage 300 mV max. (1 V max. on 200 mA range)

Resistance

Ranges 200 Ω, 2 kΩ, 20 kΩ, 200 kΩ, 2 MΩ, 20 MΩ

Resolution 100 mΩ

Accuracy $\pm (1.0\% \text{ rdg} + 4 \text{ digits})$ on 200 Ω to 200 kΩ ranges

$\pm (1.5\% \text{ rdg} + 4 \text{ digits})$ on 2 MΩ ranges

$\pm (2.0\% \text{ rdg} + 5 \text{ digits})$ on 20 MΩ range

Open circuit volts 0.3 Vdc typical, (3.0 Vdc on 200 Ω range)

Overload protection 1000 VDC or 750 VAC rms

Continuity

Audible indication $75 \Omega \pm 25 \Omega$

Response time 100 ms

Overload protection 1000 VDC or 750 VAC rms

5XP

A compact full-purpose meter



Magne-Grip™ holster frees both hands for work

**Wavetek Meterman.
The right tool for the job™**

Wavetek Meterman Test Tools

5XP Specifications cont.

Diode Test

Test current	1.0 mA (approximate)
Accuracy	± (1.5 % rdg + 3 dgts)
Resolution	1 mV
Open circuit volts	3.0 Vdc typical
Overload protection	1000 VDC or 750 VAC rms

Battery Test

Ranges	1.5 V, 9 V
Resolution	1 mV, 10 mV
Accuracy	± (3.5 % rdg + 2 dgts)
Loaded current	150 mA typical for 1.5 V range, 5 mA typical for 9 V range
Overload protection	1000 VDC or 750 VAC rms on 9 V range, on VΩ input 315 mA/1000 V fast blow ceramic fuse on 1.5 V range, on mA input

Non-Contact Voltage Indicator

Sense voltage 70 V to 600 VAC beeper chirps and big bright red LED comes on, works on all ranges

General Specifications

Display	3-1/2 digit liquid crystal display (LCD) with a maximum reading of 1999
Polarity	Automatic, positive implied, negative polarity indication
OVERRANGE	(OL) or (-OL) is displayed
ZERO	Automatic
LOW BATTERY INDICATION	The “+■” is displayed when the battery voltage drops below the operating level
MEASUREMENT RATE	2.5 times per second, nominal
OPERATING ENVIRONMENT	0 °C to 50 °C at <70 % R.H.
STORAGE TEMPERATURE	-20 °C to 60 °C, 0 to 80 % R.H. with battery removed from meter
ACCURACY	Stated accuracy at 23 °C ± 5 °C, <75 % relative humidity
TEMPERATURE COEFFICIENT	0.1 x (specified accuracy) per °C (0 °C to 18 °C, 28 °C to 50 °C)
ALTITUDE	6561.7 feet (2000 M)
POWER	Single standard 9 volt battery, NEDA 1604, JIS 006P, IEC 6F22
BATTERY LIFE	200 hours typical with carbon-zinc
DIMENSIONS	155 mm (H) x 72 mm (W) x 32 mm (D)
WEIGHT	Approx. 210 g including battery
SAFETY	Designed to meet IEC 1010-1, Rev-2 CAT I 1000 V, CAT II 600 V, CAT III 300 V, class 2 and pollution deg. 2 indoor use. Complies with CE, and CSA 22.2 No. 1010-1 requirements.

Auxiliary Features

MIN/MAX	Records the maximum reading in a measurement, records the minimum reading in a measurement
DATA HOLD	Freeze the latest reading on the display
mA JACK	Input warning detects wrong connection

Included Accessories

One pair test leads TL245, fuse 315 mA/1000 V (installed) P/N FP300, 9 V battery (installed), operating instructions, holster and magnet strap



TRANSCAT®

Visit us at [Transcat.com!](http://Transcat.com)