

Shimpo Tachometer, Contact

- Measurements Per Minute and Hour
- Linear and Rotational Measurements
- Length and Total Revolutions

Speed is displayed on the 5-digit LCD display. Revolutions, yards, meters, feet, and inches. 7236FST-1 shares the same basic features while offering an LED display.

Each Unit Includes: Two conical adapters (4814FST), funnel adapter (concave tip) (4815FST), 3" extension shaft (4817FST), wheel (6" FPM) (4816FST), two 1.5V alkaline AA batteries (4708E), carrying case, instruction manual, and manufacturer's NIST certificate.

TRANSCAT

▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001



ORDERING INFORMATION

	7236FST	7236FST-1
Display:	5-digit, 0.47" (12 mm) high LCD	5-digit, 0.4" (10 mm) high LED
Display Range:	0.1 to 25,000 RPM with floating decimal	
Accuracy:	±0.06 RPM: 0.1 to 999.99; ±0.6 RPM: 1000 to 9999.9; ±0.006% rdg ±1 digit: 10,000 to 25,000 RPM	
Measuring Units:	Revolutions: RPH, RPM; Feet: FPH, FPM; Miles: MPH; Yards: YPH, YPM; Inches: IPM, Meters: mPH, mPM	
Length:	m, cm in, ft, yds; Total revolutions: REV	
Memory System:	Thirteen readings are stored in memory and retained for 5 minutes (min) (last, max, min, and 10 extra measurements)	
Detection:	Optical coupler, 60 pulses/rev.	
Operating Temp:	32° to 113°F (0 to 45°C)	
Power Supply:	Two 1.5V AA alkaline batteries	
Size/Weight:	8.3 x 2.4 x 2" LWH/1 lb	

7236FST ▶

SPECIFICATIONS

TK7236FST	Contact Tachometer, LCD
TK7236FST-1	Contact Tachometer, LED
TK4814FST	Replacement Conical Adapter
TK4815FST	Replacement Funnel Adapter (Concave Tip)
TK4816FST	Replacement Master Linear Wheel (6" Circumference)
TK4817FST	Replacement 3" Extension Shaft
TK4818FST	Linear Speed Wheel (12" Circumference)
CELT71	Transcat Certified Calibration
DELT71	Transcat Certified Plus Calibration