



FEATURES:

- Ideal for connecting terminals and wire wrap post to test equipment.
- Banana Plug mates to Model #4702, 1581 or any standard Banana Jack.

MATERIALS:

Conn: 1st End - Miniature Test Clip

Material: Contact: ½ HM Beryllium Copper alloy 165 per QQ-C-533.

Spring: Stainless steel.

Finish: Gold plated per MIL-G-45204, type II, .00001/.00002.

Insulation: Molded glass filled nylon.

Operating Temperature: +102°C. (+216°F.) Max. Color matches color of wire.

Marking: "POMONA ELECTRONICS MINI-TEST CLIP."

Wire: 20 AWG, Stranding 41 x 36 tinned copper, extra flexible polyvinyl insulation, 2.21 (.087) O.D.

Color: See Ordering Information.

Marking: "POMONA 4650-XX."

Conn: 2nd End - Banana Plug

Material: Spring: one piece heat treated Beryllium Copper, Berylco 25 per QQ-C-533.

Plug Body: Brass, H.H., per QQ-B-626, Alloy 360.

Finish: Nickel plated per QQ-N-290, Class 2 (.0002 Min.).

Insulation: Polypropylene molded to plug body and wire.

RATINGS: (Entire Assembly)

Operating Temperature: +55°C. (+131°F.) Max.

Working Voltage: 300 VRMS/DC

Current: 5 Amperes Con.

ORDERING INFORMATION: Model 4650-XX.*

XX = Cable Lengths, Standard Lengths: 12" (305), 18" (457), 24" (610), 36" (914), 48" (1219) & 60" (1524). Additional lengths can be quoted upon request.

* = Color, -0 Black, -2 Red.

Ordering Example: 4650-60-2 Indicates 60" in length, color is Red

All dimensions are in inches. Tolerances (except actual) .xx = +.007"/-.01 mm, .xxx = +.007"/-.012 mm.

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

0000

000000

Pomona Electronics Inc., 10000 N. 10th Ave., Scottsdale, AZ 85258

Sales 909-469-2100 Fax 909-429-5167
Technical Assistance: 800-240-2660

PomonaACCESS 90900 (800) 444-6785 or (949) 253-3838

More drawings available at www.pomonaelectronics.com

Page 1 of 1