

Heavy Duty Dissolved Oxygen Meter

Dual display of oxygen concentration and temperature plus RS-232 PC interface

Features:

- Super large 1.4" (36mm) LCD display
- Dual display of oxygen and temperature
- Measures dissolved oxygen from 0 to 20.0mg/L and 0 to 100.0% oxygen plus temperature from 32 to 122°F (0 to 50°C)
- Automatic Temperature Compensation from 0 to 50°C via temperature probe sensor built into polarographic type oxygen probe
- Fast 0.8 second sampling time
- Recall Min/Max/Average readings
- Data Hold
- Built-in RS-232 PC serial interface with optional data acquisition software and datalogger
- Auto power off saves battery life
- Kitted complete with 0.8" (20mm) diameter probe on 13ft (4m) cable, 3 membranes, rubber holster, 9V battery and hard vinyl carrying case
- Optional Windows® Data Acquisition Software and serial cable enable user to display and capture readings on a PC, and set time intervals and alarms
- Optional battery operated Datalogger module stores over 8000 readings for later transfer to a PC

Specifications:	Dissolved Oxygen	Oxygen	Temperature
Range:	0 to 20.0 mg/L	0 to 100.0%	32 to 122°F (0 to 50°C)
Accuracy:	±0.4 mg/L	±0.7%	±0.8°C/1.5°F
Probe Compensation & Adjustment:	Salt: 0 to 39%	Altitude: 0 to 3900m	Temp: 0 to 50°C
Dimensions/Weight:	7x2.9x1.3" (178x74x33mm) / 17oz (meter only) Probe: 20mm(0.8")D 125mm(4.9")L		



Ordering Information:

407510Heavy Duty Dissolved Oxygen Kit

Accessories:

- 780417**Replacement Membranes (10/pack)
407510-PReplacement Dissolved Oxygen probe
780408KCL Solution
156119117 VAC Adaptor
156221220 VAC Adaptor

Options:

- 407001**Data Acquisition Software and cable
380340Battery operated Datalogger Module
RH300-CAL33% and 75% RH Calibration Kit



EXTECH INSTRUMENTS CORPORATION
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
Phone: 781-890-7440 • FAX 781-890-7864
ISO 9001:2000 CERTIFIED

"Make mine an Extech!"™
www.extech.com



07/26/06 - R2