



605 Digital Vacuum Gauge

APPLICATIONS

- Verify the vacuum before you change a refrigerant system.
- Prevents moisture and air being left in the system.
- Finds small leaks.



Actual size
5" x 2.5"

Turn over for
technical
information
and accessory
part numbers.

The
Value
Leader™

Features

- Measure vacuum down to 0 microns
- Reads vacuum in seven international units of measure (Microns, PSI, InHg, mBar, Pascals, Torr, and mTorr)
- Display updates every 0.5 seconds
- Auto power off after 10 minutes when vacuum above 12,000 microns (12 Torr)
- Built in hook for hanging
- Cleanable sensor
- 500 PSI overpressure



605 Digital Vacuum Gauge

SPECIFICATIONS

Sensor Type	Thermistor
Connection Type	Standard 1/4" NPT male
Vacuum Range	0 - 12,000 microns (0 1600 Pascals)
Accuracy	10% of reading ± 10 dgts
Units of Measure	Microns, PSI, InHg, mBar, Pascals, Torr, mTorr
Power Supply	9 volt alkaline battery
Operating Temp:	0° - 40°C (32° to 104°F)

TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

Distributed by:

TRANSCAT[®]

35 Vantage Point Drive
Rochester, NY 14624
1.800.800.5001



Visit us at Transcat.com!



L 605-0606

Copyright © 2006 Test Products International, Inc.