



608 Single Input Manometer

APPLICATIONS

- Adjust appliance regulators
- Setting delivery pressures
- Leakage shut-in tests
- Regulator adjustments for pressure and lock-up tests



3-YEAR
LIMITED
WARRANTY

Turn over for
technical
information
and accessory
part numbers.

The
Value
Leader™

Features

- Four units of pressure: inH2O, mbar, kPa, and psi
- Temperature compensated
- Auto power off after 20 minutes
- Backlight display
- Wall hook and magnets for no-hand use



TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

608 Single Input Manometer

SPECIFICATIONS

Contents	inH2O	mbar	kPa	psi
Range	±60	±150	±15	±2.175
Resolution	0.01 to 29.9 30.0 to 60.0	0.01 to 29.99 30.0 to 150.0	0.01 to 2.999 3.00 to 15.00	0.001 to 2.175
Accuracy	±1% F.S.	±1% F.S.	±1% F.S.	±1% F.S.
Over pressure	up to 300 mbar (120 H2O, 30kPa, 5.3psi)			
Operating Temp.	-10° to 50°C			
Battery	LR6 9V alkaline			
Battery life	200 hour(typicall)			

Distributed By:

TRANSCAT®

▶ Visit us at Transcat.com!

35 Vantage Point Drive Rochester, NY 14624
Call 1.800.800.5001

