



35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

# Addited 914 **Handheld Pneumatic Pressure Test Pump**

- Generate 95% vacuum to 375 psi (25 bar) pressure
- Portable, only 3.3 lb
- Great stability and high resolution
- Minimal maintenance
- Hand-tight quick connectors





### **OVERVIEW**

The 914 Pneumatic Pressure Test Pump is a hand operated pressure pump designed to generate pressure from 95% vacuum to 375psi (25bar). A high-quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to10 Pa (0.1 mbar). A specially designed shut-off valve makes the pressure as stable as possible during calibration. A built-in gas-liquid isolator protects the pump from moisture and dirt to reduce the need for maintenance. Two hand-tight guick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 914 is an ideal comparison test pump for pressure instruments calibration.

## **FEATURES**

- Portable:
  - Only 3.3 lb
- Adjustment Resolution

10 Pa (0.1 mbar)

High-quality screw press for fine pressure adjustment

Great Stability

A specially designed shut-off valve makes the pressure as stable as possible during calibration

- Durable and Minimal Maintenance Built-in gas-liquid isolator protects the pump from moisture and dirt
- Easy-to-use
- Hand-tight Quick Connectors

Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches

#### **SPECIFICATIONS**

- Media: Air.
- Generated Pressure Range: 95% vacuum to 375 psi (25 bar) positive pressure
- Adjustment Resolution: 10 Pa (0.1 mbar).
- Material: Ram/adapters: SST Body: SST/aluminum Seals: Buna-N
- Connection

Hand-tight connectors for both test gauge and reference gauge.

Test Gauge Connection: 1/4NPT female, 1/4BSP

female, or M20X1.5 female

Reference Gauge Connection: 1/4NPT female,

1/4BSP female, or M20X1.5 female

Dimensions


Height: 5.12" (130 mm)

Base: 9.45" (240 mm) x 4.72" (120 mm)

- Weight: 3.3 lb (1.5 kg).
- Warranty: 1 year

# **ORDERING INFORMATION**

Model Number



Accessories included

O-ring: 20 pcs Manual: 1 pc

#### **Optional Accessories**

| Model numberel | Description  |
|----------------|--|
| ADT102         | Adapters and fittings, 1/4NPT male to various male and female connection (26 pcs).   |
| ADT103         | Adapters and fittings, 1/4NPT (1/4BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs).                              |
| ADT100-HTK     | Hose test kit, 5 feet flexible hose, 8000 psi, 1/4NPT male to 1/4NPT (1/8NPT, 1/2NPT, 1/4BSP, or M20X1.5) female hand-tight quick connector. |
| 9904-914       | Carrying Case for one 914 pump and two 681 gauges or 672 calibrators   |

