

## K-Sun LABELShop® BEE3 MACHINE FEATURES

**TRANSCAT**

▶ Visit us at [Transcat.com!](http://Transcat.com!)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001



<b>Machine Dimensions</b>	7.4" wide x 2.3" high x 8.8" deep
<b>Machine Weight</b>	1.23 lbs.
<b>Print Resolution</b>	180 dpi
<b>Barcode Formats</b>	6 barcode formats: Code 39, Code 128, ITF, UPC-A, UPC-E, CODABAR
<b>LCD</b>	LCD Prompts in English or Spanish. LCD Display: 12 Characters, 2-Lines Dot Matrix STNLC
<b>Characters</b>	14 Fonts, Bitmap Fonts Installed For Print Characters. Symbols: 1,028 Special Industrial, Medical, Safety, Office, Home and General Symbols, Punctuation, Math, Arrows and More.
<b>Tape Cutter</b>	Automatic tape & heat shrink tube cutter
<b>Tape Colors</b>	60 Combinations (size, color, and shrink combinations)
<b>Memory Storage</b>	4 Files
<b>Formatting</b>	multi-line
<b>Label Length</b>	15", 90 Characters
<b>Tape and Heat Shrink Tube Supplies</b>	Two-In-One Tape: <ul style="list-style-type: none"><li>• Flexible Polyester Base for Wire and Cable Wrap.</li><li>• Polyester Provides Durability and Permanent Adhesive</li><li>• Strength for Flat Surfaces Too.</li><li>• Solves Two Requirements With One Tape.</li></ul> Tape Width Selection: 5-Widths- 1/6"(4mm), 1/4"(6mm), 3/8"(9mm), 1/2"(12mm), 3/4"(18mm) Heat Shrink Tube Selection: Polyolefin Heat Shrink Tube Material in 1/8" and 3/16" Widths, Three Color Combinations
<b>Environmental and Safety</b>	Printer Runs on Safe 6.5V DC Power <ul style="list-style-type: none"><li>• Conforms to FCC Class B Standards</li><li>• RoHS Directive: Parts Within RoHS Requirements and Standards</li><li>• Non-PVC Parts</li><li>• Low Battery Warning</li><li>• Overheat Detection and Power Shut Off</li><li>• Auto Text Storage When Power Out</li><li>• Automatic Temperature Sensor</li><li>• Battery Reversed Alarm</li><li>• Circuit Breaker</li><li>• LSAD Adapter: Meets All Requirements for California Energy Commission's Minimum Efficiency and No-Load Energy Reduction Standards</li></ul>
<b>Cable Label Function</b>	Cable Label "Quick Key" Speeds Design of Wire and Cable Labels
<b>Power</b>	Runs on Batteries- 6AA, AC Power Adapter-115-240V That Complies With California Energy Reduction Requirements & DC Auto & Truck Adapter-12V
<b>Print Technology</b>	High Durability Thermal Transfer
<b>Tape Sizes</b>	1/6", 1/4", 3/8", 1/2" and 3/4"
<b>Shrink Tube Sizes</b>	1/8" and 3/16"