

09-59

**FOR IMMEDIATE RELEASE:**

For more information:  
Larry Wilson  
Public Relations Manager  
(425) 446-5671  
[larry.wilson@fluke.com](mailto:larry.wilson@fluke.com)

## **Fluke 233 Remote Display Multimeter brings wireless technology to contact electrical measurement**

*For the first time, work in two places at once*

EVERETT, Wash. – Fluke Corporation, the global leader in portable electronic test and measurement technology, has introduced the industry's first digital multimeter with a detachable wireless display.

Designed by Fluke engineers and manufactured at the Fluke Worldwide headquarters in Everett, Wash., the Fluke 233 Digital Multimeter uses a 2.4 GHz ISM Band wireless transmitter to immediately send measurements to the detached display, improving safety and increasing productivity for today's busy industrial and commercial electricians and electronic technicians.

In addition to functioning as a highly capable multimeter, the new [Fluke 233 Remote Display Multimeter](#) gives users ultimate flexibility in unusual test situations. By simply sliding the wireless display out of the meter body, the user can place the display where it is most easily seen—up to 10 meters (33 feet) from the point of measurement—while putting the meter in the best position to take measurements. There's no more juggling of leads and the meter while stretching into tight spots. For a video demonstration, go to [www.fluke.com/233\\_DMM](http://www.fluke.com/233_DMM).

Designed for both convenience and safety, the Fluke 233 makes it easier to take measurements in hard-to-reach places, or make measurements in machines or panels that are physically separated from a limit or isolator switch. It is ideal in areas where the operator can't be close to the active measurement point, like clean rooms or hazardous areas. Making measurements without holding the meter can help users improve their visual focus on their test probes and work more safely.

**(More)**

## **Fluke 233 Remote Display Multimeter brings wireless technology to contact electrical measurements – Page 2 of 3**

The detachable wireless display lets the user:

- Find a comfortable position to view and record test data, even when the test location is hard to reach or in a dirty or noisy environment.
- View readings when the test point is across the room—or in the next room.
- See test results even when the meter is hidden behind an equipment enclosure.
- Run tests and read results at a safe distance from shock and arc flash hazards, moving machinery and other dangers.
- Separate the tasks of positioning your meter and reading test results, so you can devote full attention to each job—and work more safely.

The low-power, 2.4 GHz-ISM Band wireless signal that transmits measurement data is resistant to electromagnetic interference. The radio transmitter automatically turns on when the display is removed from the meter and off when the display is reattached. The removable display is magnetic and has a flat bottom, so it can be conveniently mounted or placed on a flat surface where it can easily be seen. When the display is attached, the Fluke 233 operates as a conventional multimeter.

The Fluke 233 will measure up to 1000 V ac and dc and up to 10A. It features a 10,000  $\mu$ F capacitance range, measures frequencies to 50 kHz and captures min/max and average readings automatically. It features a 6,000-count display and includes a built-in thermometer that enables users to take temperature readings easily without carrying a separate instrument. The meter body is powered by three AA batteries; the display has two AA batteries. Average battery life is 400 hours. An auto-off feature maximizes battery life.

The Fluke 233 is safety rated for use in CAT IV 600V/CAT III 1000 V working environments.

### **Availability**

A specification sheet on the Fluke 233 is available at [http://www.fluke.com/233\\_DMM](http://www.fluke.com/233_DMM). For more information on Fluke tools and applications, or to find the location of your nearest

**(More)**

**Fluke 233 Remote Display Multimeter brings wireless technology to contact electrical measurements – Page 3 of 3**

distributor, contact Fluke Corporation, P.O. Box 9090, Everett, WA USA 98206, call (800) 44-FLUKE (800-443-5853), fax (425) 446-5116, e-mail [fluke-info@fluke.com](mailto:fluke-info@fluke.com) or visit the Fluke Web site at <http://www.fluke.com>.

**About Fluke**

Fluke Corporation is the leader in compact, professional electronic test tools. Fluke customers are technicians, engineers, electricians, metrologists and building diagnostic professionals who install, troubleshoot, and manage industrial electrical and electronic equipment and calibration processes for quality control as well as conducting building restoration and remediation services. Fluke is a registered trademark of Fluke Corporation in the United States and/or other countries. The names of actual companies and products mentioned herein may be the trademarks of their respective owners.

# # #

**(More)**