

FLIR IR Windows Stainless Steel Series

Reduce hazardous risks during thermal and visual electrical cabinet inspections with FLIR IR Windows. Increase inspection efficiency without compromising on safety.

- Stainless steel durability for harsh or exterior environments
- Easy Installation Standard Punch Tool Compatible
- PIRma-Lock[™] locking ring technology with improved stainless steel ring
- Hinged flip open cover with integrated thumb screw
- Crystal IR Window for clear visual and thermal viewing
- No dis-similar metal concerns with stainless steel cabinets
- Increased corrosion resistance



GENERAL SPECIFICATIONS		
NEMA Environment Type	Type 4/12 (outdoor/indoor)	
Voltage Range	Any	
Automatically Grounded	Yes	
Maximum Operating Temperature	260°C	
Body Material	Stainless Steel AISI 316	
Gasket Material	Silicone	
Optic Material	Calcium Fluoride	
Hardware Material	Steel	
Compatible with All FLIR Cameras	Yes	
PIRma-Lock Installation System	Yes	
Cover and Fastener Permanently Attached	Yes	
Single-hole Installation	Yes	
Thumb Screw and Safety Screw Included	Yes	
Broadband IR - Short-, Mid-, & Longwave	Yes	
Visible Light Spectrum	Yes	
Warranty	Limited Lifetime	

RATINGS & TESTING		
UL Component Recognition (UL 50V)	Yes	
UL 50 / NEMA Environment Rating	Type 4/12	

Ordering Information

19250-200	FLIR IRW-2S 2" Stain	less Steel IR Window wit	h Calcium Fluoride Crystal
19251-200	FLIR IRW-3S 3" Stain	less Steel IR Window wit	h Calcium Fluoride Crystal
19252-200	FLIR IRW-4S 4" Stain	less Steel IR Window wit	h Calcium Fluoride Crystal



NASHUA

FLIR Systems, Inc. PH: +1 603-324-7600 PORTLAND Corporate Headquarters FLIR Systems, Inc. PH: +1 866.477.3687 CANADA

FLIR Systems, Ltd. PH: +1 800.613.0507 MEXICO/LATIN AMERICA

FLIR Systems Brasil Av. Antonio Bardella PH: +55 15 3238 8070