



# Intrinsically-Safe Magnet Probe Magnet-Ex 12

For testing solenoid valves, relays, transformers and flow-meters in Ex-hazardous areas.

Magnet-Ex 12 is a pencil sized magnet probe, designed to detect magnetic fields in hazardous areas. Within seconds it is possible to detect whether or not a solenoid valve is electrically activated.

Connection to electronic circuitry or opening of terminal boxes is rendered unnecessary.

The highly sensitive probe point of the Magnet-Ex 12 only needs to be brought near the coil of a solenoid valve, if the probe shows a red light this indicates that the magnet is activated. In the same manner tests can be carried out on flowmeters or any other equipment that is working magnetically, even when located in hazardous areas.

The Magnet-Ex 12 comes with an integral test magnet that is securely fitted in such a way that it cannot be easily lost. Using this magnet, tests can be carried out to establish the working state of both unit and batteries.

After any check the Magnet-Ex 12 will automatically switch off if it is no longer being used. This ensures a long battery life.

The clip attached to the instrument's side secures it from accidental loss and allows the maintenance engineer to easily carry it at all times.

#### **Properties:**

- highly sensitive
- no contact with test object required
- resistant to dirt

#### Indication:

• optical

## Built-in test magnet:

- for testing Magnet-Ex 12
- for battery check

## Standard delivery:

- Magnet-Ex 12
- batteries
- instruction manual





Ex-Data: Ex-designation: Il 2 G EEx ia IIC T4

EC-Certificate of conformity: PTB 01 ATEX 2018

# Technical data:

Detectable magnetic fields::

Detection: Indication: Power supply:

TRANSCAT<sup>®</sup>

Operating temperature: Storage temperature: Ingress protection: Casing material: Dimensions: Weight:

► Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

alternating, direct and permanent fields no contact with test object required optical, built-in LED 2 × LR03 (AAA) according to IEC, type approved -20°C ... +50°C -40°C ... +60°C IP 54 metal/plastic probe point 150 × Ø18 mm 60g (batteries included)