

Part No.

QTCM-3KPSIG-D

QTCM-3KPSIG-D

Perform static pressure calibrations using nitrogen with included calibration manifold, pressure gauge and hoses

Features

Item Includes

- Assembly - QTCM Assembly (QTCM)
- Gauge - 0-3000 psig Digital Pressure Gauge (GAUD-3000)
- Gauge Adapter - 1/4" female NPT x female QT, no check-valve, brass (QTHA-2FBA)
- Hose - Quick-test hose, brass hose ends, 20 ft (6.10 m) long (QTQT-HOS-20ft)
- Hose - Quick-test hose, brass hose ends, 2 ft (61 cm) long (QTQT-HOS-2ft)
- Hose Adapter - 1/4" male NPT x male QT, no check-valve, brass (QTHA-2MB0)
- Hose Adapter - 1/4" male NPT x male QT, no check-valve, brass (QTHA-2MB0)



QTCM-3KPSIG-D

Specifications

Pressure Range	0 to 3000 psi (0 to 207 bar)
Gauge Pressure Range	0 to 3000 psig
Temperature range	0 to 130 °F (-18 to 54 °C)
Gauge Temperature range	-4 to 185 °F (-20 to 85 °C)
Construction	Brass
Seal materials	Buna-N, Delrin, Teflon
Weight	2.71 lb (1.2 kg)
Dimensions	H: 7.88 in (20.02 cm) x W: 5 in (12.70 cm) x D: 3.78 in (9.60 cm)