

Part No.

XTHP-2FSA

10kpsi / 70 MPa Hydraulic hand pump, 2 Quick-test XT outlet ports, 3 ft hose, 1/4" FNPT gauge conn., 1/4" MNPT Process conn.

10kpsi / 70 MPa Hydraulic hand pump, 2 Quick-test XT outlet ports, 3 ft hose, 1/4" FNPT gauge conn., 1/4" MNPT Process conn.



XTHP-2FSA

Included Items

- Hand Pump - XTHP 10,000 psi / 70 MPa Hydraulic Pump (XTHP)
- Reference Connection - 1/4" female NPT x female Quick-test XT, stainless steel (XTHA-2FSA)
- Process Connection - 1/4" male NPT x male Quick-test XT Adapter, S.S. (XTHA-2MS0)
- Hose - Quick-test XT 10,000 psi hose, S.S. hose ends, 3ft long (XTXT-HOS-3ft)

Specs/Attributes

| | |
|-------------------|---|
| Country of origin | USA |
| Weight | 3.38 lbs / 1.53 kg |
| Dimensions | H: 5.7 in (14.48 cm) x W: 7.5 in (19.05 cm) x D: 10.6 in (26.92 cm) |

Hand Pump XTHP

| | |
|---------------------|--|
| Materials | Anodized Aluminum, Stainless Steel, Delrin, Polysulfone |
| Max Pressure | 10000 PSI / 690 bar / 69 MPa |
| Media Compatibility | Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Mineral Oil, Petroleum Based Oil, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil |
| Seal Materials | Teflon, Viton |
| Outlet Port | Male Quick-test XT, Male Quick-test XT with cap and chain |
| Pressure Media | Liquid |

Hand Pump XTHP

| | |
|----------------------------|---|
| Fine Adjustment Resolution | 0.01 PSI / 0.07 mbar / 0.07 kPa |
| Max Temperature | 140 °F / 60 °C |
| Country of origin | USA |
| Min Temperature | -15 °F / -26 °C |
| Weight | 3.12 lbs / 1.41 kg |
| Dimensions | H: 5.7 in (14.48 cm) x W: 7.5 in (19.05 cm) x D: 10.6 in (26.92 cm) |

Reference Connection XTHA-2FSA

| | |
|-------------------|---|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Stainless Steel |
| Max Pressure | 10000 PSI / 690 bar / 69 MPa |
| Max Temperature | 225 °F / 105 °C |
| Min Temperature | 0 °F / -18 °C |
| Wrench Size | 3/4 In 19 mm |
| Dimensions | H: 1.52 in (3.86 cm) x W: 0.75 in (1.91 cm) |

Process Connection XTHA-2MSO

| | |
|-------------------|--|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Stainless Steel |
| Max Pressure | 10000 PSI / 690 bar / 69 MPa |
| Max Temperature | 225 °F / 105 °C |
| Min Temperature | 0 °F / -18 °C |
| Seal Materials | Teflon, Viton |
| Wrench Size | 5/8 In 16 mm |
| Dimensions | H: 1.29 in (3.28 cm) x W: 0.63 in (1.6 cm) |

Hose XTXT-HOS-3ft

| | |
|-------------------|---|
| Burst Pressure | 40000 PSI / 2760 bar / 275 MPa |
| Color | Blue |
| Country of origin | USA |
| Fluid Media | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Inner Diameter | 0.08 In / 3.00 mm |
| Length | 3 ft / 92 cm |
| Materials | Stainless Steel |
| Max Pressure | 10000 PSI / 690 bar / 69 MPa |
| Max Temperature | 140 °F / 60 °C |
| Min Temperature | -40 °F / -40 °C |

Hose XTXT-HOS-3ft

| | |
|---------------------|-------------------|
| Minimum Bend Radius | 1.00 In / 26 mm |
| Outer Diameter | 0.24 In / 7.00 mm |
| Type | XT |