

## XTXT-HOS-8ft

Quick-test XT 10,000 psi hose, S.S. hose ends, 8ft long

10,000 psi (689 bar) working pressure Microbore hoses that provide a very quick, low volume, high pressure way of connecting to any pressure instrumentation, hand pump, calibration source or device under test

## **Features**

- · Low volume reduces the pumping effort or compressed gas usage in pressure calibration
- No thread sealant required â€" connect to adapters without wrenches, thread sealant or thread tape
- Bubble tight connections to 10000 psi (689 bar) with no moving parts reduces maintenance to almost zero
- Hose is hard to break and very flexible
- Adapt from hose to virtually any device under test with only one connection
- A corrosion resistant strain-relief on each hose end reduces wear and dramatically increases hose life
- Note that these hoses are NOT compatible with QTHA adapters. Please use XTHA adapters
- Made in USA

## **Specifications**

Length	8 ft
Pressure Range	0 to 10000 psi (0 to 689 bar)
Burst Pressure	40000 psi (2,756 bar)
End 1	Female Quick-test XT, stainless steel
End 2	Female Quick-test XT, stainless steel
Temperature range	-40 to 140 °F (-40 to 60 °C)
Outer Diameter	0.24 in (6.1 mm)
Inner Diameter	0.08 in (2.0 mm)
Minimum Bend Radius	1 in (25.4 mm)
Color	Blue
Construction	Polyamide core tube, High tensile synthetic fiber and polyamide outer cover
End materials	Stainless Steel
Fluid Media	Water, Petroleum Based Oil, Air, Inert Gas