

## Standard Features

- Capacities between 300 g and 6000 g
- Internal resolution: 1/600,000
- LCD display
- Quick response
- Accumulation, counting and percentage modes
- 13 different units of measure
- Detachable enclosed weighing chamber (in capacities ≤1 kg)
- Battery operation for up to 40 hours of continuous use (without backlight)
- Standard RS-232 interface for connecting to printer or PC
- Plastic enclosure
- AC adapter



## Approvals



## Specifications

	EQ-300^	EQ-600^	EQ-1500	EQ-3000	EQ-6000
Part #	129410	129411	129412	129413	132435
List Price	Consult	Consult	Consult	Consult	Consult
Capacity	300 g	600 g	1500 g	3000 g	6000 g
Resolution	0.01 g	0.02 g	0.05 g	0.1 g	0.2 g
Weighing Units	Gram, Carat, Ounce, Ounce Troy, Pound, Pennyweight, Grain, Momme, Hong Kong Tael, Singapore Tael, Taiwan, Tael, tola				
Operating Modes	Weighing, Percent Weighing, Parts Counting, Accumulation				
Repeatability(+/-)	0.01 g	0.02 g	0.05 g	0.1 g	0.2 g
Linearity(+/-)	0.02 g	0.04 g	0.1 g	0.2 g	0.4 g
Stabilization Time	2 seconds				
Operating Temperature	32° F to 104° F (0° C to 40° C)				
Weighing Chamber	6.7 x 5.7 x 3.1 in (170 x 145 x 80 mm)		N/A	N/A	N/A
Pan Size	Ø 4.7in (Ø 120 mm)		4.8in x 5.6in (122 mm x 142 mm)		
Dimensions	7.1 x 8.7 x 3.3in (180 x 220 x 85 mm)				
Est. Ship Weight	6.6 lb (3 kg)				
Calibration Weight	300 g	600 g	1500 g	3000 g	6000 g
Power	AC adapter (12V/500 mA); internal rechargeable battery (6V/1.2Ah)				
Warranty	One-year limited warranty				
Return Policy	Rice Lake Standard Policy				

<sup>^</sup>Weighing Chamber

**Part Number/Price**

PART #	MODEL #	CAPACITY	EST SHIP WEIGHT	PRICE
129410	EQ-300	300 g x 0.01 g	6 lb	Consult
129411	EQ-600	600 g x 0.02 g	6 lb	Consult
129412	EQ-1500	1500 g x 0.05 g	6 lb	Consult
129413	EQ-3000	3000 g x 0.1 g	6 lb	Consult
132435	EQ-6000	6000 g x 0.2 g	6 lb	Consult

**Options/Accessories**

PART #	DESCRIPTION	PRICE
41279	Printer cable, DB9M to 25-Pin M	Consult
103141	SP712 dot matrix printer, tear bar	Consult
130789	Null modem adapter DBF/M	Consult
158056	Prove statistical printer	Consult
129425	AC Adapter, 110-240 VAC	Consult
119919	AbleCable RS-232/USB cable (requires 130789)	Consult
130789	Slim line null modem adapter	Consult
131135	Aluminum case	Consult
165183	AC adapter, 110-240VAC, interchangeable plugs	Consult