Track-It™ Rugged Temperature Data Logger





35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Description

The Track-It™ Rugged Temperature Data Logger is a submersible battery powered stand alone compact data logger that records up to 64,000 samples of temperature data. The wide temperature range and stainless steel IP68 packaging make it versatile and rugged enough for the more strenuous temperature logging applications. Moisture, corrosion, and force are prevented from affecting your measurements, as well as shallow submersion. The unit is easily configured using the included Track-It™ Software. Simply connect the logger to an open USB port on your PC and the software automatically identifies the logger. Use the internal push button to start and stop recording and check status or configure the unit to start



recording immediately, start and/or stop at a predetermined time and date, or only when an alarm condition is sensed. The sample storage rate can be set from 1 sample every 2 seconds to 1 sample every 24 hours. The on board data storage is non-volatile so data will not be lost in the event of a depleted battery.

Features

- · Push button or program to start recording
- Up to 64,000 samples per record
- Alarm set points
- Small compact size
- Integral USB interface (no custom cable!)
- Interactive software (included!)
- Three year battery life (battery included!)
- N.I.S.T. calibration (optional)
- Wide temperature range –40 to 257F/125C
- High accuracy and repeatability
- Accurate internal clock (1 minute/year)
- Projected time and date of full log
- Fast data retrieval
- Two seconds to 24 hours sample rate

Typical Uses

- FDA
- Storage
- Food
- Oil and Gas
- Buildings
- Laboratories

- HVAC
- Refrigeration
- Pharmaceutical
- Transportation/Cold Chain
- Freezers
- HACCP











Track-It[™] Rugged Temperature Data Logger

Specifications

General	
Record:	Sample Rates: User configured 1 every 2 seconds to 1 every 24 hours No. of Samples: 64,000
Record Trigger:	Two independent triggers. Multiple trigger modes: Instantaneous, button control, on alarm, time and date (start and stop), day of week.
Record Mode:	Fill to end of memory, cyclic, number of samples, time duration
LED:	User programmable: Indication of alarms, recording, triggered
Button:	User programmable: Record on/off, reset alarms, view status
Alarms:	2 user programmable alarms. High or Low
Communication:	Direct USB connection via standard USB cable (included)
Software:	Track-It™ Software - Program device, view data (historic or real time), export to Excel™. Simple and advanced modes
Battery:	Battery: 1/2 AA High Temperature Model TLH-5902 or equal Life: 3 years @ 1 minute sample rate
Dimensions	3.585" (91.06mm)L x 0.787" (20mm)diameter

MeasurementTemperature Range:-40 to +125°C / -40 to 257°FAccuracy:± .25°C / .45°FResolution:0.1°C / 0.1°FClock Accuracy:± 1 minute/year



Ordering Information Model Number Description Rugged Temp Track-It Logger with battery NIST Temp NIST Calibration Certificate

Track-It™ Software

Track-It™ Software is a powerful Windows based software package that is included with every Track-It™ Data Logger. It allows for easy setup, retrieval, interpretation and export of the recorded data. Simply connect your Track-It™ data logger to an open USB port and begin communicating immediately.

Point and click to select your sample interval, alarm set points, engineering units and recording triggers.

View a numerical data table or graphical representation of data readings relative to time. Use the graph tools such as zoom, cursor, min and max to examine and analyze the record. Track-It™ Software turns your PC into a real time data acquisition system by allowing you to stream graphical or tabular data directly to your PC (capability varies by model). Use the one click export function to automatically export stored data into an Excel spreadsheet.

