# SAFECHECK 8

Bench Mounted Comprehensive Tester for the Service and Rental Industry



This tester is ideal for use in the hire and service industry.

SafeCheck 8 is a bench-mounted instrument for those who need a comprehensive tester with memory which can provide result traceability.

Operators can select one of the following tests from its clear user interface: Class I, Class II, IEC Extension Power Cord.

Equipment and tools are automatically sequenced through the test routine. The results are recorded, and information is displayed on a large clear LCD screen.

In order to eliminate potential data entry errors and to speed up the test process, the tester can also be used with a barcode reader which scans in the equipment's ID number.

SafeCheck 8 is outstanding value for money and helps you meet your safety obligations while you improving productivity.





sales@transcat.com 1.800.828.1470

# **Key Features**

- Earth / Ground Bond Test
- DC Insulation Resistance
- Leakage Test
- IEC Cord Test
- Power / Run Test
- Storage of test results
- Predefined and custom test sequences
- Link to a printer and scanner for fast and traceable testing



## **SPECIFICATION**

# Flash/Hipot Test (Class I)

Test Voltage Class I 1.25kV AC
Display Range 0.1 - 10 mA AC
Resolution 0.01mA

Accuracy +/- 5% +/- 2 digits
Pass Levels selectable up to 10mA

# Flash/Hipot Test (Class II)

Test Voltage Class II 2.5 kV AC
Display Range 0.1 - 10 mA AC.
Resolution 0.01mA

Accuracy +/- 5% +/- 2 digits
Pass Levels selectable up to 10mA

#### **DC Insulation Test**

Test Voltage 500V

Display Range  $0.1 - 99.99M\Omega$ 

Accuracy +/- 5% +/- 2 digits (up to 19.99M $\Omega$ )

#### **Earth/Ground Bond Test**

Test Voltage 6V AC (open circuit)

Test Current 25A, 10A, 4A, 100mA AC into short circuit

 $\begin{array}{ll} \text{Range} & 0.04\Omega \text{ - } 20\Omega \\ \text{Resolution} & 1\text{m}\Omega \end{array}$ 

Accuracy +/- 5% +/- 2 digits
Pass Levels user selectable

# Substitute Leakage (Short to Case Test)

Test Voltage 40V AC o/c
Display Range 0.1 - 20.0mA AC

Resolution 0.01mA

Accuracy +/- 10% +/- 2 digits (1.00 - 20mA)

Pass Levels selectable up to 15mA

# Earth Leakage

Test Voltage Mains Supply
Display Range 0.1 - 20.0mA AC

Resolution 0.01mA

Accuracy +/- 10% +/- 2 digits (1.00 - 20mA)

Pass Levels selectable up to 10mA

# Power / Run / Load Tests

Resolution 0.01kVA Measured Load 0 - 4kVA

Accuracy +/- 10 of reading, +/- 2 digits

# **Optional Extras**

#### Hardware

194A922 Barcode scanner312A912 Desk Test n Tag printer3PHA Three phase adaptor

## Software

352A910 PATGuard Elite 2 - Premier 352A920 PATGuard Pro 2 - Professional 352A930 PATGuard Lite 2 - Entry level

#### Services

Service and Calibration

#### Order Number

SC08 UK SC08 USA

SC08 UK

Package Includes Test n Tag Printer and labels

SC08 USA

Package Includes Test n Tag Printer and labels



## **IEC Power Cord Test**

Test Voltage 40V AC

Detects Good, Open, Short, Reversed

# ADDITIONAL INFORMATION

#### Mechanical

Dimensions 450W x 410H x 155D mm

Weight Approx 8.8kg

#### Electrical

Supply Voltage Selectable 115V / 230V 50 or 60Hz

Operating Temperature  $0^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$ Storage Temperature  $-10^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$ 

EN50191 Compliant when used with appropriate accessories

## **Supplied With**

HT Probe 3 pin guard link connector Earth bond clip Mains lead Instruction Manual

# SafeCheck 8 Solutions package for automation and traceability, includes:

SafeCheck 8
Desk Test n Tag printer
Barcode Scanner
1000 white labels
PATGuard Lite 2









Seaward test and measurement companies include:



