



# CERTIFICATE OF ACCREDITATION

## The ANSI National Accreditation Board

Hereby attests that

**Transcat, Inc.**  
**35 Vantage Point Drive**  
**Rochester, NY 14624**

Fulfills the requirements of

**ISO/IEC 17025:2017**

and national standards

**ANSI/NCSL Z540-1-1994 (R2002) AND**  
**ANSI/NCSL Z540.3-2006 (R2013)**

In the fields of

**CALIBRATION AND DIMENSIONAL MEASUREMENT**

This certificate is valid only when accompanied by a current scope of accreditation document.  
The current scope of accreditation can be verified at [www.anab.org](http://www.anab.org).

Jason Stine, Vice President

Expiry Date: 07 September 2027  
Certificate Number: AC-2489



This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory  
quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

**SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017**

**AND**

**ANSI/NCSL Z540-1-1994 (R2002)**

**ANSI/NCSL Z540.3-2006 (R2013)**

**Transcat, Inc.**

35 Vantage Point Drive

Rochester, NY 14624

Miguel Colom 585-352-9720

**CALIBRATION AND DIMENSIONAL MEASUREMENT**

ISO/IEC 17025 Accreditation Granted: **04 April 2025**

Certificate Number: **AC-2489** Certificate Expiry Date: **07 September 2027**

**CALIBRATION**

**Chemical Quantities**

| Parameter/Equipment      | Range                                                                        | Expanded Uncertainty of Measurement (+/-)                          | Reference Standard, Method, and/or Equipment    |
|--------------------------|------------------------------------------------------------------------------|--------------------------------------------------------------------|-------------------------------------------------|
| pH – Source <sup>1</sup> | 4 pH<br>7 pH<br>10 pH                                                        | 0.013 pH<br>0.013 pH<br>0.012 pH                                   | Comparison to Accredited pH Solutions           |
| Conductivity – Source    | 5 µS<br>10 µS<br>100 µS<br>1 000 µS<br>10 000 µS<br>100 000 µS<br>150 000 µS | 0.3 µS<br>0.3 µS<br>0.88 µS<br>4.4 µS<br>46 µS<br>420 µS<br>710 µS | Comparison to Accredited Conductivity Solutions |

## Electrical – DC/Low Frequency

| Parameter/Equipment                       | Range                                                                                                                                                      | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                              | Reference Standard, Method, and/or Equipment                                               |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Sine Wave Flatness – Measure <sup>1</sup> | Up to 3 V<br>10 Hz<br>10 Hz to 1 MHz<br>(1 to 10) MHz<br>(10 to 30) MHz<br>(30 to 50) MHz<br>(50 to 80) MHz<br>(80 to 100) MHz                             | 0.2 % of reading<br>0.11 % of reading<br>0.21 % of reading<br>0.32 % of reading<br>0.36 % of reading<br>0.48 % of reading<br>0.53 % of reading                                                                                                                         | Comparison to Thermal Voltage Converter, Keysight 3458A, Opt. 002 8.5 Digit Multimeter     |
| DC Current – Source <sup>1</sup>          | (0 to 220) $\mu$ A<br>(0.22 to 2.2) mA<br>(2.2 to 22) mA<br>(22 to 220) mA<br>(0.22 to 2.2) A                                                              | 0.004 1 % of reading + 6 nA<br>0.003 5 % of reading + 7 nA<br>0.003 5 % of reading + 40 nA<br>0.004 5 % of reading + 0.7 $\mu$ A<br>0.008 1 % of reading + 12 $\mu$ A                                                                                                  | Comparison to Fluke 5730A Multiproduct Calibrator                                          |
| DC Current – Source <sup>1</sup>          | (2.2 to 11) A                                                                                                                                              | 0.036 % of reading + 0.48 mA                                                                                                                                                                                                                                           | Comparison to Fluke 5720A Multiproduct Calibrator, Fluke 5725 Amplifier                    |
| DC Current – Source <sup>1</sup>          | (11 to 100) A                                                                                                                                              | 0.012 % of reading + 5 mA                                                                                                                                                                                                                                              | Comparison to Fluke 5520A Multiproduct Calibrator, Fluke 52120A Transconductance Amplifier |
| DC Current – Measure <sup>1</sup>         | (0 to 100) nA<br>100 nA to 1 $\mu$ A<br>(1 to 10) $\mu$ A<br>(10 to 100) $\mu$ A<br>100 $\mu$ A to 1 mA<br>(1 to 10) mA<br>(10 to 100) mA<br>100 mA to 1 A | 0.003 6 % of reading + 40 pA<br>0.002 9 % of reading + 40 pA<br>0.002 9 % of reading + 0.1 nA<br>0.002 3 % of reading + 0.8 nA<br>0.002 4 % of reading + 5 nA<br>0.002 6 % of reading + 50 nA<br>0.003 8 % of reading + 0.5 $\mu$ A<br>0.011 % of reading + 10 $\mu$ A | Comparison to Keysight 3458A, Opt. 002 8.5 Digit Multimeter                                |
| DC Current – Measure <sup>1</sup>         | (1 to 3) A<br>(3 to 10) A                                                                                                                                  | 0.14 % of reading<br>0.18 % of reading + 0.8 mA                                                                                                                                                                                                                        | Comparison to Fluke 8846A 6.5 Digit Multimeter                                             |
| DC Current – Measure <sup>1</sup>         | (1 to 10) A                                                                                                                                                | 0.047 % of reading                                                                                                                                                                                                                                                     | Comparison to L&N 4361 Current Shunt, Keysight 3458A, Opt. 002 8.5 Digit Multimeter        |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                                           | Range                                                                                                                                                                                                                                                                                                                  | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Reference Standard, Method, and/or Equipment                                                                                    |
|-------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| DC Current – Measure <sup>1</sup>                                             | Up to 100 A                                                                                                                                                                                                                                                                                                            | 0.012 % of reading + 0.58 mA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Comparison to<br>Ohms Labs CS-100<br>Precision Shunt,<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter                       |
| DC Clamp-on Ammeter<br>(Non-Toroidal Type)<br>Hall Effect Sensor <sup>1</sup> | (20 to 150) A<br>(150 to 1 000) A                                                                                                                                                                                                                                                                                      | 0.5 % of reading + 0.14 A<br>0.52 % of reading + 0.5 A                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Comparison to<br>Fluke 5520A<br>Multiproduct Calibrator,<br>Fluke 5500A/Coil<br>50-turn Coil                                    |
| DC Clamp-on Ammeter <sup>1</sup>                                              | (1 000 to 5 000) A                                                                                                                                                                                                                                                                                                     | 0.58 % of reading                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Comparison to<br>Fluke 52120A<br>Transconductance<br>Amplifier,<br>Fluke 5520A<br>Multiproduct Calibrator,<br>3 kA or 6 kA Coil |
| AC Current – Source <sup>1</sup>                                              | Up to 220 $\mu$ A<br>(10 to 20) Hz<br>(20 to 40) Hz<br>40 Hz to 1 kHz<br>(1 to 5) kHz<br>(5 to 10) kHz<br>(0.22 to 2.2) mA<br>(10 to 20) Hz<br>(20 to 40) Hz<br>40 Hz to 1 kHz<br>(1 to 5) kHz<br>(5 to 10) kHz<br>(2.2 to 22) mA<br>(10 to 20) Hz<br>(20 to 40) Hz<br>40 Hz to 1 kHz<br>(1 to 5) kHz<br>(5 to 10) kHz | 0.025 % of reading + 16 nA<br>0.02 % of reading + 10 nA<br>0.016 % of reading + 8 nA<br>0.03 % of reading + 12 nA<br>0.11 % of reading + 65 nA<br><br>0.025 % of reading + 40 nA<br>0.016 % of reading + 35 nA<br>0.012 % of reading + 35 nA<br>0.02 % of reading + 0.11 $\mu$ A<br>0.11 % of reading + 0.65 $\mu$ A<br><br>0.025 % of reading + 0.4 $\mu$ A<br>0.022 % of reading + 0.35 $\mu$ A<br>0.012 % of reading + 0.35 $\mu$ A<br>0.023 % of reading + 0.55 $\mu$ A<br>0.11 % of reading + 5 $\mu$ A | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator                                                                         |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                              | Range                                                                                                                                                                                                                 | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                                                              | Reference Standard, Method, and/or Equipment                                                              |
|------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| AC Current – Source <sup>1</sup>                                 | (22 to 220) mA<br>(10 to 20) Hz<br>(20 to 40) Hz<br>40 Hz to 1 kHz<br>(1 to 5) kHz<br>(5 to 10) kHz<br>(0.22 to 2.2) A<br>20 Hz to 1 kHz<br>(1 to 5) kHz<br>(5 to 10) kHz                                             | 0.025 % of reading + 4 $\mu$ A<br>0.022 % of reading + 3.5 $\mu$ A<br>0.014 % of reading + 2.5 $\mu$ A<br>0.022 % of reading + 3.5 $\mu$ A<br>0.11 % of reading + 10 $\mu$ A<br>0.03 % of reading + 35 $\mu$ A<br>0.05 % of reading + 80 $\mu$ A<br>0.7 % of reading + 0.16 mA                         | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator                                                   |
| AC Current – Source <sup>1</sup>                                 | (2.2 to 11) A<br>40 Hz to 1 kHz<br>(1 to 5) kHz<br>(5 to 10) kHz                                                                                                                                                      | 0.046 % of reading + 0.85 mA<br>0.095 % of reading + 0.19 mA<br>0.36 % of reading + 0.8 mA                                                                                                                                                                                                             | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator,<br>Fluke 5725 Amplifier                          |
| AC Current – Source <sup>1</sup>                                 | (11 to 20.5) A<br>(10 to 100) Hz<br>100 Hz to 1 kHz<br>(1 to 5) kHz                                                                                                                                                   | 0.097 % of reading + 3.9 mA<br>0.12 % of reading + 3.9 mA<br>2.3 % of reading + 3.9 mA                                                                                                                                                                                                                 | Comparison to<br>Fluke 5520A<br>Multiproduct Calibrator                                                   |
| AC Current – Source <sup>1</sup>                                 | (20.5 to 40) A<br>(10 to 100) Hz<br>100 Hz to 1 kHz<br>(1 to 5) kHz                                                                                                                                                   | 0.13 % of reading + 11 mA<br>0.17 % of reading + 11 mA<br>2.3 % of reading + 11 mA                                                                                                                                                                                                                     | Comparison to<br>(2) Fluke 5520A<br>Multiproduct Calibrators<br>in Parallel configuration.                |
| AC Current – Source <sup>1</sup>                                 | (10 to 65) Hz<br>(20 to 33) A<br>(33 to 40) A<br>(40 to 60) A<br>(60 to 100) A<br>(65 to 300) Hz<br>(20 to 33) A<br>(33 to 60) A<br>(60 to 100) A<br>300 Hz to 1 kHz<br>(20 to 33) A<br>(33 to 60) A<br>(60 to 100) A | 0.032 % of reading + 24 mA<br>0.04 % of reading + 36 mA<br>0.04 % of reading + 36 mA<br>0.037 % of reading + 36 mA<br>0.044 % of reading + 36 mA<br>0.052 % of reading + 45 mA<br>0.037 % of reading + 45 mA<br>0.12 % of reading + 0.12 A<br>0.12 % of reading + 0.12 A<br>0.12 % of reading + 0.12 A | Comparison to<br>Fluke 52120A<br>Transconductance<br>Amplifier,<br>Fluke 5520A<br>Multiproduct Calibrator |
| AC Current – Source <sup>1</sup><br>Extended Frequency<br>Ranges | (10 to 30) kHz<br>(29 to 330) $\mu$ A<br>(0.33 to 3.3) mA<br>(3.3 to 33) mA<br>(33 to 330) mA                                                                                                                         | 1.2 % of reading + 0.31 $\mu$ A<br>0.78 % of reading + 0.47 $\mu$ A<br>0.31 % of reading + 3.1 $\mu$ A<br>0.31 % of reading + 0.16 mA                                                                                                                                                                  | Comparison to<br>Fluke 5520A<br>Multiproduct Calibrator                                                   |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                                          | Range                                                                                                                                                                                                                                                                                                                                                            | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Reference Standard, Method, and/or Equipment                                                                                 |
|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| AC Clamp-on Ammeters (Toroidal Type)<br>Transformer Type Sensor <sup>1</sup> | (20 to 150) A<br>(45 to 65) Hz<br>(65 to 440) Hz<br>(150 to 1 000) A<br>(45 to 65) Hz<br>(65 to 440) Hz                                                                                                                                                                                                                                                          | 0.3 % of reading + 26 mA<br>0.83 % of reading + 47 mA<br>0.35 % of reading + 0.12 A<br>1.1 % of reading + 0.22 A                                                                                                                                                                                                                                                                                                                                                                                                                                            | Comparison to<br>Fluke 5520A<br>Multiproduct Calibrator,<br>Fluke 5500A/COIL<br>50-turn Coil                                 |
| AC Clamp-on Ammeters (Non-Toroidal Type)<br>Hall Effect Sensor <sup>1</sup>  | (20 to 150) A<br>(45 to 65) Hz<br>(65 to 440) Hz<br>(150 to 1 000) A<br>(45 to 65) Hz<br>(65 to 440) Hz                                                                                                                                                                                                                                                          | 0.57 % of reading + 0.26 A<br>1 % of reading + 0.29 A<br>0.6 % of reading + 0.9 A<br>1.3 % of reading + 0.92 A                                                                                                                                                                                                                                                                                                                                                                                                                                              | Comparison to<br>Fluke 5520A<br>Multiproduct Calibrator,<br>Fluke 5500A/COIL<br>50-turn Coil                                 |
| AC Clamp-on Ammeters (Non-Toroidal Type)<br>Hall Effect Sensor <sup>1</sup>  | (1 to 6) kA<br>(10 to 300) Hz<br>(1 to 2) kA<br>(300 to 440) Hz<br>(2 to 6) kA<br>(300 to 440) Hz                                                                                                                                                                                                                                                                | 0.6 % of reading<br>0.8 % of reading<br>0.66 % of reading                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Comparison to<br>Fluke 52120A<br>Transconductance Amplifier,<br>Fluke 5520A<br>Multiproduct Calibrator,<br>3 kA or 6 kA Coil |
| AC Current – Measure <sup>1</sup>                                            | Up to 100 $\mu$ A<br>(10 to 20) Hz<br>(20 to 45) Hz<br>(45 to 100) Hz<br>100 Hz to 1 kHz<br>(0.1 to 1) mA<br>(10 to 20) Hz<br>(20 to 45) Hz<br>(45 to 100) Hz<br>100 Hz to 5 kHz<br>(1 to 10) mA<br>(10 to 20) Hz<br>(20 to 45) Hz<br>(45 to 100) Hz<br>100 Hz to 5 kHz<br>(10 to 100) mA<br>(10 to 20) Hz<br>(20 to 45) Hz<br>(45 to 100) Hz<br>100 Hz to 5 kHz | 0.46 % of reading + 35 nA<br>0.17 % of reading + 35 nA<br>0.072 % of reading + 35 nA<br>0.072 % of reading + 35 nA<br>0.46 % of reading + 0.23 $\mu$ A<br>0.17 % of reading + 0.23 $\mu$ A<br>0.07 % of reading + 0.23 $\mu$ A<br>0.038 % of reading + 0.23 $\mu$ A<br>0.46 % of reading + 2.3 $\mu$ A<br>0.17 % of reading + 2.3 $\mu$ A<br>0.071 % of reading + 2.3 $\mu$ A<br>0.038 % of reading + 2.3 $\mu$ A<br>0.48 % of reading + 23 $\mu$ A<br>0.17 % of reading + 23 $\mu$ A<br>0.071 % of reading + 23 $\mu$ A<br>0.037 % of reading + 23 $\mu$ A | Comparison to<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter                                                            |



## Electrical – DC/Low Frequency

| Parameter/Equipment                                     | Range                                                                                                                                                                                                                    | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                                                                                                                               | Reference Standard, Method, and/or Equipment                                                            |
|---------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| AC Current – Measure <sup>1</sup>                       | 100 mA to 1 A<br>(10 to 20) Hz<br>(20 to 45) Hz<br>(45 to 100) Hz<br>100 Hz to 5 kHz                                                                                                                                     | 0.46 % of reading + 0.23 mA<br>0.19 % of reading + 0.23 mA<br>0.097 % of reading + 0.23 mA<br>0.12 % of reading + 0.23 mA                                                                                                                                                                                                                                               | Comparison to<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter                                       |
| AC Current – Measure <sup>1</sup>                       | (1 to 3) A<br>(3 to 5) Hz<br>(5 to 10) Hz<br>10 Hz to 5 kHz<br>(5 to 10) kHz<br>(3 to 10) A<br>(3 to 5) Hz<br>(5 to 10) Hz<br>10 Hz to 5 kHz<br>(5 to 10) kHz                                                            | 1.3 % of reading + 2 mA<br>0.41 % of reading + 2 mA<br>0.18 % of reading + 2 mA<br>0.41 % of reading + 24 mA<br>1.1 % of reading + 13 mA<br>0.41 % of reading + 7 mA<br>0.18 % of reading + 7 mA<br>0.42 % of reading + 81 mA                                                                                                                                           | Comparison to<br>Fluke 8846A<br>6.5 Digit Multimeter                                                    |
| AC Current – Measure <sup>1</sup>                       | Up to 60 Hz<br>Up to 10 A<br>(10 to 20) A<br>(20 to 40) A<br>(40 to 60) A<br>(60 to 100) A                                                                                                                               | 0.019 % of reading + 2.3 mA<br>0.02 % of reading + 2.3 mA<br>0.029 % of reading + 2.3 mA<br>0.03 % of reading + 2.3 mA<br>0.025 % of reading + 2.3 mA                                                                                                                                                                                                                   | Comparison to<br>Current Shunt,<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter                     |
| AC Current – Measure <sup>1</sup>                       | (60 to 100) Hz<br>Up to 5 A<br>(5 to 20) A<br>(20 to 60) A<br>(60 to 100) A<br>100 Hz to 1 kHz<br>Up to 100 A                                                                                                            | 0.023 % of reading + 2.3 mA<br>0.024 % of reading + 2.3 mA<br>0.032 % of reading + 2.3 mA<br>0.037 % of reading + 2.3 mA<br>0.12 % of reading + 2.3 mA                                                                                                                                                                                                                  | Comparison to<br>Ohms Labs CS-100<br>Current Shunt,<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter |
| DC Resistance – Source/Measure <sup>1</sup>             | Up to 10 $\Omega$<br>(10 to 100) $\Omega$<br>(0.1 to 1) k $\Omega$<br>(1 to 10) k $\Omega$<br>(10 to 100) k $\Omega$<br>(0.1 to 1) M $\Omega$<br>(1 to 10) M $\Omega$<br>(10 to 100) M $\Omega$<br>(0.1 to 1) G $\Omega$ | 0.001 8 % of reading + 58 $\mu\Omega$<br>0.001 5 % of reading + 0.58 m $\Omega$<br>0.001 3 % of reading + 0.58 m $\Omega$<br>0.001 2 % of reading + 5.8 m $\Omega$<br>0.001 3 % of reading + 58 m $\Omega$<br>0.002 1 % of reading + 2.3 $\Omega$<br>0.006 2 % of reading + 0.12 k $\Omega$<br>0.059 % of reading + 1.2 k $\Omega$<br>0.82 % of reading + 12 k $\Omega$ | Comparison to<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter,<br>Decade Resistor                   |
| DC Resistance – Source <sup>1</sup><br>(Fixed Artifact) | 1 m $\Omega$                                                                                                                                                                                                             | 0.12 $\mu\Omega$                                                                                                                                                                                                                                                                                                                                                        | Comparison to<br>Ohms Labs CS-100<br>Current Shunt                                                      |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                                       | Range                                                                                                                                                                                                                             | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                                                                          | Reference Standard, Method, and/or Equipment                                         |
|---------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| DC Resistance – Source <sup>1</sup><br>(Fixed Artifact)                   | 1 $\Omega$                                                                                                                                                                                                                        | 12 $\mu\Omega$                                                                                                                                                                                                                                                                                                     | Comparison to<br>Leeds & Northrup 4020-B<br>Standard Resistor                        |
| DC Resistance – Source <sup>1</sup><br>(Variable Artifact)                | 10 m $\Omega$<br>0.1 $\Omega$                                                                                                                                                                                                     | 1 $\mu\Omega$<br>10 $\mu\Omega$                                                                                                                                                                                                                                                                                    | Comparison to<br>Guideline 9200<br>Multiple Standard Resistor                        |
| DC Resistance – Source <sup>1</sup><br>(Variable Artifact)                | 1 G $\Omega$<br>10 G $\Omega$                                                                                                                                                                                                     | 5.8 M $\Omega$<br>0.12 G $\Omega$                                                                                                                                                                                                                                                                                  | Comparison to<br>Biddle Megadek,<br>High Resistance<br>Decade Box                    |
| DC Resistance – Source <sup>1</sup><br>Up to 10 kV<br>(Variable Artifact) | (100 to 200) k $\Omega$<br>(300 to 700) k $\Omega$<br>(0.8 to 1) M $\Omega$<br>(1 to 10) M $\Omega$<br>(20 to 100) M $\Omega$<br>(200 to 900) M $\Omega$<br>(1 to 9) G $\Omega$<br>(10 to 90) G $\Omega$<br>(0.1 to 1) T $\Omega$ | 0.035 % of reading<br>0.035 % of reading<br>0.035 % of reading<br>0.035 % of reading + 1.2 $\mu\Omega/V$<br>0.12 % of reading + 1.2 $\mu\Omega/V$<br>0.3 % of reading + 1.2 $\mu\Omega/V$<br>0.59 % of reading + 1.2 $\mu\Omega/V$<br>1.2 % of reading + 2.3 $\mu\Omega/V$<br>1.2 % of reading + 5.8 $\mu\Omega/V$ | Comparison to<br>IET High Resistance<br>Decade Substituter                           |
| DC Resistance – Source <sup>1</sup><br>(Fixed Artifact)                   | (0.5 to 5) kV<br>1 T $\Omega$                                                                                                                                                                                                     | 6 G $\Omega$                                                                                                                                                                                                                                                                                                       | Comparison to<br>IET Standard Resistor                                               |
| DC Resistance – Source <sup>1</sup><br>(Fixed Artifact)                   | 500 V<br>10 T $\Omega$<br>1 kV<br>10 T $\Omega$<br>2.5 kV<br>10 T $\Omega$<br>5 kV<br>10 T $\Omega$                                                                                                                               | 86 G $\Omega$<br>0.15 T $\Omega$<br>0.1 T $\Omega$<br>60 G $\Omega$                                                                                                                                                                                                                                                | Comparison to<br>IET Standard Resistors                                              |
| DC Voltage – Source <sup>1</sup>                                          | (0 to 220) mV<br>(0.22 to 2.2) V<br>(2.2 to 11) V<br>(11 to 22) V<br>(22 to 220) V                                                                                                                                                | 0.000 78 % of reading + 0.4 $\mu V$<br>0.000 5 % of reading + 0.7 $\mu V$<br>0.000 35 % of reading + 2.5 $\mu V$<br>0.000 35 % of reading + 4 $\mu V$<br>0.000 5 % of reading + 40 $\mu V$                                                                                                                         | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator                              |
| DC Voltage – Source <sup>1</sup>                                          | (220 to 1 100) V                                                                                                                                                                                                                  | 0.000 65 % of reading + 0.4 mV                                                                                                                                                                                                                                                                                     | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator,<br>Fluke 5725A<br>Amplifier |



## Electrical – DC/Low Frequency

| Parameter/Equipment                    | Range                                                                                                                                                              | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                                     | Reference Standard, Method, and/or Equipment                                              |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| DC Voltage – Measure <sup>1</sup>      | (0 to 100) mV<br>(0.1 to 1) V<br>(1 to 10) V<br>(10 to 100) V<br>(100 to 500) V<br>(500 to 800) V<br>(800 to 1 000) V                                              | 0.000 8 % of reading + 0.58 $\mu$ V<br>0.000 5 % of reading + 0.58 $\mu$ V<br>0.000 5 % of reading + 0.58 $\mu$ V<br>0.000 8 % of reading + 35 $\mu$ V<br>0.001 5 % of reading + 0.12 mV<br>0.001 8 % of reading + 0.12 mV<br>0.002 1 % of reading + 0.12 mV                  | Comparison to<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter                         |
| DC High Voltage – Measure <sup>1</sup> | (1 to 10) kV                                                                                                                                                       | 0.039 % of reading + 0.12 V                                                                                                                                                                                                                                                   | Comparison to<br>Vitrek 4700<br>Digital HV Meter                                          |
| DC High Voltage – Measure <sup>1</sup> | (10 to 20) kV<br>(20 to 35) kV                                                                                                                                     | 0.036 % of reading + 1.2 V<br>0.064 % of reading + 1.2 V                                                                                                                                                                                                                      | Comparison to<br>Vitrek 4700<br>Digital HV Meter,<br>Vitrek HVL-35<br>High Voltage Probe  |
| DC High Voltage – Measure <sup>1</sup> | (15 to 30) kV<br>(30 to 45) kV<br>(45 to 70) kV                                                                                                                    | 0.039 % of reading + 1.2 V<br>0.049 % of reading + 1.2 V<br>0.088 % of reading + 1.2 V                                                                                                                                                                                        | Comparison to<br>Vitrek 4700<br>Digital HV Meter,<br>Vitrek HVL-70<br>High Voltage Probe  |
| DC High Voltage – Measure <sup>1</sup> | (25 to 100) kV                                                                                                                                                     | 0.17 % of reading + 1.2 V                                                                                                                                                                                                                                                     | Comparison to<br>Vitrek 4700<br>Digital HV Meter,<br>Vitrek HVL-100<br>High Voltage Probe |
| AC Voltage – Source <sup>1</sup>       | Up to 2.2 mV<br>(10 to 20) Hz<br>(20 to 40) Hz<br>40 Hz to 20 kHz<br>(20 to 50) kHz<br>(50 to 100) kHz<br>(100 to 300) kHz<br>(300 to 500) kHz<br>500 kHz to 1 MHz | 0.024 % of reading + 4 $\mu$ V<br>0.009 1 % of reading + 4 $\mu$ V<br>0.008 % of reading + 4 $\mu$ V<br>0.025 % of reading + 4 $\mu$ V<br>0.05 % of reading + 5 $\mu$ V<br>0.11 % of reading + 10 $\mu$ V<br>0.14 % of reading + 20 $\mu$ V<br>0.27 % of reading + 20 $\mu$ V | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator                                   |

## Electrical – DC/Low Frequency

| Parameter/Equipment              | Range            | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment            |
|----------------------------------|------------------|-------------------------------------------|---------------------------------------------------------|
| AC Voltage – Source <sup>1</sup> | (2.2 to 22) mV   |                                           | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator |
|                                  | (10 to 20) Hz    | 0.024 % of reading + 4 $\mu$ V            |                                                         |
|                                  | (20 to 40) Hz    | 0.009 % of reading + 4 $\mu$ V            |                                                         |
|                                  | 40 Hz to 20 kHz  | 0.008 % of reading + 4 $\mu$ V            |                                                         |
|                                  | (20 to 50) kHz   | 0.02 % of reading + 4 $\mu$ V             |                                                         |
|                                  | (50 to 100) kHz  | 0.05 % of reading + 5 $\mu$ V             |                                                         |
|                                  | (100 to 300) kHz | 0.11 % of reading + 10 $\mu$ V            |                                                         |
|                                  | (300 to 500) kHz | 0.14 % of reading + 20 $\mu$ V            |                                                         |
|                                  | 500 kHz to 1 MHz | 0.27 % of reading + 20 $\mu$ V            |                                                         |
|                                  | (22 to 220) mV   |                                           |                                                         |
|                                  | (10 to 20) Hz    | 0.024 % of reading + 12 $\mu$ V           |                                                         |
|                                  | (20 to 40) Hz    | 0.009 3 % of reading + 7 $\mu$ V          |                                                         |
|                                  | 40 Hz to 20 kHz  | 0.005 9 % of reading + 7 $\mu$ V          |                                                         |
|                                  | (20 o 50) kHz    | 0.012 % of reading + 7 $\mu$ V            |                                                         |
|                                  | (50 to 100) kHz  | 0.031 % of reading + 17 $\mu$ V           |                                                         |
|                                  | (100 to 300) kHz | 0.066 % of reading + 20 $\mu$ V           |                                                         |
|                                  | (300 to 500) kHz | 0.14 % of reading + 25 $\mu$ V            |                                                         |
|                                  | 500 kHz to 1 MHz | 0.27 % of reading + 45 $\mu$ V            |                                                         |
|                                  | (0.22 to 2.2) V  |                                           |                                                         |
|                                  | (10 to 20) Hz    | 0.024 % of reading + 40 $\mu$ V           |                                                         |
|                                  | (20 to 40) Hz    | 0.009 4 % of reading + 15 $\mu$ V         |                                                         |
|                                  | 40 Hz to 20 kHz  | 0.004 6 % of reading + 8 $\mu$ V          |                                                         |
|                                  | (20 o 50) kHz    | 0.006 9 % of reading + 10 $\mu$ V         |                                                         |
|                                  | (50 to 100) kHz  | 0.008 6 % of reading + 30 $\mu$ V         |                                                         |
|                                  | (100 to 300) kHz | 0.034 % of reading + 80 $\mu$ V           |                                                         |
|                                  | (300 to 500) kHz | 0.1 % of reading + 0.2 mV                 |                                                         |
|                                  | 500 kHz to 1 MHz | 0.17 % of reading + 0.3 mV                |                                                         |
|                                  | (2.2 to 22) V    |                                           |                                                         |
|                                  | (10 to 20) Hz    | 0.024 % of reading + 0.4 mV               |                                                         |
|                                  | (20 to 40) Hz    | 0.009 3 % of reading + 0.15 mV            |                                                         |
|                                  | 40 Hz to 20 kHz  | 0.004 7 % of reading + 50 $\mu$ V         |                                                         |
|                                  | (20 o 50) kHz    | 0.007 1 % of reading + 0.1 mV             |                                                         |
|                                  | (50 to 100) kHz  | 0.008 4 % of reading + 0.2 mV             |                                                         |
|                                  | (100 to 300) kHz | 0.025 % of reading + 0.6 mV               |                                                         |
|                                  | (300 to 500) kHz | 0.1 % of reading + 2 mV                   |                                                         |
|                                  | 500 kHz to 1 MHz | 0.15 % of reading + 3.2 mV                |                                                         |

## Electrical – DC/Low Frequency

| Parameter/Equipment               | Range                                                                                                                                                                                                                                                                                                                                                                          | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Reference Standard, Method, and/or Equipment                                         |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| AC Voltage – Source <sup>1</sup>  | (22 to 220) V<br>(10 to 20) Hz<br>(20 to 40) Hz<br>40 Hz to 20 kHz<br>(20 to 50) kHz<br>(50 to 100) kHz<br>(100 to 300) kHz<br>(300 to 500) kHz<br>500 kHz to 1 MHz                                                                                                                                                                                                            | 0.024 % of reading + 4 mV<br>0.009 4 % of reading + 1.5 mV<br>0.005 5 % of reading + 0.6 mV<br>0.008 1 % of reading + 1 mV<br>0.015 % of reading + 2.5 mV<br>0.09 % of reading + 16 mV<br>0.44 % of reading + 40 mV<br>0.8 % of reading + 80 mV                                                                                                                                                                                                                                                                                                                                                                                                                                | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator                              |
| AC Voltage – Source <sup>1</sup>  | (220 to 250) V<br>(15 to 50) Hz<br>(220 to 750) V<br>(30 to 50) kHz<br>(50 to 100) kHz<br>(220 to 1 100) V<br>40 Hz to 1 kHz<br>(1 to 20) kHz<br>(20 to 30) kHz                                                                                                                                                                                                                | 0.03 % of reading + 11 mV<br><br>0.06 % of reading<br>0.23 % of reading<br><br>0.009 3 % of reading<br>0.007 3 % of reading<br>0.06 % of reading                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Comparison to<br>Fluke 5730A<br>Multiproduct Calibrator,<br>Fluke 5725A<br>Amplifier |
| AC Voltage – Measure <sup>1</sup> | Up to 10 mV<br>(1 to 40) Hz<br>40 Hz to 1 kHz<br>(1 to 20) kHz<br>(20 to 50) kHz<br>(50 to 100) kHz<br>(100 to 300) kHz<br>300 kHz to 1 MHz<br>(1 to 4) MHz<br>(10 to 100) mV<br>(1 to 40) Hz<br>40 Hz to 1 kHz<br>(1 to 20) kHz<br>(20 to 50) kHz<br>(50 to 100) kHz<br>(100 to 300) kHz<br>300 kHz to 1 MHz<br>(1 to 2) MHz<br>(2 to 4) MHz<br>(4 to 8) MHz<br>(8 to 10) MHz | 0.04 % of reading + 3.5 $\mu$ V<br>0.03 % of reading + 1.2 $\mu$ V<br>0.04 % of reading + 1.2 $\mu$ V<br>0.15 % of reading + 1.2 $\mu$ V<br>0.59 % of reading + 1.2 $\mu$ V<br>4.6 % of reading + 2.3 $\mu$ V<br>1.5 % of reading + 5.8 $\mu$ V<br>8.1 % of reading + 8.1 $\mu$ V<br><br>0.013 % of reading + 4.6 $\mu$ V<br>0.009 7 % of reading + 2.3 $\mu$ V<br>0.017 % of reading + 2.3 $\mu$ V<br>0.038 % of reading + 2.3 $\mu$ V<br>0.093 % of reading + 2.3 $\mu$ V<br>0.36 % of reading + 12 $\mu$ V<br>1.2 % of reading + 12 $\mu$ V<br>1.8 % of reading + 12 $\mu$ V<br>4.7 % of reading + 81 $\mu$ V<br>4.7 % of reading + 92 $\mu$ V<br>17 % of reading + 0.12 mV | Comparison to<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter                    |

**Electrical – DC/Low Frequency**

| Parameter/Equipment               | Range            | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment                      |
|-----------------------------------|------------------|-------------------------------------------|-------------------------------------------------------------------|
| AC Voltage – Measure <sup>1</sup> | (0.1 to 1) V     |                                           | Comparison to<br>Keysight 3458A, Opt. 002<br>8.5 Digit Multimeter |
|                                   | (1 to 40) Hz     | 0.008 8 % of reading + 46 $\mu$ V         |                                                                   |
|                                   | 40 Hz to 1 kHz   | 0.008 3 % of reading + 23 $\mu$ V         |                                                                   |
|                                   | (1 to 20) kHz    | 0.017 % of reading + 23 $\mu$ V           |                                                                   |
|                                   | (20 to 50) kHz   | 0.036 % of reading + 23 $\mu$ V           |                                                                   |
|                                   | (50 to 100) kHz  | 0.093 % of reading + 23 $\mu$ V           |                                                                   |
|                                   | (100 to 300) kHz | 0.35 % of reading + 0.12 mV               |                                                                   |
|                                   | 300 kHz to 1 MHz | 1.2 % of reading + 0.12 mV                |                                                                   |
|                                   | (1 to 2) MHz     | 1.8 % of reading + 0.12 mV                |                                                                   |
|                                   | (2 to 4) MHz     | 4.6 % of reading + 0.81 mV                |                                                                   |
|                                   | (4 to 8) MHz     | 4.6 % of reading + 0.92 mV                |                                                                   |
|                                   | (8 to 10) MHz    | 17 % of reading + 1.2 mV                  |                                                                   |
|                                   | (1 to 10) V      |                                           |                                                                   |
|                                   | (1 to 40) Hz     | 0.009 5 % of reading + 0.46 mV            |                                                                   |
|                                   | 40 Hz to 1 kHz   | 0.023 % of reading + 0.23 mV              |                                                                   |
|                                   | (1 to 20) kHz    | 0.017 % of reading + 0.23 mV              |                                                                   |
|                                   | (20 to 50) kHz   | 0.036 % of reading + 0.23 mV              |                                                                   |
|                                   | (50 to 100) kHz  | 0.093 % of reading + 0.23 mV              |                                                                   |
|                                   | (100 to 300) kHz | 0.35 % of reading + 1.2 mV                |                                                                   |
|                                   | 300 kHz to 1 MHz | 1.2 % of reading + 1.2 mV                 |                                                                   |
|                                   | (1 to 2) MHz     | 1.8 % of reading + 1.2 mV                 |                                                                   |
|                                   | (2 to 4) MHz     | 4.6 % of reading + 8.1 mV                 |                                                                   |
|                                   | (4 to 8) MHz     | 4.6 % of reading + 9.2 mV                 |                                                                   |
|                                   | (8 to 10) MHz    | 17 % of reading + 12 mV                   |                                                                   |
|                                   | (10 to 100) V    |                                           |                                                                   |
|                                   | (1 to 40) Hz     | 0.024 % of reading + 4.6 mV               |                                                                   |
|                                   | 40 Hz to 1 kHz   | 0.024 % of reading + 2.3 mV               |                                                                   |
|                                   | (1 to 20) kHz    | 0.024 % of reading + 2.3 mV               |                                                                   |
|                                   | (20 to 50) kHz   | 0.041 % of reading + 2.3 mV               |                                                                   |
|                                   | (50 to 100) kHz  | 0.14 % of reading + 2.3 mV                |                                                                   |
|                                   | (100 to 300) kHz | 0.46 % of reading + 12 mV                 |                                                                   |
|                                   | 300 kHz to 1 MHz | 1.7 % of reading + 12 mV                  |                                                                   |
|                                   | (100 to 700) V   |                                           |                                                                   |
|                                   | (1 to 40) Hz     | 0.048 % of reading + 46 mV                |                                                                   |
|                                   | 40 Hz to 1 kHz   | 0.048 % of reading + 23 mV                |                                                                   |
|                                   | (1 to 20) kHz    | 0.071 % of reading + 23 mV                |                                                                   |
|                                   | (20 to 50) kHz   | 0.19 % of reading + 23 mV                 |                                                                   |
|                                   | (50 to 100) kHz  | 0.35 % of reading + 23 mV                 |                                                                   |

## Electrical – DC/Low Frequency

| Parameter/Equipment                    | Range                                                                                                  | Expanded Uncertainty of Measurement (+/-)                                                                                                                    | Reference Standard, Method, and/or Equipment                                                  |
|----------------------------------------|--------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| AC Voltage – Measure <sup>1</sup>      | Up to 1 mV<br>100 kHz to 1 MHz<br>(1 to 3) MHz<br>(3 to 10) MHz<br>(10 to 20) MHz                      | 2 % of reading + 2.4 $\mu$ V<br>3.8 % of reading + 2.4 $\mu$ V<br>10 % of reading + 2.4 $\mu$ V<br>25 % of reading + 2.4 $\mu$ V                             | Comparison to<br>Rohde & Schwarz URE3<br>RMS Voltmeter                                        |
|                                        | (1 to 3) mV<br>100 kHz to 1 MHz<br>(1 to 3) MHz<br>(3 to 10) MHz<br>(10 to 20) MHz                     | 1 % of reading + 2 $\mu$ V<br>3.8 % of reading + 2 $\mu$ V<br>11 % of reading + 2 $\mu$ V<br>25 % of reading + 2 $\mu$ V                                     |                                                                                               |
|                                        | (3 to 100) mV<br>100 kHz to 1 MHz<br>(1 to 3) MHz<br>(3 to 10) MHz<br>(10 to 20) MHz<br>(20 to 30) MHz | 0.98 % of reading + 3 $\mu$ V<br>1.9 % of reading + 3 $\mu$ V<br>3.2 % of reading + 3 $\mu$ V<br>7.6 % of reading + 3 $\mu$ V<br>16 % of reading + 3 $\mu$ V |                                                                                               |
| AC High Voltage – Measure <sup>1</sup> | (0.7 to 10) kV<br>60 Hz                                                                                | 0.15 % of reading + 0.21 V                                                                                                                                   | Comparison to<br>Vitretek 4700<br>Digital HV Meter                                            |
| AC High Voltage – Measure <sup>1</sup> | (10 to 20) kV<br>60 Hz                                                                                 | 0.07 % of reading + 1.2 V                                                                                                                                    | Comparison to<br>Vitretek 4700<br>Digital HV Meter,<br>Vitretek HVP-35<br>High Voltage Probe  |
|                                        | (20 to 35) kV<br>60 Hz                                                                                 | 0.08 % of reading + 1.2 V                                                                                                                                    |                                                                                               |
| AC High Voltage – Measure <sup>1</sup> | (12.5 to 25) kV<br>60 Hz                                                                               | 0.094 % of reading + 1.3 V                                                                                                                                   | Comparison to<br>Vitretek 4700<br>Digital HV Meter,<br>Vitretek HVL-70<br>High Voltage Probe  |
|                                        | (25 to 37.5) kV<br>60 Hz                                                                               | 0.096 % of reading + 1.3 V                                                                                                                                   |                                                                                               |
|                                        | (37.5 to 50) kV<br>60 Hz                                                                               | 0.1 % of reading + 1.3 V                                                                                                                                     |                                                                                               |
| AC High Voltage – Measure <sup>1</sup> | 25 kV to 75 kV<br>60 Hz                                                                                | 0.17 % of reading + 1.4 V                                                                                                                                    | Comparison to<br>Vitretek 4700<br>Digital HV Meter,<br>Vitretek HVL-100<br>High Voltage Probe |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                        | Range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Reference Standard, Method, and/or Equipment                      |
|------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| Capacitance – Source <sup>1,2</sup><br>(Simulation)        | 220 pF to 399.99 pF<br>0.4 nF to 1.0999 nF<br>1.1 nF to 3.2999 nF<br>3.3 nF to 10.9999 nF<br>11 nF to 32.9999 nF<br>33 nF to 109.99 nF<br>110 nF to 329.999 nF<br>0.33 $\mu$ F to 1.0999 $\mu$ F<br>1.1 $\mu$ F to 3.2999 $\mu$ F<br>3.3 $\mu$ F to 10.9999 $\mu$ F<br>11 $\mu$ F to 32.9999 $\mu$ F<br>33 $\mu$ F to 109.999 $\mu$ F<br>110 $\mu$ F to 329.999 $\mu$ F<br>0.33 mF to 1.099999 mF<br>1.1 mF to 3.29999 mF<br>3.3 mF to 10.9999 mF<br>11 mF to 32.9999 mF<br>33 mF to 110 mF | 0.45 % of reading + 7.8 pF<br>0.4 % of reading + 7.8 pF<br>0.4 % of reading + 0.0078 nF<br>0.22 % of reading + 0.0078 nF<br>0.22 % of reading + 0.078 nF<br>0.22 % of reading + 0.078 nF<br>0.22 % of reading + 0.23 nF<br>0.21 % of reading + 0.78 nF<br>0.22 % of reading + 2.3 nF<br>0.21 % of reading + 7.8 nF<br>0.32 % of reading + 23 nF<br>0.38 % of reading + 0.078 $\mu$ F<br>0.35 % of reading + 0.23 $\mu$ F<br>0.35 % of reading + 0.78 $\mu$ F<br>0.35 % of reading + 2.3 $\mu$ F<br>0.35 % of reading + 7.8 $\mu$ F<br>0.58 % of reading + 23 $\mu$ F<br>0.85 % of reading + 78 $\mu$ F | Comparison to<br>Fluke 5522A<br>Multifunction Calibrator          |
| Capacitance – Source <sup>1,2</sup><br>(Fixed Artifacts)   | 100 Hz to 1 kHz<br>(0.1 to 0.7) nF<br>(0.7 to 600) nF<br>600 nF to 1.4 $\mu$ F                                                                                                                                                                                                                                                                                                                                                                                                              | 0.1 % of reading + 0.54 pF<br>0.16 % of reading + 0.1 pF<br>0.045 % of reading + 0.5 nF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Comparison to<br>Arco SS32<br>Precision Standard<br>Capacitor Set |
| Capacitance – Source <sup>1,2</sup><br>(Variable Artifact) | 1 kHz<br>100 pF to 1 nF<br>(1.1 to 10.1) nF<br>(10.1 to 100.1) nF<br>100.1 nF to 1.1111 $\mu$ F                                                                                                                                                                                                                                                                                                                                                                                             | 0.61 fF/pF + 1.3 fF<br>0.17 pF/nF + 12 pF<br>0.57 pF/nF + 4.6 pF<br>0.61 pF/nF + 2.1 pF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Comparison to<br>GenRad 1423A<br>Decade Capacitor                 |
| Capacitance – Measure <sup>2</sup>                         | 0.1 pF<br>100 kHz<br>1 MHz<br>1 pF<br>10 kHz<br>100 kHz<br>1 MHz<br>10 pF<br>1 kHz<br>10 kHz<br>100 kHz<br>1 MHz                                                                                                                                                                                                                                                                                                                                                                            | 1.4 % of reading<br>1.8 % of reading<br>1.4 % of reading<br>0.37 % of reading<br>0.44 % of reading<br>1.4 % of reading<br>0.28 % of reading<br>0.28 % of reading<br>0.3 % of reading                                                                                                                                                                                                                                                                                                                                                                                                                   | Comparison to<br>Agilent E4980AL<br>LCR Meter                     |



**Electrical – DC/Low Frequency**

| Parameter/Equipment                | Range   | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment                   |
|------------------------------------|---------|-------------------------------------------|----------------------------------------------------------------|
| Capacitance – Measure <sup>2</sup> | 100 pF  |                                           | Comparison to<br>Agilent E4980AL<br>Comparison to<br>LCR Meter |
|                                    | 100 Hz  | 2.1 % of reading                          |                                                                |
|                                    | 1 kHz   | 0.23 % of reading                         |                                                                |
|                                    | 10 kHz  | 0.18 % of reading                         |                                                                |
|                                    | 100 kHz | 0.21 % of reading                         |                                                                |
|                                    | 1 MHz   | 0.23 % of reading                         |                                                                |
|                                    | 1 nF    |                                           |                                                                |
|                                    | 20 Hz   | 1.8 % of reading                          |                                                                |
|                                    | 100 Hz  | 0.3 % of reading                          |                                                                |
|                                    | 1 kHz   | 0.1 % of reading                          |                                                                |
|                                    | 10 kHz  | 0.1 % of reading                          |                                                                |
|                                    | 100 kHz | 0.1 % of reading                          |                                                                |
|                                    | 1 MHz   | 0.14 % of reading                         |                                                                |
|                                    | 10 nF   |                                           |                                                                |
|                                    | 20 Hz   | 0.31 % of reading                         |                                                                |
|                                    | 100 Hz  | 0.12 % of reading                         |                                                                |
|                                    | 1 kHz   | 0.1 % of reading                          |                                                                |
|                                    | 10 kHz  | 0.1 % of reading                          |                                                                |
|                                    | 100 kHz | 0.1 % of reading                          |                                                                |
|                                    | 1 MHz   | 0.25 % of reading                         |                                                                |
|                                    | 100 nF  |                                           |                                                                |
|                                    | 20 Hz   | 0.16 % of reading                         |                                                                |
|                                    | 100 Hz  | 0.1 % of reading                          |                                                                |
|                                    | 1 kHz   | 0.1 % of reading                          |                                                                |
|                                    | 10 kHz  | 0.1 % of reading                          |                                                                |
|                                    | 100 kHz | 0.18 % of reading                         |                                                                |
|                                    | 1 MHz   | 0.33 % of reading                         |                                                                |
|                                    | 1 µF    |                                           |                                                                |
|                                    | 20 Hz   | 0.15 % of reading                         |                                                                |
|                                    | 100 Hz  | 0.1 % of reading                          |                                                                |
|                                    | 1 kHz   | 0.1 % of reading                          |                                                                |
|                                    | 10 kHz  | 0.18 % of reading                         |                                                                |
|                                    | 100 kHz | 0.25 % of reading                         |                                                                |
|                                    | 1 MHz   | 0.79 % of reading                         |                                                                |
|                                    | 10 µF   |                                           |                                                                |
|                                    | 20 Hz   | 0.15 % of reading                         |                                                                |
|                                    | 100 Hz  | 0.01 % of reading                         |                                                                |
|                                    | 1 kHz   | 0.16 % of reading                         |                                                                |
|                                    | 10 kHz  | 0.28 % of reading                         |                                                                |
|                                    | 100 kHz | 0.73 % of reading                         |                                                                |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                   | Range        | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment                   |
|-------------------------------------------------------|--------------|-------------------------------------------|----------------------------------------------------------------|
| Capacitance – Measure <sup>2</sup>                    | 100 $\mu$ F  |                                           | Comparison to<br>Agilent E4980AL<br>Comparison to<br>LCR Meter |
|                                                       | 20 Hz        | 0.16 % of reading                         |                                                                |
|                                                       | 100 Hz       | 0.17 % of reading                         |                                                                |
|                                                       | 1 kHz        | 0.29 % of reading                         |                                                                |
|                                                       | 10 kHz       | 0.8 % of reading                          |                                                                |
| Impedance – Measure <sup>1,2</sup><br>(AC Resistance) | 0.1 $\Omega$ |                                           | Comparison to<br>Agilent E4980AL<br>LCR Meter                  |
|                                                       | 1 kHz        | 2 % of reading                            |                                                                |
|                                                       | 10 kHz       | 1.2 % of reading                          |                                                                |
|                                                       | 100 kHz      | 1.1 % of reading                          |                                                                |
|                                                       | 1 MHz        | 1.2 % of reading                          |                                                                |
|                                                       | 1 $\Omega$   |                                           |                                                                |
|                                                       | 20 Hz        | 0.67 % of reading                         |                                                                |
|                                                       | 100 Hz       | 0.45 % of reading                         |                                                                |
|                                                       | 1 kHz        | 0.36 % of reading                         |                                                                |
|                                                       | 10 kHz       | 0.33 % of reading                         |                                                                |
|                                                       | 100 kHz      | 0.31 % of reading                         |                                                                |
|                                                       | 1 MHz        | 0.38 % of reading                         |                                                                |
|                                                       | 10 $\Omega$  |                                           |                                                                |
|                                                       | 20 Hz        | 0.29 % of reading                         |                                                                |
|                                                       | 100 Hz       | 0.2 % of reading                          |                                                                |
|                                                       | 1 kHz        | 0.17 % of reading                         |                                                                |
|                                                       | 10 kHz       | 0.18 % of reading                         |                                                                |
|                                                       | 100 kHz      | 0.18 % of reading                         |                                                                |
|                                                       | 1 MHz        | 0.31 % of reading                         |                                                                |
|                                                       | 100 $\Omega$ |                                           |                                                                |
|                                                       | 20 Hz        | 0.16 % of reading                         |                                                                |
|                                                       | 100 Hz       | 0.1 % of reading                          |                                                                |
|                                                       | 1 kHz        | 0.1 % of reading                          |                                                                |
|                                                       | 10 kHz       | 0.12 % of reading                         |                                                                |
|                                                       | 100 kHz      | 0.12 % of reading                         |                                                                |
|                                                       | 1 MHz        | 0.2 % of reading                          |                                                                |
|                                                       | 1 k $\Omega$ |                                           |                                                                |
|                                                       | 20 Hz        | 0.15 % of reading                         |                                                                |
|                                                       | 100 Hz       | 0.1 % of reading                          |                                                                |
|                                                       | 1 kHz        | 0.1 % of reading                          |                                                                |
|                                                       | 10 kHz       | 0.1 % of reading                          |                                                                |
|                                                       | 100 kHz      | 0.1 % of reading                          |                                                                |
|                                                       | 1 MHz        | 0.14 % of reading                         |                                                                |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                    | Range          | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment  |
|--------------------------------------------------------|----------------|-------------------------------------------|-----------------------------------------------|
| Impedance – Measure <sup>1,2</sup><br>(AC Resistance)  | 10 k $\Omega$  |                                           | Comparison to<br>Agilent E4980AL<br>LCR Meter |
|                                                        | 20 Hz          | 0.15 % of reading                         |                                               |
|                                                        | 100 Hz         | 0.1 % of reading                          |                                               |
|                                                        | 1 kHz          | 0.1 % of reading                          |                                               |
|                                                        | 10 kHz         | 0.1 % of reading                          |                                               |
|                                                        | 100 kHz        | 0.1 % of reading                          |                                               |
|                                                        | 1 MHz          | 0.29 % of reading                         |                                               |
|                                                        | 100 k $\Omega$ |                                           |                                               |
|                                                        | 20 Hz          | 0.17 % of reading                         |                                               |
|                                                        | 100 Hz         | 0.1 % of reading                          |                                               |
|                                                        | 1 kHz          | 0.1 % of reading                          |                                               |
|                                                        | 10 kHz         | 0.17 % of reading                         |                                               |
|                                                        | 100 kHz        | 0.28 % of reading                         |                                               |
|                                                        | 1 MHz          | 0.38 % of reading                         |                                               |
| Inductance – Source <sup>1,2</sup><br>(Fixed Artifact) | 100 mH         |                                           | Comparison to<br>Standard Inductor            |
|                                                        | 1 kHz          | 0.14 mH                                   |                                               |
| Inductance – Measure <sup>2</sup>                      | 1 $\mu$ H      |                                           | Comparison to<br>Agilent E4980AL<br>LCR Meter |
|                                                        | 10 kHz         | 1.6 % of reading                          |                                               |
|                                                        | 100 kHz        | 0.36 % of reading                         |                                               |
|                                                        | 1 MHz          | 0.27 % of reading                         |                                               |
|                                                        | 10 $\mu$ H     |                                           |                                               |
|                                                        | 10 kHz         | 0.37 % of reading                         |                                               |
|                                                        | 100 kHz        | 0.2 % of reading                          |                                               |
|                                                        | 1 MHz          | 0.2 % of reading                          |                                               |
|                                                        | 100 $\mu$ H    |                                           |                                               |
|                                                        | 1 kHz          | 0.41 % of reading                         |                                               |
|                                                        | 10 kHz         | 0.2 % of reading                          |                                               |
|                                                        | 100 kHz        | 0.12 % of reading                         |                                               |
|                                                        | 1 MHz          | 0.14 % of reading                         |                                               |
|                                                        | 1 mH           |                                           |                                               |
|                                                        | 100 Hz         | 0.56 % of reading                         |                                               |
|                                                        | 1 kHz          | 0.19 % of reading                         |                                               |
|                                                        | 10 kHz         | 0.12 % of reading                         |                                               |
|                                                        | 100 kHz        | 0.1 % of reading                          |                                               |
|                                                        | 1 MHz          | 0.23 % of reading                         |                                               |

## Electrical – DC/Low Frequency

| Parameter/Equipment                       | Range                                                              | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment                           |
|-------------------------------------------|--------------------------------------------------------------------|-------------------------------------------|------------------------------------------------------------------------|
| Inductance – Measure <sup>1,2</sup>       | 10 mH                                                              |                                           | Comparison to<br>Agilent E4980AL<br>LCR Meter                          |
|                                           | 20 Hz                                                              | 0.86 % of reading                         |                                                                        |
|                                           | 100 Hz                                                             | 0.22 % of reading                         |                                                                        |
|                                           | 1 kHz                                                              | 0.1 % of reading                          |                                                                        |
|                                           | 10 kHz                                                             | 0.1 % of reading                          |                                                                        |
|                                           | 100 kHz                                                            | 0.11 % of reading                         |                                                                        |
|                                           | 1 MHz                                                              | 0.35 % of reading                         |                                                                        |
|                                           | 100 mH                                                             |                                           |                                                                        |
|                                           | 20 Hz                                                              | 0.28 % of reading                         |                                                                        |
|                                           | 100 Hz                                                             | 0.11 % of reading                         |                                                                        |
|                                           | 1 kHz                                                              | 0.1 % of reading                          |                                                                        |
|                                           | 10 kHz                                                             | 0.1 % of reading                          |                                                                        |
|                                           | 100 kHz                                                            | 0.21 % of reading                         |                                                                        |
|                                           | 1 MHz                                                              | 0.88 % of reading                         |                                                                        |
|                                           | 10 H                                                               |                                           |                                                                        |
|                                           | 20 Hz                                                              | 0.15 % of reading                         |                                                                        |
|                                           | 100 Hz                                                             | 0.1 % of reading                          |                                                                        |
|                                           | 1 kHz                                                              | 0.11 % of reading                         |                                                                        |
|                                           | 10 kHz                                                             | 0.21 % of reading                         |                                                                        |
|                                           | 100 kHz                                                            | 0.69 % of reading                         |                                                                        |
|                                           | 100 H                                                              |                                           |                                                                        |
|                                           | 20 Hz                                                              | 0.15 % of reading                         |                                                                        |
|                                           | 100 Hz                                                             | 0.11 % of reading                         |                                                                        |
|                                           | 1 kHz                                                              | 0.15 % of reading                         |                                                                        |
|                                           | 10 kHz                                                             | 0.62 % of reading                         |                                                                        |
| Current Harmonics – Source <sup>1,3</sup> | Carrier Range to 0.25 A<br>Harmonic: Up to 75 mA<br>(16 to 850) Hz | 61 $\mu$ A/A + 21 $\mu$ A                 | Comparison to<br>Fluke 6105A<br>Electrical Power<br>Quality Calibrator |
|                                           | 850 Hz to 6.5 kHz                                                  | 0.46 mA/A + 22 $\mu$ A                    |                                                                        |
|                                           | Carrier Range to 0.5 A<br>Harmonic: Up to 0.15 A<br>(16 to 850) Hz | 70 $\mu$ A/A + 21 $\mu$ A                 |                                                                        |
|                                           | 850 Hz to 6.5 kHz                                                  | 0.46 mA/A + 23 $\mu$ A                    |                                                                        |

## Electrical – DC/Low Frequency

| Parameter/Equipment                       | Range                                                                                   | Expanded Uncertainty of Measurement (+/-)           | Reference Standard, Method, and/or Equipment                           |
|-------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------------------|------------------------------------------------------------------------|
| Current Harmonics – Source <sup>1,3</sup> | Carrier Range to 1 A<br>Harmonic: Up to 0.3 A<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz    | 70 $\mu$ A/A + 29 $\mu$ A<br>0.46 mA/A + 29 $\mu$ A | Comparison to<br>Fluke 6105A<br>Electrical Power<br>Quality Calibrator |
|                                           | Carrier Range to 2 A<br>Harmonic: Up to 0.6 A<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz    | 70 $\mu$ A/A + 0.1 mA<br>0.46 mA/A + 0.1 mA         |                                                                        |
|                                           | Carrier Range to 5 A<br>Harmonic: Up to 1.5 A<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz    | 70 $\mu$ A/A + 0.1 mA<br>0.46 A/A + 0.1 mA          |                                                                        |
|                                           | Carrier Range to 10 A<br>Harmonic: Up to 3 A<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz     | 74 $\mu$ A/A + 0.29 mA<br>0.46 mA/A + 0.29 mA       |                                                                        |
|                                           | Carrier Range to 20 A<br>Harmonic: Up to 6 A<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz     | 75 $\mu$ A/A + 0.45 mA<br>0.46 mA/A + 0.45 mA       |                                                                        |
| Voltage Harmonics – Source <sup>1,3</sup> | Carrier Range to 23 V<br>Harmonic: Up to 6.9 V<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz   | 58 $\mu$ V/V + 1 mV<br>0.52 mV/V + 1 mV             | Comparison to<br>Fluke 6105A<br>Electrical Power<br>Quality Calibrator |
|                                           | Carrier Range to 45 V<br>Harmonic: Up to 13.5 V<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz  | 67 $\mu$ V/V + 2 mV<br>0.52 mV/V + 2 mV             |                                                                        |
| Voltage Harmonics – Source <sup>1,3</sup> | Carrier Range to 90 V<br>Harmonic: Up to 27 V<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz    | 69 $\mu$ V/V + 2 mV<br>0.52 mV/V + 2 mV             | Comparison to<br>Fluke 6105A<br>Electrical Power<br>Quality Calibrator |
|                                           | Carrier Range to 135 V<br>Harmonic: Up to 40.5 V<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz | 69 $\mu$ V/V + 2 mV<br>0.52 mV/V + 2 mV             |                                                                        |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                | Range                                                                                    | Expanded Uncertainty of Measurement (+/-)                                            | Reference Standard, Method, and/or Equipment                           |
|----------------------------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------------------------------------|
| Voltage Harmonics – Source <sup>1,3</sup>          | Carrier Range to 180 V<br>Harmonic: Up to 54 V<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz    | 69 $\mu$ V/V + 6 mV<br>0.52 mV/V + 6 mV                                              | Comparison to<br>Fluke 6105A<br>Electrical Power<br>Quality Calibrator |
|                                                    | Carrier Range to 360 V<br>Harmonic: Up to 108 V<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz   | 69 $\mu$ V/V + 13 mV<br>0.52 V/V + 13 mV                                             |                                                                        |
|                                                    | Carrier Range to 650 V<br>Harmonic: Up to 195 V<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz   | 70 $\mu$ V/V + 22 mV<br>0.52 mV/V + 22 mV                                            |                                                                        |
|                                                    | Carrier Range to 1 008 V<br>Harmonic: Up to 302 V<br>(16 to 850) Hz<br>850 Hz to 6.5 kHz | 70 $\mu$ V/V + 33 mV<br>0.52 mV/V + 33 mV                                            |                                                                        |
| DC Power – Source <sup>1</sup><br>(0.33 to 330) mA | 11 $\mu$ W to 1.1 mW<br>1.1 mW to 0.11 W<br>(0.11 to 110) W<br>(110 to 330) W            | 0.024 % of reading<br>0.027 % of reading<br>0.024 % of reading<br>0.018 % of reading | Comparison to<br>Fluke 5520A<br>Multiproduct Calibrator                |
| (0.33 to 3) A                                      | 11 $\mu$ W to 110 mW<br>(0.11 to 990) W<br>(0.99 to 3) kW                                | 0.044 % of reading<br>0.053 % of reading<br>0.009 6 % of reading                     |                                                                        |
| (3 to 20.5) A                                      | 99 mW to 0.99 W<br>0.99 W to 6.8 kW<br>(6.8 to 20.5) kW                                  | 0.088 % of reading<br>0.07 % of reading<br>0.04 % of reading                         |                                                                        |



## Electrical – DC/Low Frequency

| Parameter/Equipment                        | Range                                                                                                               | Expanded Uncertainty of Measurement (+/-)                   | Reference Standard, Method, and/or Equipment                           |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|------------------------------------------------------------------------|
| AC Power – Source <sup>1,4</sup><br>PF = 1 |                                                                                                                     |                                                             |                                                                        |
| (3.3 to 9) mA                              | (10 to 65) Hz<br>(0.11 mW to 3) mW<br>3 mW to 9 W                                                                   | 0.13 % of reading<br>0.077 % of reading                     | Comparison to<br>Fluke 5520A<br>Multiproduct Calibrator                |
| (9 to 33) mA                               | (10 to 65) W<br>(0.3 to 10) mW<br>10 mW to 33 W                                                                     | 0.089 % of reading<br>0.077 % of reading                    |                                                                        |
| (33 to 90) mA                              | (10 to 65) Hz<br>(1 to 30) mW<br>30 mW to 90 W                                                                      | 0.071 % of reading<br>0.057 % of reading                    |                                                                        |
| (90 to 330) mA                             | (10 to 65) Hz<br>(3 to 100) mW<br>100 mW to 300 W                                                                   | 0.089 % of reading<br>0.078 % of reading                    |                                                                        |
| (0.33 to 0.9) A                            | (10 to 65) Hz<br>(11 to 300) mW<br>(0.3 to 900) W                                                                   | 0.071 % of reading<br>0.081 % of reading                    |                                                                        |
| (0.9 to 2.2) A                             | (10 to 65) Hz<br>(30 to 720) mW<br>0.72 W to 2 kW                                                                   | 0.089 % of reading<br>0.079 % of reading                    |                                                                        |
| (2.2 to 4.5) A                             | (10 to 65) Hz<br>80 mW to 1.4 W<br>1.4 W to 4.5 kW                                                                  | 0.088 % of reading<br>0.18 % of reading                     |                                                                        |
| (4.5 to 20.5) A                            | (10 to 65) Hz<br>150 mW to 20 kW                                                                                    | 0.17 % of reading                                           |                                                                        |
| AC Power – Source <sup>1,4</sup><br>PF = 1 |                                                                                                                     |                                                             | Comparison to<br>Fluke 6105A<br>Electrical Power<br>Quality Calibrator |
| (0.5 to 20) A                              | (16 to 850) Hz<br>23 W to 13 kW                                                                                     | 0.024 % of reading                                          |                                                                        |
| Phase – Source <sup>1</sup>                | (0 to 90)°<br>(10 to 65) Hz<br>(65 to 500) Hz<br>500 Hz to 1 kHz<br>(1 to 5) kHz<br>(5 to 10) kHz<br>(10 to 30) kHz | 0.11°<br>0.2°<br>0.39°<br>1.9°<br>3.9°<br>7.8°              | Comparison to<br>Fluke 5520A<br>Multiproduct Calibrator                |
| Total Harmonic Distortion                  | 5 Hz to 500 kHz<br>500 kHz to 1 MHz                                                                                 | 18 % of reading + 0.13 %T HD<br>29 % of reading + 0.7 % THD | Comparison to<br>Kron-Hite 6900B<br>Distortion Analyzer                |

# Electrical – DC/Low Frequency

| Parameter/Equipment                                                                    | Range               | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment                 |
|----------------------------------------------------------------------------------------|---------------------|-------------------------------------------|--------------------------------------------------------------|
| Electrical Simulation of Thermocouple Indicating Devices – Measure/Source <sup>1</sup> | Type B              |                                           | Comparison to Ectron 1140A Thermocouple Calibrator/Simulator |
|                                                                                        | (250 to 350) °C     | 1.2 °C                                    |                                                              |
|                                                                                        | (350 to 445) °C     | 0.9 °C                                    |                                                              |
|                                                                                        | (445 to 580) °C     | 0.71 °C                                   |                                                              |
|                                                                                        | (580 to 750) °C     | 0.55 °C                                   |                                                              |
|                                                                                        | (750 to 1 000) °C   | 0.45 °C                                   |                                                              |
|                                                                                        | (1 000 to 1 820) °C | 0.35 °C                                   |                                                              |
|                                                                                        | Type C              |                                           |                                                              |
|                                                                                        | (0 to 250) °C       | 0.21 °C                                   |                                                              |
|                                                                                        | (250 to 1 000) °C   | 0.17 °C                                   |                                                              |
|                                                                                        | (1 000 to 1 500) °C | 0.19 °C                                   |                                                              |
|                                                                                        | (1 500 to 1 800) °C | 0.22 °C                                   |                                                              |
|                                                                                        | (1 800 to 2 000) °C | 0.24 °C                                   |                                                              |
|                                                                                        | (2 000 to 2 250) °C | 0.30 °C                                   |                                                              |
|                                                                                        | (2 250 to 2 315) °C | 0.33 °C                                   |                                                              |
|                                                                                        | Type E              |                                           |                                                              |
|                                                                                        | (-270 to -245) °C   | 1.6 °C                                    |                                                              |
|                                                                                        | (-245 to -195) °C   | 0.24 °C                                   |                                                              |
|                                                                                        | (-195 to -155) °C   | 0.12 °C                                   |                                                              |
|                                                                                        | (-155 to -90) °C    | 0.095 °C                                  |                                                              |
|                                                                                        | (-90 to 0) °C       | 0.08 °C                                   |                                                              |
|                                                                                        | (0 to 15) °C        | 0.076 °C                                  |                                                              |
|                                                                                        | (15 to 890) °C      | 0.064 °C                                  |                                                              |
|                                                                                        | (890 to 1 000) °C   | 0.074 °C                                  |                                                              |
|                                                                                        | Type J              |                                           |                                                              |
|                                                                                        | (-210 to -180) °C   | 0.15 °C                                   |                                                              |
|                                                                                        | (-180 to -120) °C   | 0.12 °C                                   |                                                              |
|                                                                                        | (-120 to -50) °C    | 0.093 °C                                  |                                                              |
|                                                                                        | (-50 to 990) °C     | 0.08 °C                                   |                                                              |
|                                                                                        | (990 to 1 200) °C   | 0.094 °C                                  |                                                              |
|                                                                                        | Type K              |                                           |                                                              |
|                                                                                        | (-270 to -255) °C   | 2.5 °C                                    |                                                              |
|                                                                                        | (-255 to -195) °C   | 0.85 °C                                   |                                                              |
|                                                                                        | (-195 to -115) °C   | 0.16 °C                                   |                                                              |
|                                                                                        | (-115 to -55) °C    | 0.12 °C                                   |                                                              |
|                                                                                        | (-55 to 1 000) °C   | 0.087 °C                                  |                                                              |
|                                                                                        | (1 000 to 1 372) °C | 0.096 °C                                  |                                                              |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                                                    | Range                              | Expanded Uncertainty of Measurement (+/-)                    | Reference Standard, Method, and/or Equipment                                                                                                                            |
|----------------------------------------------------------------------------------------|------------------------------------|--------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical Simulation of Thermocouple Indicating Devices – Measure/Source <sup>1</sup> | Type N                             |                                                              | Comparison to Ectron 1140A Thermocouple Calibrator/Simulator                                                                                                            |
|                                                                                        | (-270 to -260) °C                  | 5.4 °C                                                       |                                                                                                                                                                         |
|                                                                                        | (-260 to -200) °C                  | 1.5 °C                                                       |                                                                                                                                                                         |
|                                                                                        | (-200 to -140) °C                  | 0.29 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (-140 to -70) °C                   | 0.18 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (-70 to 25) °C                     | 0.14 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (-25 to 160) °C                    | 0.12 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (160 to 1 300) °C                  | 0.11 °C                                                      |                                                                                                                                                                         |
|                                                                                        | Type R                             |                                                              |                                                                                                                                                                         |
|                                                                                        | (-50 to -30) °C                    | 0.8 °C                                                       |                                                                                                                                                                         |
|                                                                                        | (-30 to 45) °C                     | 0.69 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (45 to 160) °C                     | 0.49 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (160 to 380) °C                    | 0.35 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (380 to 775) °C                    | 0.3 °C                                                       |                                                                                                                                                                         |
|                                                                                        | (775 to 1 768) °C                  | 0.26 °C                                                      |                                                                                                                                                                         |
|                                                                                        | Type S                             |                                                              |                                                                                                                                                                         |
|                                                                                        | (-50 to -30) °C                    | 0.76 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (-30 to 45) °C                     | 0.68 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (45 to 105) °C                     | 0.49 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (105 to 310) °C                    | 0.41 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (310 to 615) °C                    | 0.35 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (615 to 1 768) °C                  | 0.31 °C                                                      |                                                                                                                                                                         |
|                                                                                        | Type T                             |                                                              |                                                                                                                                                                         |
|                                                                                        | (-270 to -255) °C                  | 1.9 °C                                                       |                                                                                                                                                                         |
|                                                                                        | (-255 to -240) °C                  | 0.6 °C                                                       |                                                                                                                                                                         |
|                                                                                        | (-240 to -210) °C                  | 0.36 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (-210 to -150) °C                  | 0.22 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (-150 to -40) °C                   | 0.15 °C                                                      |                                                                                                                                                                         |
|                                                                                        | (-40 to 100) °C                    | 0.095 °C                                                     |                                                                                                                                                                         |
|                                                                                        | (100 to 400) °C                    | 0.08 °C                                                      |                                                                                                                                                                         |
| Oscilloscopes <sup>1,8</sup><br>Amplitude – DC<br>into 50 Ω load<br><br>into 1 MΩ load | (-5 to 5) V<br><br>(-200 to 200) V | 0.023 % of reading + 19 μV<br><br>0.023 % of reading + 19 μV | Comparison to Fluke 9500B Oscilloscope Calibrator, Fluke 9500B/3200 Oscilloscope Calibrator, Fluke 9530 3.2 GHz Active Head, Fluke 9550 Active Head w/ 25 ps Capability |

## Electrical – DC/Low Frequency

| Parameter/Equipment                                                                                       | Range                                                     | Expanded Uncertainty of Measurement (+/-)                           | Reference Standard, Method, and/or Equipment                                                                                                                                                       |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Oscilloscopes <sup>1,8</sup><br>Amplitude – Square Wave<br>Rate: 10 Hz to 10 kHz<br>into 50 $\Omega$ load | 40 $\mu$ Vp-p to 1 mVp-p<br>1 mVp-p to 5 Vp-p             | 0.78 % of reading + 7.8 $\mu$ V<br>0.078 % of reading + 7.8 $\mu$ V | Comparison to<br>Fluke 9500B<br>Oscilloscope Calibrator,<br>Fluke 9500B/3200<br>Oscilloscope Calibrator,<br>Fluke 9530<br>3.2 GHz Active Head,<br>Fluke 9550<br>Active Head w/ 25 ps<br>Capability |
| into 1 M $\Omega$ load                                                                                    | 40 $\mu$ Vp-p to 1 mVp-p<br>1 mVp-p to 200 Vp-p           | 0.78 % of reading + 7.8 $\mu$ V<br>0.078 % of reading + 7.8 $\mu$ V |                                                                                                                                                                                                    |
| Time Markers<br>100 mVp-p to 1 Vp-p<br>into 50 $\Omega$ load                                              |                                                           |                                                                     |                                                                                                                                                                                                    |
| Square Wave                                                                                               | 9.009 1 ns to 83 $\mu$ s<br>83 $\mu$ s to 55s             | 0.19 $\mu$ s/s<br>2.3 $\mu$ s/s                                     |                                                                                                                                                                                                    |
| Sine Wave                                                                                                 | 450.5 ps to 9.009 ns                                      | 0.19 $\mu$ s/s                                                      |                                                                                                                                                                                                    |
| Pulse                                                                                                     | 900.91 ns to 83 $\mu$ s<br>83 $\mu$ s to 55s              | 0.19 $\mu$ s/s<br>2.3 $\mu$ s/s                                     |                                                                                                                                                                                                    |
| Triangle Wave                                                                                             | 900.91 ns to 83 $\mu$ s<br>83 $\mu$ s to 55s              | 0.19 $\mu$ s/s<br>2.3 $\mu$ s/s                                     |                                                                                                                                                                                                    |
| Rise Time<br>into 50 $\Omega$ load<br>Rate: 10 Hz to 2 MHz                                                | 5 mVp-p to 3 Vp-p<br>500 ps (nominal)<br>150 ps (nominal) | 290 ps<br>31 ps                                                     |                                                                                                                                                                                                    |
| Rate: 10 Hz to 1 MHz                                                                                      | 425 mVp-p to 575 mVp-p<br>25 ps (nominal)                 | 6.8 ps                                                              |                                                                                                                                                                                                    |
| Leveled Sine Wave<br>50 kHz Reference<br>into 50 $\Omega$ load                                            | 50 kHz to 10 MHz                                          | 1.2 % of reading                                                    |                                                                                                                                                                                                    |

### Electrical – DC/Low Frequency

| Parameter/Equipment                                                                       | Range                                                                                                                                                              | Expanded Uncertainty of Measurement (+/-)                                                                                    | Reference Standard, Method, and/or Equipment                                                                                                                 |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Oscilloscopes <sup>1,8</sup><br>Input Impedance Measure                                   | (10 to 40) $\Omega$<br>(40 to 90) $\Omega$<br>(90 to 150) $\Omega$<br>(50 to 800) k $\Omega$<br>(0.8 to 1.2) M $\Omega$<br>(1.2 to 12) M $\Omega$                  | 0.39 % of reading<br>0.083 % of reading<br>0.39 % of reading<br>0.39 % of reading<br>0.083 % of reading<br>0.39 % of reading | Comparison to<br>Fluke 9500B<br>Oscilloscope Calibrator,<br>Fluke 9500B/3200<br>Oscilloscope Calibrator,<br>Fluke 9530<br>3.2 GHz Active Head,<br>Fluke 9550 |
| Input Capacitance Measure                                                                 | (1 to 35) pF<br>(35 to 95) pF                                                                                                                                      | 1.6 % of reading + 0.19 pF<br>2.3 % of reading + 0.19 pF                                                                     | Active Head w/ 25 ps<br>Capability                                                                                                                           |
| Rise Time – Source <sup>1,8</sup><br>(45 to 55) kHz                                       | 25 Vp-p<br>(300 to 400) ps                                                                                                                                         | 64 ps                                                                                                                        | Comparison to<br>Tektronix PG509<br>Pulse Generator                                                                                                          |
| Rise Time – Measure <sup>1</sup>                                                          | $\geq 350$ ps                                                                                                                                                      | 28 ps                                                                                                                        | Comparison to<br>Agilent DSO6102<br>Oscilloscope                                                                                                             |
| Bandwidth Flatness Measure <sup>1</sup><br>into VSWR (1.2:1)<br>(wrt Reference Frequency) | 5 mVp-p to 5 Vp-p<br>100 Hz to 300 MHz<br>(300 to 550) MHz<br>5 mVp-p to 3 Vp-p<br>550 MHz to 1.1 GHz<br>(1.1 to 2.5) GHz<br>5 mVp-p to 2 Vp-p<br>(2.5 to 3.2) GHz | 1.6 % of reading<br>1.9 % of reading<br>2.7 % of reading<br>3.1 % of reading<br>3.1 % of reading                             | Comparison to<br>Fluke 9500B/3200<br>Oscilloscope Calibrator,<br>Fluke 9530<br>3.2 GHz Active Head                                                           |

### Electrical – RF/Microwave

| Parameter/Equipment                                                 | Range                                                                                                      | Expanded Uncertainty of Measurement (+/-)                                                        | Reference Standard, Method, and/or Equipment                                   |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| Harmonic Distortion –<br>Measure<br>(dBc)<br>into VSWR $\leq 1.3:1$ | (-80 to 0) dB<br>9 kHz to 3 GHz<br>(3 to 6.8) GHz<br>(6.8 to 13.2) GHz                                     | 0.02 dB/dB + 1.1 dB<br>0.02 dB/dB + 3.1 dB<br>0.02 dB/dB + 3.7 dB                                | Comparison to<br>Agilent E4405B<br>Opt. 1DS, 1DR, 1D5<br>Spectrum Analyzer     |
| Frequency Response to<br>RF Source                                  | 100 kHz to 4.2 GHz<br>(-30 to -20) dB<br>(-20 to -10) dB<br>(-10 to 0) dB<br>(0 to 10) dB<br>(10 to 20) dB | 1.9 % of reading<br>1.9 % of reading<br>1.9 % of reading<br>1.9 % of reading<br>1.9 % of reading | Comparison to<br>Agilent 438A<br>Power Meter,<br>Agilent 8482A<br>Power Sensor |

## Length – Dimensional Metrology

| Parameter/Equipment                                                                 | Range                                                                                    | Expanded Uncertainty of Measurement (+/-)                                                                  | Reference Standard, Method, and/or Equipment           |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|
| Angle Measuring Devices<br>(Protractors, Inclinometers, Squares, Angle Gages, etc.) | 0.005 6" to 5°<br>(5 to 20)°<br>(20 to 35)°<br>(35 to 45)°<br>(45 to 60)°                | 3.2"<br>6.1"<br>11"<br>15"<br>25"                                                                          | Comparison to<br>5 in Sine Bar, Gage Blocks            |
|                                                                                     | 90°                                                                                      | 15"                                                                                                        | Master Square                                          |
| Calipers <sup>1,5,9</sup><br>(Dial, Digital, Vernier)                               | Up to 40 in<br>Up to 1 000 mm                                                            | $(51 + 2.9L) \mu\text{in}$<br>$(1.3 + 1.7L) \mu\text{m}$                                                   | Comparison to<br>Gage Blocks                           |
| Micrometers <sup>1,5,9</sup><br>(Inside, Outside)                                   | Up to 36 in<br>Up to 900 mm                                                              | $(14 + 6.2L) \mu\text{in}$<br>$(14 + 6.2L) \mu\text{m}$                                                    | Comparison to<br>Gage Blocks                           |
| Micrometer Anvil<br>Flatness <sup>1,5,9</sup><br>(Inside, Outside)                  | Flatness up to 1 in<br>Flatness up to 25 mm                                              | 6.4 $\mu\text{in}$<br>0.16 $\mu\text{m}$                                                                   | Comparison to<br>Optical Flats                         |
| Micrometer Anvil<br>Parallelism <sup>1,5,9</sup><br>(Inside, Outside)               | Parallelism to 1 in<br>Parallelism > 1 in<br>Parallelism to 25 mm<br>Parallelism > 25 mm | 13 $\mu\text{in}$<br>$(11 + 0.64L) \mu\text{in}$<br>0.33 $\mu\text{m}$<br>$(0.27 + 0.000 65L) \mu\text{m}$ | Comparison to<br>Optical Parallels                     |
| Micrometer <sup>1,5,9</sup><br>(Depth, Step)                                        | Up to 36 in<br>Up to 900 mm                                                              | $(42 + 3.8L) \mu\text{in}$<br>$(1.1 + 3.5L) \mu\text{m}$                                                   | Comparison to<br>Gage Blocks                           |
| Micrometer Flatness <sup>1</sup><br>(Depth, Step)                                   | Up to 1.5 in<br>Up to 37.5 mm                                                            | 6.4 $\mu\text{in}$<br>0.16 $\mu\text{m}$                                                                   | Comparison to<br>Optical Flats                         |
| Bore Gages <sup>5</sup>                                                             | (0.125 to 1) in<br>(1 to 6) in                                                           | 33 $\mu\text{in}$<br>$(26 + 7L) \mu\text{in}$                                                              | Comparison to<br>Characterized<br>Cylindrical Rings    |
| Indicators <sup>1,5</sup><br>(Dial, Digital, Test)                                  | Up to 1 in<br>(1 to 6) in                                                                | $(10 + 2L) \mu\text{in}$<br>$(5 + 5L) \mu\text{in}$                                                        | Comparison to<br>Gage Blocks,<br>Surface Plates        |
| Linear Indicators <sup>5,9</sup>                                                    | Up to 10 in<br>Up to 250 mm                                                              | $(10 + 2.2L) \mu\text{in}$<br>$(0.26 + 2.2L) \mu\text{m}$                                                  | Comparison to<br>Universal Length<br>Measuring Machine |



## Length – Dimensional Metrology

| Parameter/Equipment                                                                                           | Range                                                                           | Expanded Uncertainty of Measurement (+/-)                                                                                                   | Reference Standard, Method, and/or Equipment                                                             |
|---------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Single Axis Length – Outside <sup>5</sup>                                                                     | Up to 1 in<br>(1 to 7) in<br>(7 to 12) in<br><br>(12 to 24) in<br>(24 to 48) in | $(6 + 1L) \mu\text{in}$<br>$(4 + 3.5L) \mu\text{in}$<br>$(4L) \mu\text{in}$<br><br>$(53 + 3L) \mu\text{in}$<br>$(8.2 + 1.67L) \mu\text{in}$ | Comparison to Universal Length Measuring Machine<br><br>P&W U304393<br>Digital & Laser Measuring Machine |
| Single Axis Length – Inside <sup>5</sup>                                                                      | (0.04 to 1) in<br>(1 to 2.5) in<br>(2.5 to 10) in<br>(10 to 12) in              | $(9 + 1L) \mu\text{in}$<br>$(9 + 3L) \mu\text{in}$<br>$(14 + 3L) \mu\text{in}$<br>$(25 + 3L) \mu\text{in}$                                  | Comparison to Universal Length Measuring Machine                                                         |
| Chamfer/Countersink Gages <sup>1,5</sup>                                                                      | Up to 0.825 in<br>(0.825 to 1.51) in<br>(1.51 to 2.51) in                       | $58 \mu\text{in}$<br>$(72 + 12L) \mu\text{in}$<br>$(80 + 23L) \mu\text{in}$                                                                 | Comparison to Characterized Cylindrical Ring Gages                                                       |
| Height Gages <sup>1,5,9</sup>                                                                                 | Up to 24 in<br><br>Up to 600 mm                                                 | $(21 + 3.2L) \mu\text{in}$<br><br>$(0.55 + 1.8L) \mu\text{m}$                                                                               | Comparison to Gage Blocks, Grade AA Surface Plate                                                        |
| Height Standards, Height Masters, Risers <sup>5</sup>                                                         | Up to 12 in                                                                     | $(28 + 3.2L) \mu\text{in}$                                                                                                                  | Comparison to Gage Amplifier, Probe, Grade AA Surface Plate                                              |
| Squareness                                                                                                    | Up to 18 in                                                                     | $9 \mu\text{in/in}$                                                                                                                         | Comparison to Master Square, Gage Amplifier, Probe, Grade AA Surface Plate                               |
| Parallelism<br>Physical Size<br>Up to (3 x 12) in<br>(3 x 12) in to (3 x 18) in<br>(6 x 18) in to (6 x 30) in | Up to 0.05 in<br>Up to 0.05 in<br>Up to 0.05 in                                 | $47 \mu\text{in}$<br>$52 \mu\text{in}$<br>$42 \mu\text{in}$                                                                                 | Comparison to Gage Amplifier, Probe, Grade AA Surface Plate                                              |
| Straightness<br>Physical Size<br>Up to 12 in<br>(12 to 18) in<br>(18 to 30) in                                | Up to 0.05 in<br>Up to 0.05 in<br>Up to 0.05 in                                 | $35 \mu\text{in}$<br>$42 \mu\text{in}$<br>$46 \mu\text{in}$                                                                                 | Comparison to Gage Amplifier, Probe, Grade AA Surface Plate                                              |

## Length – Dimensional Metrology

| Parameter/Equipment                     | Range                                  | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment |
|-----------------------------------------|----------------------------------------|-------------------------------------------|----------------------------------------------|
| Flatness                                |                                        |                                           | Comparison to                                |
| Physical Size                           |                                        |                                           | Optical Flat                                 |
| Up to 4 in Diameter                     | Up to 250 $\mu\text{in}$               | 4.4 $\mu\text{in}$                        |                                              |
| Up to (3 x 12) in                       | Up to 0.05 in                          | 49 $\mu\text{in}$                         | Gage Amplifier, Probe,                       |
| (3 x 12) in to (3 x 18) in              | Up to 0.05 in                          | 54 $\mu\text{in}$                         | Grade AA Surface Plate                       |
| (6 x 18) in to (6 x 30) in              | Up to 0.05 in                          | 54 $\mu\text{in}$                         |                                              |
| Up to (3 x 12) in                       | Up to 1 in                             | 138 $\mu\text{in}$                        | Multi-axis Vision System                     |
| Optical Comparator <sup>1,5</sup>       |                                        |                                           | Comparison to                                |
| Length                                  | (0 to 6) in                            | (185 + 13L) $\mu\text{in}$                | Calibration Grids                            |
| Squareness                              | (0.04 to 1) in                         | (213 + 1L) $\mu\text{in}$                 | Calibration Grids                            |
| Magnification                           | 10X to 50X                             | (295 + 20L) $\mu\text{in}$                | Magnification Checker                        |
| Length Measuring Equipment <sup>5</sup> |                                        |                                           | Comparison to                                |
| Linear Displacement                     | Up to 12 ft                            | (1 + 2.1L) $\mu\text{in}$                 | Laser Interferometer                         |
| Optical Reference Plane                 | Up to 6 in                             | 51 $\mu\text{in}$                         | Comparison to                                |
|                                         | (6 to 12) in                           | 74 $\mu\text{in}$                         | Glass Scale,<br>Calibration Grid             |
| Thread Wires                            | (2 to 120) TPI<br>(0.008 33 to 0.5) in | 12 $\mu\text{in}$                         | Direct Measure using<br>Measuring Machine    |
| Cylindrical Plug Gages <sup>5</sup>     |                                        |                                           | Comparison to                                |
| Outside Diameter                        | (0.01 to 4) in                         | (8 + 3.3L) $\mu\text{in}$                 | Universal Length<br>Measuring Machine,       |
|                                         | (> 4 to 10) in                         | (10 + 3.3L) $\mu\text{in}$                | Gage Blocks                                  |
|                                         | (0.25 to 100) mm                       | (0.2 + 3L) $\mu\text{m}$                  |                                              |
|                                         | (> 100 to 250) mm                      | (0.24 + 3.3L) $\mu\text{m}$               |                                              |
| Pin Gages                               |                                        |                                           | Non-contact Measure using                    |
| Outside Diameter                        | (0.003 to 1) in                        | 30 $\mu\text{in}$                         | Laser Micrometer                             |
| Cylindrical Rings <sup>5</sup>          |                                        |                                           | Comparison to                                |
| Inside Diameter                         | (0.04 to < 0.25) in                    | (12 + 1.3L) $\mu\text{in}$                | Universal Length<br>Measuring Machine,       |
|                                         | (0.25 to < 4) in                       | (10 + 1.3L) $\mu\text{in}$                | Master Ring Gages                            |
|                                         | (4 to 14) in                           | (11 + 1.3L) $\mu\text{in}$                | (Non-commercial Cal)                         |
| Cylindrical Rings <sup>5</sup>          |                                        |                                           | Comparison to                                |
| Inside Diameter                         | (0.04 to < 0.25) in                    | (15 + 1.9L) $\mu\text{in}$                | Universal Length<br>Measuring Machine,       |
|                                         | (0.25 to < 4) in                       | (13 + 1.9L) $\mu\text{in}$                | Working Reference Rings                      |
|                                         | (4 to 14) in                           | (19 + 1.9L) $\mu\text{in}$                |                                              |

## Length – Dimensional Metrology

| Parameter/Equipment                                         | Range                                                                                                     | Expanded Uncertainty of Measurement (+/-)                                                                             | Reference Standard, Method, and/or Equipment                          |
|-------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Laser Micrometers <sup>1,5</sup>                            | Up to 0.1 in<br>(0.1 to 0.4) in<br>(0.4 to 1) in                                                          | 13 µin<br>8 µin<br>(12 + 5L) µin                                                                                      | Comparison to Characterized Master Pin Gages                          |
| Measuring Tapes, Rulers <sup>5</sup>                        | Up to 1 ft<br>(1 to 3) ft<br>(3 to 1 000) ft                                                              | (760 + 0.5L) µin<br>(740 + 2L) µin<br>(23L) µin                                                                       | Direct Measure using Vision System                                    |
| Laser Distance Meters                                       | Up to 1 m                                                                                                 | 0.31 mm                                                                                                               | Direct Measure using Vision System                                    |
| Surface Plates <sup>1,4</sup>                               |                                                                                                           |                                                                                                                       |                                                                       |
| Overall Flatness                                            | (17 to 168) inDL                                                                                          | (24 + √DL) µin                                                                                                        | In accordance with ASME B89.3.7 using Electronic Level System         |
| Local Area Flatness (Repeat Readings)                       | Up to 0.001 in                                                                                            | 31 µin                                                                                                                | Repeat-o-Meter w/ Supramess                                           |
| Thread Plug Gages <sup>5</sup><br>Pitch Diameter 60° Thread | Up to 1 in<br>(> 1 to 4) in<br>(> 4 to 10) in<br><br>Up to 25 mm<br>(> 25 to 100) mm<br>(> 100 to 250) mm | (78 + 2.4L) µin<br>(78 + 3.2L) µin<br>(78 + 3.5L) µin<br><br>(2 + 2.4L) µm<br>(2 + 2.8L) µm<br>(2 + 2.8L) µm          | Comparison to Universal Length Measuring Machine, Master Thread Wires |
| Thread Plug Gages <sup>5</sup><br>Major Diameter            | Up to 1 in<br>(> 1 to 4) in<br>(> 4 to 10) in<br><br>Up to 25 mm<br>(> 25 to 100) mm<br>(> 100 to 250) mm | (2.4 + 32L) µin<br>(3.2 + 32L) µin<br>(3.5 + 32L) µin<br><br>(2.4 + 0.78L) µm<br>(2.8 + 0.78L) µm<br>(2.8 + 0.78L) µm | Comparison to Universal Length Measuring Machine, Gage Blocks         |
| Step Height                                                 | Up to 1 in                                                                                                | 32 µin                                                                                                                | Comparison to Gage Amplifier, Probe, Gage Blocks                      |
| Tapered Thread Plug<br>Pitch Diameter                       | Up to 3 in                                                                                                | 90 µin                                                                                                                | Comparison to Universal Length Measuring Machine, Master Thread Wires |
| Standoff                                                    | Up to 1 in                                                                                                | 31 µin                                                                                                                | Gage Amplifier, Probe                                                 |
| Tapered Thread Ring Gage                                    | Up to 3 in                                                                                                | 90 µin                                                                                                                | Comparison to Master Plug                                             |

### Length – Dimensional Metrology

| Parameter/Equipment                               | Range                                    | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment |
|---------------------------------------------------|------------------------------------------|-------------------------------------------|----------------------------------------------|
| Thread Ring Gage<br>Inner Pitch Diameter          | Up to 1 in<br>(1 to 4) in<br>(4 to 7) in | 79 $\mu$ in<br>80 $\mu$ in<br>83 $\mu$ in | Comparison to<br>Master Plug                 |
| Wire Crimpers/Dies <sup>1,5</sup><br>Die Diameter | (0.011 to 0.625) in                      | (34 + 4L) $\mu$ in                        | Comparison to<br>Pin Gage Set                |
| Crimp Height                                      | (0.001 to 0.8) in                        | 180 $\mu$ in                              | Crimp Height Micrometer                      |

### Mass and Mass Related

| Parameter/Equipment                                             | Range                                             | Expanded Uncertainty of Measurement (+/-)                             | Reference Standard, Method, and/or Equipment                                                 |
|-----------------------------------------------------------------|---------------------------------------------------|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| Air Velocity<br>Pitot Tube, Constant<br>Temperature Anemometers | (0.3 to 2) m/s<br>(2 to 30) m/s                   | 0.76 % of reading + 0.02 m/s<br>0.6 % of reading                      | Comparison to<br>Laser Doppler<br>Velocimeter,<br>Westenberg Westi-box<br>Wind Tunnel System |
|                                                                 | (0.3 to 2) m/s<br>(2 to 60) m/s                   | 0.06 m/s<br>1.4 % of reading                                          | Westenberg Westi-box<br>Wind Tunnel System                                                   |
| Air Velocity<br>Vane Anemometers                                | (0.3 to 2) m/s<br>(2 to 30) m/s<br>(30 to 60) m/s | 0.87 % of reading + 0.04 m/s<br>0.95 % of reading<br>2.4 % of reading | Comparison to<br>Laser Doppler<br>Velocimeter,<br>Westenberg Westi-box<br>Wind Tunnel System |
| Shore Hardness Test Blocks<br>Type A                            | (15 to 95) duro                                   | 1.8 duro                                                              | Comparison to<br>Type A Digital<br>Durometer                                                 |
| Type D                                                          | (15 to 95) duro                                   | 1.6 duro                                                              | Type D Digital<br>Durometer                                                                  |

## Mass and Mass Related

| Parameter/Equipment                                                                                               | Range                                                                                                         | Expanded Uncertainty of Measurement (+/-)                                                         | Reference Standard, Method, and/or Equipment                                                                      |
|-------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Durometers<br>(Type A, B, C, D, E, DO, O)<br>Indenter Dimensions<br>Length<br>Angle<br>Radius<br><br>Spring Force | Up to 1 in<br>Up to 40°<br>50 µin to 1 in<br><br>Up to 60 duro<br>(60 to 100) duro                            | 84 µin<br>0.006°<br>120 µin<br><br>0.73 duro<br>0.94 duro                                         | Direct Verification per ASTM D2240 using<br><br>Multi-axis Vision System<br><br>Duro Calibrator                   |
| Balances and Scales <sup>1,6</sup><br>(SI)                                                                        | Up to 500 mg<br>(0.5 to 5) g<br>(5 to 20) g<br>20 g to 10 kg<br>(10 to 25) kg<br>(25 to 35) kg                | 12 µg<br>40 µg<br>90 µg<br>0.000 31 % of reading<br>0.000 3 % of reading<br>0.000 25 % of reading | ASTM E617 Class 1 weights and internal calibration procedure utilized for the calibration of the weighing system. |
| Balances and Scales <sup>1,6</sup><br>(SI)                                                                        | Up to 3 mg<br>(3 to 10) mg<br>(10 to 50) mg<br>(50 to 100) mg<br>(100 to 300) mg                              | 30 µg<br>40 µg<br>50 µg<br>60 µg<br>70 µg                                                         | ASTM E617 Class 3 weights and internal calibration procedure utilized for the calibration of the weighing system. |
| Balances and Scales <sup>1,6</sup><br>(SI)                                                                        | (300 to 500) mg<br>(0.5 to 3) g<br>(3 to 5) g<br>(5 to 10) g<br>(10 to 30) g<br>(30 to 50) g<br>(50 to 100) g | 0.1 mg<br>0.15 mg<br>0.2 mg<br>0.3 mg<br>0.5 mg<br>0.7 mg<br>1.2 mg                               | ASTM E617 Class 3 weights and internal calibration procedure utilized for the calibration of the weighing system. |
| Balances and Scales <sup>1,6</sup><br>(Avoirdupois)                                                               | Up to 0.5 lb<br>(0.5 to 2) lb<br>(2 to 10) lb<br>(10 to 1 150) lb                                             | 0.024 % of reading<br>0.018 % of reading<br>0.013 % of reading<br>0.012 % of reading              | NIST Class F weights and internal calibration procedure utilized for the calibration of the weighing system.      |
| Mass Determination                                                                                                | Up to 1.2 kg                                                                                                  | 0.002 8 mg/g + 6.8 mg                                                                             | Direct Measure using Mettler Toledo XS1203S Precision Balance                                                     |
| Force<br>(Tension and Compression)                                                                                | Up to 400 lbf                                                                                                 | 0.012 % of reading                                                                                | Comparison to Deadweight                                                                                          |

## Mass and Mass Related

| Parameter/Equipment                           | Range                                                                                                                                                             | Expanded Uncertainty of Measurement (+/-)                                                                                                                                                                                                              | Reference Standard, Method, and/or Equipment              |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| Force                                         |                                                                                                                                                                   |                                                                                                                                                                                                                                                        |                                                           |
| Compression                                   | (2.5 to 100) lbf<br>(100 to 500) lbf<br>(500 to 2 000) lbf<br>(10 000 to 25 000) lbf<br>(25 000 to 100 000) lbf                                                   | 0.03 % of reading + 0.02 lbf<br>0.02 % of reading + 0.05 lbf<br>0.02 % of reading + 0.15 lbf<br>0.04 % of reading + 1.2 lbf<br>0.04 % of reading + 9 lbf                                                                                               | Comparison to Morehouse PCM/UCM with Precision Load Cells |
| Tension                                       | (2.5 to 100) lbf<br>(100 to 500) lbf<br>(500 to 2 000) lbf<br>(10 000 to 25 000) lbf<br>(25 000 to 100 000) lbf                                                   | 0.03 % of reading + 0.03 lbf<br>0.02 % of reading + 0.06 lbf<br>0.02 % of reading + 0.19 lbf<br>0.04 % of reading + 1.2 lbf<br>0.04 % of reading + 9 lbf                                                                                               |                                                           |
| Pneumatic Absolute Pressure Devices           | Up to 14.7 psia<br>(14.7 to 39.7) psia<br>(39.7 to 514.7) psia                                                                                                    | 0.002 5 psi<br>0.000 7 % of reading + 0.002 3 psi<br>0.006 5 % of reading                                                                                                                                                                              | Comparison to Ruska 7250xi Pressure Controller/Calibrator |
| Pneumatic Absolute Pressure Devices           | Up to 30 psia<br>(30 to 1 000) psia                                                                                                                               | 0.002 4 psi<br>0.007 % of reading + 0.000 48 psi                                                                                                                                                                                                       | Comparison to DHI PPC4 Pressure Controller                |
| Hydraulic Absolute Pressure Devices           | (500 to 1 600) psia<br>(> 1 600 to 16 000) psia                                                                                                                   | 0.011 % of reading + 0.07 psi<br>0.015 % of reading + 0.01 psi                                                                                                                                                                                         | Comparison to Fluke P3125-3 Deadweight Tester, Barometer  |
| Pneumatic Gauge Pressure Devices <sup>1</sup> | (0 to 25) psig<br>(25 to 500) psig                                                                                                                                | 0.001 4 % of reading + 0.001 3 psi<br>0.006 7 % of reading                                                                                                                                                                                             | Comparison to Ruska 7250xi Pressure Controller/Calibrator |
| Pneumatic Gauge Pressure Devices <sup>1</sup> | (500 to 1 000) psig                                                                                                                                               | 0.006 2 % of reading + 0.000 1 psi                                                                                                                                                                                                                     | Comparison to DHI PPC4 Pressure Controller                |
| Pneumatic Vacuum Devices <sup>1</sup>         | (-14.7 to 0) psig                                                                                                                                                 | 0.000 64 % of reading + 0.001 3 psi                                                                                                                                                                                                                    | Comparison to Ruska 7250xi Pressure Controller/Calibrator |
| Pneumatic Compound Devices <sup>1</sup>       | (-60 to -6) inH <sub>2</sub> O<br>(-6 to 6) inH <sub>2</sub> O<br>(6 to 60) inH <sub>2</sub> O<br><br>(-14.7 to -7.5) psi<br>(-7.5 to 7.5) psi<br>(7.5 to 30) psi | 0.007 % of reading + 0.000 005 inH <sub>2</sub> O<br>0.002 1 % of reading + 0.000 3 inH <sub>2</sub> O<br>0.007 % of reading + 0.000 005 inH <sub>2</sub> O<br><br>0.006 5 % of reading<br>0.001 5 % of reading + 0.000 38 psi<br>0.006 5 % of reading | Comparison to Ruska 7252i Pressure Controller/Calibrator  |



## Mass and Mass Related

| Parameter/Equipment                           | Range                                                                                            | Expanded Uncertainty of Measurement (+/-)                                            | Reference Standard, Method, and/or Equipment                              |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| Hydraulic Gauge Pressure Devices <sup>1</sup> | (500 to 1 600) psig<br>(> 1 600 to 16 000) psig                                                  | 0.1 psi<br>0.006 1 % of reading                                                      | Comparison to<br>Fluke P3125-3<br>Deadweight Tester                       |
| Torque Tools <sup>1</sup>                     | (1 to 10) lbf·in<br>9 lbf·in to 800 lbf·ft                                                       | 0.37 % of reading + 0.028 lbf·in<br>1 % of reading                                   | Comparison to<br>Torque Calibration<br>System                             |
| Pneumatic Torque Tools                        | 0.2 lbf·in to 18 lbf·in<br>18 lbf·in to 70 lbf·in<br>8 lbf·in to 130 lbf·in                      | 0.55 lbf·in<br>1.1 lbf·in<br>0.89 lbf·in                                             | Comparison to<br>Imada Torque Tester                                      |
| Torque Transducers                            | 2.5 ozf·in to 12.5 lbf·in<br>(12 to 150) lbf·in<br>(12.5 to 250) lbf·ft<br>(250 to 2 000) lbf·ft | 0.085 % of reading<br>0.052 % of reading<br>0.048 % of reading<br>0.053 % of reading | Comparison to<br>Master Weights,<br>Butterfly Wheels,<br>40 in Torque Arm |
| Torque Angle<br>(Fixed Points)                | 45° and 225°<br>90° and 270°<br>135° and 315°<br>180° and 360°                                   | 0.67°<br>0.67°<br>0.67°<br>0.67°                                                     | Comparison to<br>Torque Angle Fixture                                     |

## Thermodynamics

| Parameter/Equipment | Range                                                                                                                                                        | Expanded Uncertainty of Measurement (+/-)                        | Reference Standard, Method, and/or Equipment                                                                                                      |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Humidity – Source   | (15.56 to 25) °F<br>0 %RH                                                                                                                                    | 0.003 %RH                                                        | Comparison to<br>Thunder Scientific 3900<br>Humidity Generator,<br>Liquid Nitrogen (N <sub>2</sub> ),<br>Vaisala DMT-152<br>Dew Point Transmitter |
| Humidity – Source   | (-10 to 15) °C<br>(10 to 75) %RH<br>(75 to 95) %RH<br>(15 to 35) °C<br>(10 to 95) %RH<br>(35 to 70) °C<br>(10 to 50) %RH<br>(50 to 70) %RH<br>(70 to 95) %RH | 0.5 %RH<br>0.65 %RH<br>0.5 %RH<br>0.5 %RH<br>0.7 %RH<br>0.85 %RH | Comparison to<br>Thunder Scientific 2500<br>Humidity Generator                                                                                    |

## Thermodynamics

| Parameter/Equipment                                                     | Range                                                                                                                | Expanded Uncertainty of Measurement (+/-)                                                      | Reference Standard, Method, and/or Equipment                                                             |
|-------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Humidity – Measure <sup>1</sup>                                         | (-20 to 15) °C<br>Up to 95 %RH<br>(15 to 25) °C<br>(10 to 90) %RH<br>(90 to 95) %RH<br>(25 to 40) °C<br>Up to 95 %RH | 0.008 4 % of reading + 1.2 %RH<br><br>1.3 %RH<br>1.9 %RH<br><br>0.008 4 % of reading + 1.2 %RH | Direct Measure using<br>Vaisala MI70/HMP76B<br>Temperature/Humidity<br>Indicator/Probe                   |
| Dew/Frost Point – Source <sup>1</sup>                                   | (-85 to -80) °C<br>(-80 to -70) °C<br>(-70 to -60) °C<br>(-60 to -50) °C<br>(-50 to -40) °C<br>(-40 to -10) °C       | 1.2 °C<br>0.61 °C<br>0.4 °C<br>0.36 °C<br>0.25 °C<br>0.15 °C                                   | Comparison to<br>Thunder Scientific 3900<br>Humidity Generator                                           |
| Dew/Frost Point – Source <sup>1</sup>                                   | (-10 to 20) °C<br>(20 to 30) °C<br>(30 to 40) °C<br>(40 to 65) °C                                                    | 0.13 °C<br>0.15 °C<br>0.16 °C<br>0.17 °C                                                       | Comparison to<br>Thunder Scientific 2500<br>Humidity Generator                                           |
| Temperature – Source <sup>1</sup><br>(Temperature Measuring<br>Devices) | (-75 to -70) °C<br>(-70 to 100) °C<br>(100 to 200) °C<br>(200 to 400) °C<br>(400 to 600) °C                          | 0.039 °C<br>0.039 °C<br>0.051 °C<br>0.074 °C<br>0.092 °C                                       | Comparison to<br>AccuMac AM1760 SPRT,<br>Black Stack,<br>Hart Bath or<br>Metrology Well                  |
| Temperature – Source <sup>1</sup><br>(Temperature Measuring<br>Devices) | (600 to 800) °C<br>(800 to 1 000) °C<br>(1 000 to 1 200) °C                                                          | 1.2 °C<br>1.5 °C<br>3.6 °C                                                                     | Comparison to<br>Fluke 5649 Type R<br>Thermocouple Probe,<br>HP 3458<br>8.5 Digit Multimeter,<br>Furnace |
| Temperature – Measure <sup>1</sup>                                      | (-195 to 0) °C<br>(0 to 420) °C<br>(420 to 660) °C                                                                   | 0.015 °C<br>0.03 °C<br>0.039 °C                                                                | Direct Measure using<br>AccuMac AM1760 SPRT,<br>Black Stack                                              |
| Temperature – Measure <sup>1</sup>                                      | (600 to 800) °C<br>(800 to 1 000) °C<br>(1 000 to 1 450) °C                                                          | 0.55 °C<br>0.76 °C<br>2.9 °C                                                                   | Comparison to<br>Fluke 5649 Type R<br>Thermocouple Probe,<br>HP 3458<br>8.5 Digit Multimeter             |

## Thermodynamics

| Parameter/Equipment                                                           | Range                                                                                                                                                                                                                        | Expanded Uncertainty of Measurement (+/-)                                                                                 | Reference Standard, Method, and/or Equipment                                                                                       |
|-------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Infrared Temperature – Source<br>(Infrared Temperature Measuring Instruments) | (-15 to 0) °C<br>(0 to 50) °C<br>(50 to 100) °C<br>(100 to 120) °C<br>(120 to 200) °C<br>(200 to 350) °C<br>(350 to 500) °C<br>(500 to 600) °C<br>(600 to 700) °C<br>(700 to 800) °C<br>(800 to 900) °C<br>(900 to 1 000) °C | 0.44 °C<br>0.44 °C<br>0.48 °C<br>0.59 °C<br>0.64 °C<br>1.1 °C<br>1.8 °C<br>4.4 °C<br>4.7 °C<br>5.1 °C<br>5.4 °C<br>5.8 °C | Comparison to Blackbody Source (Flat Plate)<br>$\lambda = (8 \text{ to } 14) \mu\text{m}$ ,<br>$\varepsilon = (0.9 \text{ to } 1)$ |
| Surface Probe Measuring Equipment                                             | (20 to 100) °C                                                                                                                                                                                                               | 0.68 °C                                                                                                                   | Comparison to Fluke 3125 Surface Probe Calibrator                                                                                  |
| Surface Probe Measuring Equipment                                             | (100 to 300) °C                                                                                                                                                                                                              | 1.2 °C                                                                                                                    | Comparison to Pyromation RAT185 RTD, Fluke 1502 Thermometer Readout                                                                |
| Centrifuge Chamber <sup>1</sup> Temperature                                   | (-40 to 100) °C                                                                                                                                                                                                              | 1.2 °C                                                                                                                    | Comparison to Altek 422 Thermocouple Calibrator, Type T Thermocouple Probe                                                         |

## Time and Frequency

| Parameter/Equipment   | Range        | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment                                                                      |
|-----------------------|--------------|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Frequency – Reference | 10 MHz       | 1.6 pHz/Hz                                | Comparison to Pendulum FTR-210R GPS Disciplined Oscillator                                                        |
| Period – Source       | (1 to 100) s | 58 ns/s                                   | Comparison to Keysight 33250A Function/Arbitrary Waveform Generator, Pendulum FTR-210R GPS Disciplined Oscillator |

## Time and Frequency

| Parameter/Equipment                                                                       | Range                                                                                                                                                                                                                                         | Expanded Uncertainty of Measurement (+/-)                                                                                                                          | Reference Standard, Method, and/or Equipment                                                                                     |
|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Period – Measure                                                                          | (1 to 10) s<br>(10 to 100) s                                                                                                                                                                                                                  | 17 $\mu$ s<br>53 $\mu$ s                                                                                                                                           | Comparison to<br>HP 53132A<br>Universal Counter,<br>Pendulum FTR-210R<br>GPS Disciplined Oscillator                              |
| Frequency – Source                                                                        | 1 Hz to 80 MHz                                                                                                                                                                                                                                | 58 nHz/Hz                                                                                                                                                          | Comparison to<br>Keysight 33250A<br>Function/Arbitrary<br>Waveform Generator,<br>Pendulum FTR-210R<br>GPS Disciplined Oscillator |
| Frequency – Measure                                                                       | 1 Hz to 1 kHz<br>1 kHz to 10 MHz<br>(10 to 225) MHz                                                                                                                                                                                           | 1.5 nHz/Hz + 5.5 $\mu$ Hz<br>1.3 nHz/Hz + 4 $\mu$ Hz<br>1.2 nHz/Hz                                                                                                 | Comparison to<br>HP 53132A<br>Universal Counter,<br>Pendulum FTR-210R<br>GPS Disciplined Oscillator                              |
| AC Duty Cycle – Source <sup>1</sup><br>Square Wave: < 3.3 Vp-p<br>Freq: 0.1 Hz to 100 kHz | (1 to 10) % Duty Cycle<br>10 $\mu$ s to 100 s<br>(10 to 49) % Duty Cycle<br>10 $\mu$ s to 100 s<br>50 % Duty Cycle<br>10 $\mu$ s to 100 s<br>(51 to 90) % Duty Cycle<br>10 $\mu$ s to 100 s<br>(90 to 99) % Duty Cycle<br>10 $\mu$ s to 100 s | 0.039 % of reading + 78 ns<br>0.62 % of reading + 78 ns<br>0.001 6 % of reading + 78 ns<br>0.62 % of reading + 78 ns<br>0.039 % of reading + 78 ns                 | Comparison to<br>Fluke 5522A<br>Multiproduct Calibrator                                                                          |
| Stopwatches/Timers                                                                        | Up to 19.99 s/d                                                                                                                                                                                                                               | 59 ms/d                                                                                                                                                            | Direct Measure using<br>Vibrograf 4500<br>Timometer                                                                              |
| Time – Measure <sup>1</sup>                                                               | Up to 24 hr                                                                                                                                                                                                                                   | 1.1 s/d + 0.2 s                                                                                                                                                    | Comparison to<br>Stopwatch                                                                                                       |
| Non-Contact Rate of Rotation<br>(Including Centrifuges) <sup>1,2</sup>                    | (5 to 99.999) rpm<br>(100 to 999.99) rpm<br>(1 000 to 9 999.9) rpm<br>(10 000 to 99 999) rpm<br>(100 000 to 200 000) rpm                                                                                                                      | 0.012 % of reading + 0.001 2 rpm<br>0.012 % of reading + 0.012 rpm<br>0.012 % of reading + 0.12 rpm<br>0.014 % of reading + 1.2 rpm<br>0.014 % of reading + 12 rpm | Comparison to<br>Optical Tachometer                                                                                              |

## DIMENSIONAL MEASUREMENT

### 1 Dimensional

| Parameter/Equipment                                                                                                    | Range                                                                                                          | Expanded Uncertainty of Measurement (+/-)                                                                                                | Reference Standard, Method, and/or Equipment                                                       |
|------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Geometric Measurement of Fixtures, Gauges, Dies and Molds <sup>5</sup><br>(Length – Single Axis)<br>Outside Dimensions | Up to 1 in<br>(1 to 7) in<br>(7 to 12) in                                                                      | $(6 + 1L) \mu\text{in}$<br>$(4 + 3.5L) \mu\text{in}$<br>$(4L) \mu\text{in}$                                                              | Universal Length Measuring Machine utilized as the reference standard for 1-D Length Measurements. |
| Inside Dimensions                                                                                                      | (0.04 to 0.125) in<br>(0.125 to 0.25) in<br>(0.25 to 1) in<br>(1 to 2.5) in<br>(2.5 to 10) in<br>(10 to 14) in | 11 $\mu\text{in}$<br>11 $\mu\text{in}$<br>11 $\mu\text{in}$<br>17 $\mu\text{in}$<br>$(18 + 3L) \mu\text{in}$<br>$(38 + 3L) \mu\text{in}$ |                                                                                                    |

### 2 Dimensional

| Parameter/Equipment                                                                | Range                     | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment                                             |
|------------------------------------------------------------------------------------|---------------------------|-------------------------------------------|------------------------------------------------------------------------------------------|
| Geometric Measurement of Fixtures, Gauges, Dies and Molds <sup>5</sup><br>X-Y Axis | Up to 16 in               | $(97 + 5.8L) \mu\text{in}$                | Multi-axis Vision System utilized as the reference standard for 2-D Length Measurements. |
| Angles <sup>5</sup>                                                                | Up to 360°<br>Up to 12 in | $(\frac{20}{L(\text{in})} + 1.2)''$       | Multi-axis Vision System utilized as the reference standard for Angle Measurements.      |
| Radius <sup>5</sup>                                                                | Up to 8 in                | $(97 + 7L) \mu\text{in}$                  | Multi-axis Vision System utilized as the reference standard for Radius Measurements.     |


### 3 Dimensional

| Parameter/Equipment                                          | Range                                                 | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment                                               |
|--------------------------------------------------------------|-------------------------------------------------------|-------------------------------------------|--------------------------------------------------------------------------------------------|
| Dimensional Measurement –<br>3D <sup>5</sup><br>(Volumetric) | X = Up to 12 in<br>Y = Up to 12 in<br>Z = Up to 10 in | (191 + 5.8L) μin                          | Multi-axis Vision System<br>utilized as the reference<br>standard for 3-D<br>Measurements. |

Calibration and Measurement Capability (CMC) is expressed in terms of the measurement parameter, measurement range, expanded uncertainty of measurement and reference standard, method, and/or equipment. The expanded uncertainty of measurement is expressed as the standard uncertainty of the measurement multiplied by a coverage factor of 2 ( $k=2$ ), corresponding to a confidence level of approximately 95%.

Notes:

- On-site calibration service is available for this parameter, since on-site conditions are typically more variable than those in the laboratory, larger measurement uncertainties are expected on-site than what is reported on the accredited scope.
- As frequency deviates from the listed values, uncertainty may be higher than stated. If needed, contact the laboratory for more information regarding uncertainties at frequency and range combinations other than the ones shown.
- Carrier range is the output amplitude capability of the fundamental wave. Up to 10 harmonics can be placed on the fundamental wave up to the amplitude of the value shown as the harmonic range. The uncertainties shown are for both the fundamental and harmonic amplitudes within the frequency range shown.
- The uncertainties shown are for the most favorable conditions. There is an increase in uncertainty that corresponds to the laboratory's AC voltage and current uncertainties at different frequencies other than the ones shown. Power factors (PF) other than the one shown contribute to the power uncertainty. PF is related to the cosine of phase. Therefore, uncertainties track the laboratory's phase uncertainty closely at PF near one but are magnified heavily as PF approaches zero. The lab may also report reactive power, apparent power, and power factor under this accreditation. If needed, contact the laboratory for more information regarding uncertainties at frequency and power factor combinations other than the ones shown.
- " = arc-second; L = length in inches or millimeter; DL = diagonal length in inches; rpm = revolutions per minute.
- The CMC for scales and balances is highly dependent upon the resolution of the unit under test. The CMC presented here does not include the resolution of the unit under test. The resolution will be included in the reported measurement uncertainty at the time of calibration.
- Uncertainties are for cardinal point temperatures, measurement between cardinal temperate points are available with greater uncertainties.
- The stated uncertainty is the laboratory's ability to source a fast rise pulse that is approximately 500 ps, 350 ps, 125 ps, and 25 ps. In the typical application of measuring rise time of an oscilloscope, this value is one of the contributing factors, but other factors are derived from the DUT. The known source rise time is mathematically removed from the total measured rise time measured on the DUT.
- 0.6R will be added to the Measurement Uncertainty at the time of calibration (where R = resolution of the device under calibration).
- Unless otherwise specified in the far-right hand column, the calibration procedure/method being utilized by the laboratory was written and validated internally.



Jason Stine, Vice President