WT12 Series Mechanical Dynamometer

TR4NSC4T

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Visit us at Transcat.com!

The CHATILLON® WT12 Series mechanical dynamometer may be used as a weighing tensiometer or crane scale. This precision weighing instrument features a large 12-inch (305 mm) dial face with shatter-resistant dial cover in a strong aluminum housing. Available with pound or kilogram dial face, the WT12 Series accuracy is better than 0.5% of full scale. A manually engaged clutch "freezes" the pointer at is maximum reading for exact reading of peak weight. Needle bearings in shackles prevent brinneling under heavy loads and eliminate shackle misalignment. Mechanism sealed against dust and dirt. Oiling not required. Dynamometer comes with NIST traceable Certificate of Calibration with Data.

Features

- Pound or Kilogram Dials
 - Capacities up to 20,000 lb (10,000 kg)
- Rugged Cast Aluminum Housing
- ☐ Large, 12-inch (305 mm) Easy-to-Read Dial with Shatter-resistant Dial Cover, Anti-Parallax
- Maximum Reading Button
- Calibration traceable to NIST
- 4:1 Ultimate Safety Factor
- 2 Year Warranty
- Certificate of Calibration with NIST Traceable Data

Specifications

Accuracy: ±0.5% of Full Scale

Maximum Overload: 125% of Rated Capacity

Tare Capacity: 20% of Rated Capacity

Dial Revolutions: Full Scale in 1 Revolution

Dial Resolution: 200:1

Operating Temperature: -50°F to 140°F (-45°C to 60°C)



Ordering

Scale with Shackles

Model	Capacity	Length			
WT12-00500	500 x 2 lb	13-1/4 in (337 mm)			
WT12-01000	1000 x 5 lb	13-1/4 in (337 mm)			
WT12-02000	2000 x 10 lb	13-1/4 in (337 mm)			
WT12-05000	5000 x 20 lb	13-1/4 in (337 mm)			
WT12-10000	10000 x 50 lb	15 in (381 mm)			
WT12-20000	20000 x 100 lb	15 in (381 mm)			
THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TO THE PERSON NA		3000			
WT12-00500K	500 x 2 kg	13-1/4 in (337 mm)			
WT12-01000K	1000 x 5 kg	13-1/4 in (337 mm)			
WT12-02000K	2000 x 10 kg	13-1/4 in (337 mm)			
WT12-05000K	5000 x 20 kg	15 in (381 mm)			
WT12-10000K	10000 x 50 kg	15 in (381 mm)			
THE RESERVE OF THE PERSON NAMED IN					

With Eye Hook


Model	Capacity	Length				
WT12-00500-EH	500 x 2 lb	19-13/16 in (503 mm)				
WT12-01000-EH	1000 x 5 lb	19-13/16 in (503 mm)				
WT12-02000-EH	2000 x 10 lb	19-13/16 in (503 mm)				
WT12-05000-EH	5000 x 20 lb	19-13/16 in (503 mm)				
WT12-10000-EH	10000 x 50 lb	26-5/16 in (668 mm)				
WT12-20000-EH	20000 x 100 lb	26-5/16 in (668 mm)				
WT12-00500K-EH	500 x 2 kg	19-13/16 in (503 mm)				
WT12-01000K-EH	1000 x 5 kg	19-13/16 in (503 mm)				
WT12-02000K-EH	2000 x 10 kg	19-13/16 in (503 mm)				
WT12-05000K-EH	5000 x 20 kg	26-5/16 in (668 mm)				
WT12-10000K-EH	10000 x 50 kg	26-5/16 in (668 mm)				

With Swivel Hook

Model	Capacity	Length		
WT12-00500-SH	500 x 2 lb	21-1/2 in (546 mm)		
WT12-01000-SH	1000 x 5 lb	21-1/2 in (546 mm)		
WT12-02000-SH	2000 x 10 lb	21-1/2 in (546 mm))		
WT12-05000-SH	5000 x 20 lb	21-1/2 in (546 mm)		
WT12-10000-SH	10000 x 50 lb	28-3/8 in (721 mm)		
WT12-20000-SH	20000 x 100 lb	28-3/8 in (721 mm)		
WT12-00500K-SH	500 x 2 kg	21-1/2 in (546 mm)		
WT12-01000K-SH	1000 x 5 kg	21-1/2 in (546 mm)		
WT12-02000K-SH	2000 x 10 kg	21-1/2 in (546 mm)		
WT12-05000K-SH	5000 x 20 kg	28-3/8 in (721 mm)		
WT12-10000K-SH	10000 x 50 kg	28-3/8 in (721 mm)		



Dimensions



Dimensions with Shackles

Capacity		Α	В	С	D	Ε	F	G	Н
500 - 5000	(inch)	13-1/4	12	1-11/16	3	11-3/4	3-1/8	4-9/16	5/8
	(mm)	337	305	43	76	298	79	116	16
10,000 - 20,0	00 (inch)	15	13-1/4	1-7/16	3-1/4	11-3/4	3-1/8	4-3/4	7/8
	(mm)	381	337	37	83	298	79	121	22

Accessories

Part No.	Description
13400	Eye Hook (500 - 5000 lb)
13401	Eye Hook (10,000 - 20,000 lb)
13404	Swivel Hook (500 - 5000 lb)
13405	Swivel Hook (10,000 - 20,000 lb)
20548	Carrying Case, Metal

Notes:

Dynamometers with "EH" come standard with Eye Hook. Dynamometer with "SH" come standard with Swivel Hook. Carrying Case must be ordered separately.



Optional Carrying Case



Eye Hook - EH



Swivel Hook- SH







35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001