

Ground Resistance Testers

MODELS 6422, 6424

Strategic Advantages

- Two instruments in one – test Ground and Bonds
- Low cost, great performance and feature rich
- One button connect - press - read operation – *eliminates testing errors*
- CAT IV 600V rated – *highest safety rated Ground Testers on the market*
- Storage of 3 measurements along with average and % deviation – *easily determine proper test results (Model 6424)*
- Automatic frequency adjustments – *improves accuracy*
- Automatic continuity and resistance check of the H electrode
- Voltage and current measurement capability (Model 6424)
- IP65 dust proof, weather-resistant and flame retardant – *works in all environments*



Complete Kits Available
(provides the ability to test most systems)

Our products are backed by over 125 years of experience in test and measurement equipment, and encompass the latest international standards for quality and safety.

Technical Assistance (800) 343-1391
www.aemc.com


 **AEMC**[®]
INSTRUMENTS
CHAUVIN ARNOUX GROUP

GROUND RESISTANCE TESTERS

MULTI-FUNCTION

MODELS 6422 & 6424

To keep your installation safe, measure your resistance connection to earth!




6422



6424

These new Ground Resistance Testers are both economical and feature rich. They are ideal for testing commercial, residential and light industrial grounding systems. Their innovative design simplifies the process and provides reliable results eliminating confusion in setting it up correctly. A simple one button connect - press - read operation is all that is needed. The Model 6424 is capable of storing and calculating the measurements from the simplified 62% test method and displaying the average and % deviation which is important in determining correct pole spacing for the test.



FEATURES

- Simple, one button operation - eliminates errors in testing
- Test button turns green when measurement is stable
- 2P resistance/ 3P ground resistance measurement up to 50 kΩ for highly resistive terrain
- Large back lit digital display – easier to read in all lighting conditions
- Automatic hold function - retains last measurement after the reading stabilizes ensuring the measurement is valid
- Automatic test frequency selection between 128 and 256 Hz, providing stable results in adverse environments
- Powers up in 2 pole mode – automatically checks the injector lead connection when connected to the H auxiliary rod
- Convenient storage of the three measurements along with the average and % deviation - easily determines proper test results
- Built in test lead compensation capability – improves the accuracy of low resistance measurements
- CAT IV 600 V rated for a high level of operator safety
- Checks AC/DC voltage and AC leakage current (Model 6424)
- Stores 52, 62 and 72% measurements – eliminates errors in determining the ground resistance (Model 6424)
- Leakage current measurement from 0.5 mA to 70 A (Model 6424)
- Battery recharging via AC adapter, USB or vehicle DC port b (Model 6424)
- Color coded leads and terminals provide fast, error-free connection hook-up
- Detects and prohibits hazardous voltage measurement
- Direct access to all functions, even when wearing work gloves
- Rugged water resistance case, for all terrain use
- Built-in display stand to prop up instrument for seeing the display better when placed on the ground

GROUND RESISTANCE TESTERS

MULTI-FUNCTION

MODELS 6422 & 6424

SPECIFICATIONS

MODELS	6422			6424			
ELECTRICAL							
Voltage							
Range	-			0.1-600V _{AC/DC}			
Resolution	-			0.1V			
Accuracy	-			±(1%R + 1ct)			
Current							
Range	-			0.5-60.00A _{AC} (requires optional MN72 probe)			
Resistance (2P Mode)							
Measurement Range	0.05-99.99Ω, 80.0-999.9Ω , 0.800-9.999kΩ, 8.00-50.00kΩ						
Resolution	0.01Ω, 0.1Ω, 1Ω, 10Ω						
Intrinsic Uncertainty	± (2%R + 10 ct), ± (2%R + 2 ct), ±(2%R + 1 ct), ±(2%R + 1 ct)						
Ground Resistance (3P Mode)							
Measurement Range	0.50-99.99Ω	80.0-999.9Ω	0.800-2.000kΩ	0.50-99.99Ω	80.0-999.9Ω	0.800-9.999kΩ	8.00-50.000kΩ
Resolution	0.01Ω	0.1Ω	1Ω	0.01Ω	0.1Ω	1Ω	10Ω
Intrinsic Uncertainty	± (1%R + 10ct)	± (1%R + 2ct)	± (1%R + 1ct)	± (1%R + 10ct)	± (1%R + 2ct)	± (1%R + 1ct)	
Measurement Frequency	128Hz or 256Hz (automatically selected)						
No-load Voltage	±10 V peak						
Maximum Test Current	20mA						
Measurement Mode	One shot or continuous						
Data Storage	-			Stores the 52%, 62% and 72% 3P resistance measurements			
Calculation	-			Calculates average and % deviation of the three saved readings			
GENERAL							
Display	Backlit LCD						
Measurement Mode	2P (Ω), 3P (Ω)			V, I, 2P (Ω), 3P (Ω)			
Power Supply	(6) AA Alkaline batteries			(6) NiMH rechargeable batteries, charging time approx. 6 hrs			
Battery Life	> 2,000 x 3P earth measurements at 100 Ω			>1,500 x 3P earth measurements at 100 Ω			
Dimensions	8.78 x 4.96 x 2.75" (223 x 126 x 70mm)						
SAFETY							
Safety Ratings	EMC: IEC 61326-1; IEC 61010-2-030 / 600 V CAT IV						

ACCESSORIES/REPLACEMENTS

Catalog #2135.44

Ground Rod – Set of (2) 17" Stainless Steel T-shaped Auxiliary Ground Electrodes

Catalog #2153.06

MN72 AC Current Probe (6424 only)

CATALOG #5000.92

Calibration Checker



CATALOG #5000.92



CATALOG #2153.06



KITS AVAILABLE
SHOWN: CATALOG #2135.35

CATALOG NO.	DESCRIPTION
2135.55	Ground Resistance Tester Model 6422 (Digital, 3-Point)
2135.56	Ground Resistance Tester Model 6422 Kit-150ft (Digital, 3-Point)
2135.57	Ground Resistance Tester Model 6424 (Digital, 3-Point)
2135.58	Ground Resistance Tester Model 6424 Kit-150ft (Digital, 3-Point)
2135.59	Ground Resistance Tester Model 6424 Kit-300ft (Digital, 3-Point)

www.aemc.com

United States & Canada

Chauvin Arnoux®, Inc.
d.b.a. AEMC® Instruments
200 Foxborough Blvd.
Foxborough, MA 02035 USA
Tel (508) 698-2115
Fax (508) 698-2118

Customer Support
Place orders, obtain prices
and delivery options
(800) 343-1391
customerservice@aemc.com

Sales & Marketing Department
sales@aemc.com
marketing@aemc.com

Repair & Calibration Service
repair@aemc.com

United States & Canada (continued)

**Technical & Product
Application Support**
(800) 343-1391
techinfo@aemc.com

Webmaster
Information regarding our website
www.aemc.com
webmaster@aemc.com

South America, Central America, Mexico & the Caribbean

Chauvin Arnoux®, Inc.
d.b.a. AEMC® Instruments
15 Faraday Drive
Dover, NH 03820 USA
export@aemc.com

Australia & New Zealand

Chauvin Arnoux®, Inc.
d.b.a. AEMC® Instruments
15 Faraday Drive
Dover, NH 03820 USA
export@aemc.com

All other countries

Chauvin Arnoux®
190, rue Championnet
75876 Paris Cedex 18, France
Tel 33 1 44 85 45 28
Fax 33 1 46 27 73 89
info@chauvin-arnoux.com
www.chauvin-arnoux.com



FAMILY of PRODUCTS

Visit our website at www.aemc.com

AEMC ONE SOURCE®
For All Your Electrical Test & Measurement Instruments

Call the AEMC® Instruments Technical Assistance Hotline for immediate consultation with an applications engineer: (800) 343-1391

Chauvin Arnoux®, Inc. d.b.a. AEMC® Instruments • 200 Foxborough Blvd. • Foxborough, MA 02035 USA • (800) 343-1391 • (508) 698-2115 • Fax (508) 698-2118
E-mail: sales@aemc.com | Export Department: (978) 526-7667 • Fax (978) 526-7605 • E-mail: export@aemc.com

950.BR_6422_6424_0420 • Printed in the USA