

PDS 62-SIN

Portable PD detection and localization system



- Partial discharge diagnostics with VLF sinusoidal voltage up to 62kVpeak
- With 15 kg – the lightest PD measuring unit on the market
- Real-time data evaluation and display of results, no post processing needed
- General and localized Phase Resolved PD pattern (PRPD) display for defect type recognition

DESCRIPTION:

Network operators can now get faster and significantly more reliable information about the quality and the condition of their cables. This thanks to the brand-new PDS 62-SIN PD detector. For the first time, it has become possible to immediately locate faults in underground cables during the actual PD measurement. The PDS 62-SIN has been designed for all Megger VLF Sinusoidal testers up to 62kVpeak.

Based on many years of field experience, customer demands and unique innovations, the PDS 62-SIN has been developed. This has been reflected in the PD detector software, it has never been easier to perform PD measurements; starting with real-time data analysis and display of results during the actual measurement, ending with the highest flexibility in creating customized reports.

Furthermore the PD detector software will support the user with the data evaluation by means of so called Phase Resolved Partial Discharge (PRPD) patterns. With help from these PRPD patterns the user is able to distinct between different types of PD defects, such as corona or internal PD. This is of major importance for partial discharges located at terminations; corona discharges are not problematic, whereas internal PD would.

With its weight of 15 kg only the PDS 62-SIN is the lightest PD measuring unit on the market. The PDS 62-SIN comes with all accessories needed to perform PD measurements, like the in-house and certified PD calibrator, Laptop and connection cables.

FEATURES

- High coupling capacity of 25nF
- Low weight of 15 kg only
- PD measurement acc. to IEC 60270
- Automatic bandwidth adaption
- Fully automatic calibration
- Real-time data evaluation and display of results
- General and localized PRPD display
- Monitored withstand testing
- Reporting per mouse-click

PDS 62-SIN
Portable PD detection and localization system

TECHNICAL DATA*

PDS 62-SIN

Voltage

Operating	max. 62kV _{peak}
Type	VLF sine wave (0.01Hz - 0.1Hz)
Capacity of HV coupling capacitor	25nF
Sensitivity range	2 pC ... >100 nC
PD self-noise level	< 2 pC
PD impulse repetition range	100 kHz

PD localization

Measuring range	0 ... 16,000 m v/2 = 80 m/μs
Propagation velocity v/2	50 ... 120 m/μs
Sampling rate	125 MHz (8 ns)
Bandwidth	3 / 20 MHz (switchable)
Accuracy	1% of the cable length
Resolution	± 1 pC / ± 1 m
Filtering	attachable HF filter (max. 1A)
Power supply	Via supplied power supply 90 ... 264 VAC, 50/60 Hz
Weight	15 kg
Dimensions (W x D x H)	36 x 33 x 64 cm
Temperature	
Operation	-20 °C ... 55 °C
Storage	-40 °C ... 70 °C
Relative humidity	93% at 30 °C (non-condensing)

PD calibrator

Pulse level	100pC, 200pC, 500pC, 1nC, 2nC, 5nC, 10nC, 20nC, 50nC, 100nC
Pulse frequency	50 Hz, 60 Hz, 100 Hz or via Light triggered sensor
Power supply	9-volt block battery
Weight	410 gr
Dimensions (W x D x H)	195 x 85 x 35 mm
Temperature	
Operating	-10 °C ... 50 °C
Storage	-30 °C ... 70 °C

SCOPE OF DELIVERY

- PDS 62-SIN PD coupler
- PDS 62-SIN accessoires in bag
- PD calibrator
- Laptop
- SW license incl. 3 hardware keys

ORDERING INFORMATION

Product	Order no.
PDS 62-SIN set consisting of:	
PDS 62-SIN PD coupler	1014867
PD calibrator 100 pC till 100 nC	2008807
PD software license main package (3 activations, 5 year duration)	1389
Mandatory selection lead set (1x)	
Lead set PDS 62-SIN "Standard"	2009829
Lead set PDS 62-SIN "NAFTA"	2011559
Mandatory selection preinstalled Notebook (1x)	
Notebook DE	2007127
Notebook EN	2007129
Other languages on request	
Optional HV connection cables:	
PDS 62 HV connection cable PD free + ground cable 3 m	2009832
PDS 62 HV connection cable PD free 5m	890010915
PDS 62 HV connection cable PD free 10m	890023555
PDS 62 HV connection cable PD free 15m	890015603
PDS 62 HV connection cable PD free 5m (NAFTA)	2012596
PDS 62 HV connection cable PD free 10 m (NAFTA)	2012597
PDS 62 HV connection cable PD free 15m (NAFTA)	2012598
Optional accessories:	
Diagnostic connection set	890017909
PD-free adapter TE PC-MC-UNI-L, long version (460 mm), incl. thread-adapter M16 to M12	1013564
PD-free adapter TE PC-MC-UNI-K, short version (310 mm), incl. thread-adapter M16 to M12	1013563
Transport case PDS 62-SIN	90023948

*The information in this document is subject to change without notice and should not be construed as a commitment by Megger Germany.
Megger Germany assumes no responsibility for any errors that may appear in this document.

SALES OFFICE

Megger Germany GmbH
Dr.-Herbert-Iann-Str. 6
96148 Baunach, Germany
T +49 9544 680
F +49 9544 2273
team.international@megger.com

PDS62-SIN_DS_EN_V04b

www.megger.com
ISO 9001

The word 'Megger' is a registered trademark

Megger [®]