

**MODEL NO. 150 "VARI-DAMP" PULSATION DAMPER**

**1 2 3 STANDARD MODELS SPECIFICATIONS**

① BASIC MODEL NO.	DESCRIPTION	② BODY MATERIAL	③ THREAD SIZE	WORKING PRESS (PSIG)	WEIGHT OZ./GRAMS
150-BH	MALE X FEMALE PIPE	BRASS	1/2" NPT	5,000	8/230
150-SH	MALE X FEMALE PIPE	316 S.S.	1/2" NPT	10,000	8/230
150-AO	MALE X FEMALE PIPE	ALUM	1/4" NPT	3,000	2/66
150-BO	MALE X FEMALE PIPE	BRASS	1/4" NPT	3,000	6/170
150-SO	MALE X FEMALE PIPE	316 S.S.	1/4" NPT	5,000	6/170

**FOR OTHER END CONFIGURATIONS PLEASE CONTACT FACTORY**

**4 SEALS**

- 0. Buna N O-Ring & Teflon® Back-Up Ring **(Standard)**
- 1. Viton O-Ring & Teflon® Back-Up Ring
- 2. Neoprene O-Ring & Teflon® Back-Up Ring
- 5. Ethylene Propylene O-Ring & Teflon® Back-Up Ring
- 9. Special (Uncoded Options)

**5 OPTIONS**

- 0. None
- 9. Special (Uncoded Options)

**PART NUMBERING SYSTEM**

