



# EXPLORER PLUS™

*Semi-Micro Balances*



## ***Engineered for Accuracy, Designed for Demanding Applications***

The new Explorer Plus (EXP Series) offers a premium weighing performance, compliance support and data traceability. The advanced features take the EXP to the next level by optimizing the user experience. This flagship balance is crafted to meet the most demanding requirements of modern scientific research.

### ***Unique Features:***

- Intelligent User Experience**

Seamless setup with motorized leveling, anti-pinch auto-doors, touchless sensors, ionizer and draftshield light. A 7-inch glass touchscreen, chemical protection and 2 customizable status lights.

- Supports Compliance for Data Traceability**

Ensure compliance with 4-level user system, password protection, and 100k internal system log. The time synchronization NTP function confirms data traceability to meet pharmaceutical regulations.

- Effortless System Integration**

Advanced communication capabilities with straightforward integration to Laboratory Information Management Systems (LIMS), and hassle-free data transfer with driverless HID for easy data input.

# EXPLORER PLUS™ Semi-Micro Balances



## Specifications



Model	EXP125D/AD	EXP125/AD	EXP225D/AD	EXP225/AD
Capacity	82 g / 120 g	120 g	120 g / 220 g	220 g
Readability d, Fine Range	0.01 mg	0.01 mg	0.01 mg	0.01 mg
Readability d, Full Range	0.1 mg	0.01 mg	0.1 mg	0.01 mg
Repeatability (sd.), ≤5% of Full Load Typical	0.01 mg	0.01 mg	0.01 mg	0.01 mg
Repeatability (sd.), 5% of Full Load to Fine Range Max	0.02 mg	0.02 mg	0.02 mg	0.02 mg
Repeatability (sd.), Fine Range Max to Full Range	0.1 mg	0.02 mg	0.1 mg	0.02 mg
Linearity Deviation Typical	0.06 mg	0.06 mg	0.06 mg	0.06 mg
Linearity Deviation	0.2 mg	0.1 mg	0.2 mg	0.1 mg
Span Calibration Points	25g, 50g, 75g, 100g		50g, 100g, 150g, 200g	
Weighing Units		g, mg, ct, N, oz, ozt, Grain, dwt, mo, msg, tcl, tola, baht, Custom 1, Custom 2		
Applications		Basic Weighing, Parts Counting, Check Counting, Percent Weighing, Check Weighing, Dynamic Weighing, Totalization, Formulation, Differential, Density Determination, Peak Hold, Pipette Adjustment, SQC, Fill Weight Variation, Flow Rate Control		
Stabilization Time (typical)		0.1 mg: ≤2 seconds, 0.01 mg: ≤ 5 seconds		
Sensitivity Temperature Drift (ppm/°C)		0.8		
Min-Weight (typical) (K=2, U=1%)		2 mg		
Min-Weight (typical) (USP, K=2, U=0.10%)		20 mg		
Min-Weight (optimal) (USP, K=2, U=0.10%, SRP≤0.41d)		8.2 mg		
Terminal Display		7-inch TFT 16.7M Color Touch Screen with Glass Overlay, Detachable Terminal		
Display Resolution		800 x 480 Pixels		
Communication		USB Host (Type A) x 2, USB Device (Type B) x 1, USB Device (Type C) x 1 Ethernet (RJ45) x 1, RS232 x 1; Optional Wi-Fi, Bluetooth Dongle		
Leveling System		Motorized Leveling System with Digital Leveling Bubble		
Power Supply		AC Adapter Input: 100-240 VAC 0.5A 50-60 Hz AC Adapter Output: 12 VDC 1.5A		
Weighing Pan Size		Aero Pan 80mm x 80mm		
Built-in Ionizer		Standard		
Environmental Sensor (Load Cell)		Temperature Sensor, Relative Humidity Sensor (RH), Air Pressure Sensor		
Touchless Sensor		2 Touchless Sensors on the terminal		
Draftshield with anti-static coating		Standard		
Automatic Draftshield Door Function		Standard, Open Range: 1/2 open and fully open		
Draftshield & Terminal Status Lights		Standard, 7-color Selectable		
Sample Spotlight		Standard, White		
Terminal Housing Dimensions (W x D x H)		205mm x 126mm x 66mm		
Base Housing Dimensions (W x D x H)		229mm x 275mm x 78mm		
Assembled Dimensions (W x D x H)		229mm x 408mm x 372mm		
Shipping Dimensions (W x D x H)		415mm x 630mm x 561mm		
Net Weight		7.8 kg		
Shipping Weight		12.0 kg		

# EXPLORER PLUS™ Semi-Micro Balances

## Outline Dimensions



## Approvals

- **Product Safety:** IEC/EN 61010-1; CAN/CSA C22.2 61010-1; UL 61010-1
- **Electromagnetic Compatibility:** IEC/EN 61326-1 Class B, Basic Environments; FCC Part 15 Class A; Canada ICES-003 Class A

# EXPLORER PLUS™ Semi-Micro Balances

## Accessories

	Item No.	30944360
	Accessory Name	Bluetooth Printer, Impact, SF40A/BT
	Item No.	30064203
	Accessory Name	Printer, Impact, SF40A
	Item No.	31059238
	Accessory Name	Fingerprint scanner FIN-100A
	Item No.	31059239
	Accessory Name	BT dongle and Wi-Fi dongle LM842
	Item No.	30130302
	Accessory Name	Static Ionizer, ION-100A
	Item No.	31059237
	Accessory Name	Weighing Kit
	Item No.	80253384
	Accessory Name	Density Kit, Solids
	Item No.	83034024
	Accessory Name	Sinker, Glass, Liquid, Density Kit
	Item No.	30252145
	Accessory Name	Pipette Evaporation Trap
	Item No.	30078078
	Accessory Name	Terminal Extension Cable, RS422, 9 m
	Item No.	12120799
	Accessory Name	SF40A Paper roll (57,5mm 2pcs)
	Item No.	30529322
	Accessory Name	SF40A Ink Ribbon Cassette