

LIFTING JACKS

HJ Series Hand Jacks

SIMPLEX



Capacity Range▶ 2 - 100 tons
Stroke Range▶ 2.44 - 5.91 in.
Weight▶ 7.9 - 191.8 lbs.

- ▶ Thick base material with large area for increased strength and stability during lifting.
- ▶ High strength beam and pump linkage for long life.
- ▶ Safety relief valve to prevent overload.
- ▶ All models include over-travel protection.
- ▶ Lever Bar included on all models.

HJ2A, HJ3A and HJ8A Family Shown

SCREW EXTENSIONS

Two through 22-ton models include screw extensions with cleated saddle for quick setup.



LEVER BARS

All Hand Jacks come equipped with a 3 piece Lever Bar set to accommodate space limitations.



Various applications are suitable for the hydraulic HJ Series hand Jack, ranging from spreading, leveling, lifting and holding. ▼



Lifting Jacks

Model	Capacity (tons)	Stroke (in)	Minimum Height (in)	Extended Screw Height (in)	Maximum Height (in)	Base Area (in)	Piston Diameter (in)	Maximum Handle Effort (lbs)	Weight (lbs)
HJ2A	2	3.94	6.30	1.97	12.20	3.74 X 4.37	0.83	82	7.9
HJ3A	3	4.13	6.61	2.56	13.31	3.74 X 4.57	0.94	108	9.0
HJ5A	5	5.91	8.35	2.95	17.20	3.74 X 4.84	1.14	95	11.0
HJ8A	8	5.91	8.62	2.95	17.48	3.74 X 5.43	1.29	86	13.0
HJ11A	11	5.91	8.62	2.95	17.48	3.74 X 5.59	1.47	106	14.3
HJ11ALP	11	2.44	5.16	1.18	8.78	3.74 X 5.59	1.47	106	12.1
HJ22A	22	5.91	9.21	2.95	18.07	5.00 X 6.73	2.00	108	26.7
HJ22ALP	22	4.13	7.48	2.17	13.78	5.00 X 6.73	2.00	108	22.0
HJ35A	35	5.91	9.68	*	15.59	7.09 X 8.44	2.75	97	51.81
HJ55A	55	5.91	9.92	*	15.83	7.09 X 9.06	3.15	104	62.8
HJ100A	100	5.91	11.81	*	17.72	11.65 X 13.11	4.33	71	191.8